



Australian Government
Department of Defence

VISITS BY NUCLEAR POWERED WARSHIPS
TO AUSTRALIAN PORTS

Report on Radiation Monitoring During 2020

Canberra, Australia
2021

FOREWORD

1. This publication has been prepared for the Australian Department of Defence in consultation with the appropriate Commonwealth departments through the standing inter-departmental committee, the Visiting Ships' Panel (Nuclear).

CJ LAWRENCE, AM
Rear Admiral, RAN
Chairman,
Visiting Ships' Panel (Nuclear)

February 2021

CONTENTS

FOREWORD		Page
CONTENTS		ii
SUMMARY		iii
		v
PART I	GENERAL	Paragraph
	INTRODUCTION	1
	RADIATION MONITORING PROGRAM	
	Environmental Monitoring	5
	Internal Radiation	7
	External Radiation	9
	Passive Dosimeters	10
	Direct Radiation Monitoring	11
	PROGRAM IMPLEMENTATION	
	The Monitoring Program	12
	Contingency Arrangements	15
PART II	NUCLEAR POWERED WARSHIP VISITS IN 2020	
	HMAS STIRLING, WESTERN AUSTRALIA	
	Visit by USS TEXAS	16
	Radiation Monitoring	17
	Results	18
	Visit by FNS EMERAUDE	21
	Radiation Monitoring	22
	Results	23
PART III	MARINE ENVIRONMENTAL SAMPLING	
	Measurement Method	26
	Detection Capability	27

SUMMARY

Two Nuclear Powered Warship (NPW) visits were made to Australian ports in 2020. The visits were made by ships of the United States and French Navy. Details of the visits are as follows:

Port	Ship	Visit Dates
HMAS STIRLING	USS TEXAS	30 Jan – 04 February 2020
	FNS EMERAUDE	09-14 November 2020
Total Visit Days	10	

The Commonwealth Government requires that a radiation-monitoring program be carried out in association with each visit to detect any release of radioactivity to the ports and their environs.

This report presents a summary of the objectives and requirements of the NPW radiation-monitoring program, describes the implementation of the program for the visit during 2020 and records the results of radiation measurements taken in the ports visited.

No releases of radioactive material were detected, nor were any radiation levels recorded in excess of normal background levels of ionising radiation, either during or subsequent to these visits.

PART I – GENERAL

INTRODUCTION

1. The Commonwealth Government requires that a radiation-monitoring program be carried out in association with such visits to detect any release of radioactivity to the ports or their environs or any increase in external radiation levels above those due to natural background radiation.
2. This report presents a summary of the objectives and requirements of the Nuclear Powered Warships (NPW) radiation monitoring program, describes the implementation of the program for the visits during 2020 and records the results of radiation measurements taken.

THE RADIATION MONITORING PROGRAM

3. The requirements for the monitoring program are laid down in ‘Environmental Radiation Monitoring during Visits of Nuclear Powered Warships to Australian Ports - Requirements, Arrangements and Procedures’, Department of Defence, September 2003.
4. The monitoring program has two main components:
 - (a) environmental monitoring, is designed to detect the release of any radioactive material (e.g. waste) to the environment; and
 - (b) direct radiation monitoring is designed to provide warning of any malfunction of the reactor of an NPW while in port, which might lead to a release of radioactivity.

Environmental Monitoring

5. The environmental radiation-monitoring program is intended to provide assurance that there has been no infringement of Australian public health standards attributable to the release of radioactive material from the waste control and retention systems of a visiting NPW.
6. The relevant Australian public health standards and guides are those published in the Radiation Protection Series (RPS) by the Australian Radiation Protection and Nuclear Safety Agency. Of particular relevance to NPW visits are Code for Radiation Protection in Planned Exposure Situations (RPS C-1); Guide for Radiation Protection in Existing Exposure Situations (2017RPS G-2); Guide for radiation Protection in Emergency Exposure Situations (RPS G-3) . These guides relate to permissible ionising radiation doses received by individuals from both external radiation sources and from the intake of radionuclides in air, water and foodstuffs during and post-accident.
7. A marine environmental monitoring program is implemented to determine the potential for exposure to people and the environment due to the release of radionuclides into the marine environment. The monitoring technique is used to extract, and quantify radiocaesium (caesium-137 and caesium-134), from the seawater in the vicinity of approved berths and anchorages. The radiocaesium is concentrated, onto chemically coated filter cartridges, using an in-situ caesium extraction unit.

8. These samples are analysed for evidence of radiocaesium known to characterise the radioactive waste likely to be held in a NPW. Low levels of caesium-137 are present in the marine environment as a result of global fallout. Background levels of caesium-137 in Australian waters range from 0.7 to 1.4 mBq/L. These samples are analysed for evidence of I-131 and Cs-137 cobalt-60 and other artificial fission products that are present in a nuclear reactor accident release and any radioactive waste likely gamma ray emitting radionuclides known to characterise the radioactive waste likely to be held in a NPW.

9. **External radiation.** When a NPW is at an alongside berth, gamma radiation surveys are undertaken at the wharf in those areas in the vicinity of the vessel designated as free for access by the public or by port employees. Surveys are made initially on the vessel's arrival and periodically thereafter for the duration of the visit using fixed gamma monitors and portable dose rate meters capable of measuring ionising radiation dose rates from 0.01 $\mu\text{Sv/h}$ to 10's of mSv/h

10. **Passive dosimeters.** In order to record the accumulated ionising radiation doses that might be received in the port environs following an accidental release of airborne radioactivity, a number of passive dosimeters (OSL) are placed at selected locations. The OSL remain in position during the period that a NPW is in port or, in the event of an accident, would remain in position until the termination of the accident. Control OSL are kept at the Australian Radiation Protection and Nuclear Safety Agency's (ARPANSA) laboratory in Melbourne and also in the port being visited, but remote from the NPW to provide a comparison with the OSL placed in the field. At the completion of a visit, field and control OSL are returned to ARPANSA for dose assessment.

Direct Radiation Monitoring

11. In order to provide early warning of a NPW reactor malfunction at an alongside berth, fixed radiation detectors are located in the vicinity of the vessel to provide continuous monitoring of gamma radiation levels. The systems have multiple radiation detectors that cover the range of 10 nSv/h to 10 Sv/h, are solar powered with a battery backup and provide remote telemetry transmitted via the cellular network and a backup satellite communication pathway. The alarm is set to trigger at a level of 1 $\mu\text{Sv/h}$. A significant release of radioactivity into the interior of the vessel from the reactor would be detected and initiate an alarm.

PROGRAM IMPLEMENTATION

The Monitoring Program

12. Radiation Monitoring groups, which consist of members from the Australian Nuclear Science and Technology Organisation (ANSTO), the Health and Environmental authorities of the host State or Territory and the Royal Australian Navy (RAN) undertake the external radiation-monitoring program. The composition of the groups varies in different ports; however, the Leader of the Radiation Monitoring Group is always a Senior Health Physicist from ANSTO.

13. The marine environmental monitoring program is a joint undertaking by the ARPANSA Radiation Health Services and either the State concerned or, where the berth is in a naval establishment, the RAN. The collection of samples is carried out by State authorities or by the RAN, at approved berths and anchorages. The analysis and measurement of samples is undertaken by ARPANSA. Details of the measurement method and detection capability are presented in Part III.

14. The routine sampling program may be discontinued at NPW berths and anchorages which are visited infrequently or where an adequate baseline has been established.

Contingency Arrangements

15. Port safety organisations have been established at all ports approved for NPW visits and arrangements made so that in the event of a reactor accident they would be activated immediately. Simultaneously, Commonwealth officers would initiate radiation surveys in order to identify any radiation hazards. Prior to each visit, the Port Safety Organisation is brought to a state of readiness and briefings are conducted to familiarise key participants with the operational procedures and the tasks required of them in the event of an accident. Normally, an exercise is conducted prior to an NPW visit involving key members of the Port Safety Organisation and key Commonwealth agencies who provide support during a visit.

PART II - NUCLEAR POWERED WARSHIP VISITS IN 2020

HMAS STIRLING, WESTERN AUSTRALIA

Visit by USS TEXAS

16. USS TEXAS (SSN775) nuclear powered *Virginia* class submarines of the US Navy visited HMAS STIRLING 30 Jan – 04 Feb 20.

Radiation Monitoring

17. Throughout the visit gamma radiation levels were monitored in the vicinity of the vessel using fixed radiation detectors. Operation of the detectors commenced before the vessel's arrival and continued until its departure. Measurements were displayed and recorded on equipment located in the Emergency Operations Centre which was manned continuously. In addition, measurements of gamma radiation levels were taken daily using hand-held dose rate meters in those areas around the vessel which were accessible to personnel on the base.

Results

18. The gamma radiation dose rates measured by monitoring equipment during the visit were between 0.08 and 0.11 $\mu\text{Sv/h}$ for the fixed system and between 0.1 and 0.3 $\mu\text{Sv/h}$ for the portable systems, indicating that there was no observable increase in the external gamma radiation level above background.

19. The activity concentration in the post-visit seawater sample was 1.10 ± 0.14 mBq/L for Caesium-137 and below the minimum detectable activity concentration for Caesium-134. The results indicate there was no release of radionuclides to the marine environment.

20. The dose received by passive dosimeters at all locations were below the minimum reportable dose.

HMAS STIRLING, WESTERN AUSTRALIA

Visit by FNS EMERAUDE

21. FNS EMERAUDE (S604) nuclear powered *Rubis Amethyste* class submarine of the French Navy visited HMAS STIRLING 09 – 14 Nov 20.

Radiation Monitoring

22. Throughout the visit gamma radiation levels were monitored in the vicinity of the vessel using fixed radiation detectors. Operation of the detectors commenced before the vessel's arrival and continued until its departure. Measurements were displayed and recorded on equipment located in a caravan located on the wharf which was manned continuously.

Results

23. The gamma radiation dose rates measured by monitoring equipment during the visit were between 0.08 and 0.11 $\mu\text{Sv/h}$ for the fixed system and between 0.1 and 0.3 $\mu\text{Sv/h}$ for the portable systems, indicating that there was no observable increase in the external gamma radiation level above background.

24. The activity concentration in the post-visit seawater sample was 1.23 ± 0.13 mBq/L for Caesium-137 and below the minimum detectable activity concentration for Caesium-134. The results indicate there was no release of radionuclides to the marine environment.

25. The dose received by passive dosimeters at all locations were below the minimum reportable dose.

PART III - MARINE ENVIRONMENTAL SAMPLING

Measurement Method

26. Seawater is sampled from the site of the visiting ship and pumped through a series of filter cartridges. The coated cartridges, containing the extracted radiocaesium, undergo laboratory pre-treatment which includes drying, ashing and homogenisation, prior to measurement using high resolution gamma spectrometry.

Detection Capability

27. The detection limit for the radiocaesium (based on a 24 hour count time) is better than 0.2 mBq/L. This monitoring approach will provide the means to determine if there have been any releases from the NPW to the marine environment.