



Australian Government
**Australian Radiation Protection
and Nuclear Safety Agency**



Code for the Safe Transport of Radioactive Material

Radiation Protection Series C-2 (Rev. 1)



Radiation Protection Series

The Australian Radiation Protection and Nuclear Safety Agency (ARPANSA) publishes Fundamentals, Codes and Guides in the Radiation Protection Series (RPS), which promote national policies and practices that protect human health and the environment from harmful effects of radiation. ARPANSA develops these publications jointly with state and territory regulators through the Radiation Health Committee (RHC), which oversees the preparation of draft policies and standards with the view of their uniform implementation in all Australian jurisdictions. Following agreement, the CEO of ARPANSA will seek the endorsement of the Radiation Health and Safety Advisory Council, and publish the document.

To the extent possible and relevant for Australian circumstances, the RPS publications give effect in Australia to international standards and guidance. The sources of such standards and guidance are varied and include the International Commission on Radiological Protection (ICRP); the International Commission on Non-Ionizing Radiation Protection (ICNIRP); the International Atomic Energy Agency (IAEA); and the World Health Organization (WHO).

Fundamentals set the fundamental principles for radiation protection and describe the fundamental radiation protection, safety and security objectives. They are written in an explanatory and non-regulatory style and describe the basic concepts and objectives of international best practice.

Codes are regulatory in style and may be referenced by regulations or conditions of authorisation. They contain either general safety or security requirements which may be applicable for all dealings with radiation, or practice-specific requirements. They provide overarching requirements and are expressed as 'must' statements which are to be satisfied to ensure an acceptable level of safety and/or security.

Guides provide recommendations and guidance on how to comply with the Codes or apply the principles of the Fundamentals. They are written in an explanatory and non-regulatory style and indicate the measures recommended to provide good practice. They are generally expressed as 'should' statements.

These three categories of publications are informed by public comment during drafting and are subject to a process of assessment of regulatory impact.

All ARPANSA publications (including earlier editions of codes and guides for which ARPANSA is now responsible) are available in electronic format, and can be downloaded free of charge by visiting ARPANSA's website at <https://www.arpansa.gov.au/regulation-and-licensing/regulatory-publications/radiation-protection-series>.

Further information can be obtained by telephoning ARPANSA on 1800 022 333 (free call within Australia) or +61 (03) 9433 2211.



Australian Government
Australian Radiation Protection
and Nuclear Safety Agency



Code for the Safe Transport of Radioactive Material

Radiation Protection Series C-2 (Rev. 1)

March 2019

*This publication was prepared jointly with the Radiation
Health Committee. The Radiation Health and Safety Advisory
Council advised the CEO to adopt this Code*

© Commonwealth of Australia 2019

This publication is protected by copyright. Copyright (and any other intellectual property rights, if any) in this publication is owned by the Commonwealth of Australia as represented by the Australian Radiation Protection and Nuclear Safety Agency (ARPANSA).

ISBN 978-0-6483704-4-4

ISSN 1445-9760



Creative Commons

With the exception of the Commonwealth Coat of Arms, any ARPANSA logos and any content that is marked as being third party material, this publication, *Code for the Safe Transport of Radioactive Material (2019)*, by the Australian Radiation Protection and Nuclear Safety Agency is licensed under a Creative Commons Attribution 3.0 Australia licence (to view a copy of the licence, visit <http://creativecommons.org/licenses/by/3.0/au>). It is a further condition of the licence that any numerical data referred to in this publication may not be changed. To the extent that copyright subsists in a third party, permission will be required from the third party to reuse the material.

In essence, you are free to copy, communicate and adapt the material as long as you attribute the work to ARPANSA and abide by the other licence terms. The works are to be attributed to the Commonwealth as follows:-

“© Commonwealth of Australia 2019, as represented by the Australian Radiation Protection and Nuclear Safety Agency (ARPANSA)”

The publication should be attributed as: Code for the Safe Transport of Radioactive Material (2019).

Use of the Coat of Arms

The terms under which the Coat of Arms can be used are detailed on the Department of the Prime Minister and Cabinet website (www.dpmc.gov.au/government/commonwealth-coat-arms).

Enquiries regarding the licence and any use of this report are welcome.

ARPANSA
619 Lower Plenty Road
YALLAMBIE VIC 3085
Tel: 1800 022 333 (Free call) or +61 3 9433 2211

Email: info@arpansa.gov.au
Website: www.arpansa.gov.au

ARPANSA's purpose is to protect the Australian people and the environment from the harmful effects of radiation, through understanding risks, best practice regulation, research, policy, services, partnerships and engaging with the community.

Published by the Chief Executive Officer of ARPANSA in 2019.

Acknowledgement of Country

ARPANSA respectfully acknowledges Australia's Aboriginal and Torres Strait Islander communities and their rich culture and pays respect to their Elders past and present. We acknowledge Aboriginal and Torres Strait Islander peoples as Australia's first peoples and as the Traditional Owners and custodians of the land and water on which we rely.

We recognise and value the ongoing contribution of Aboriginal and Torres Strait Islander peoples and communities to Australian life and how this enriches us. We embrace the spirit of reconciliation, working towards the equality of outcomes and ensuring an equal voice.

Foreword

The safe transport of radioactive material in Australia is based on international requirements published by the International Atomic Energy Agency (IAEA). The Australian *Code for the Safe Transport of Radioactive Material (RPS C-2)* adopts the IAEA's Specific Safety Requirements No. SSR-6 Regulations for the Safe Transport of Radioactive Material. The Code establishes requirements for adoption by the Commonwealth, the States and the Territories that will maintain a system for safe transport of radioactive material by road and rail, and by waterways other than those subject to the *Navigation Act 2012*.

In 2018, the IAEA published Revision 1 of SSR-6.

The Radiation Health Committee, established under the *Australian Radiation Protection and Nuclear Safety Act 1998*, decided to revise RPS C-2 and incorporate Revision 1 of SSR-6. This is the 2019 Edition of the RPS Code. Previous editions were published in 2001, 2008 and 2014.

The main changes from the 2014 Edition of RPS C-2 are related to: inclusion of a new group of Surface Contaminated Objects (SCO-III); further clarification of requirements for consignor and carrier related to arrangements for emergency preparedness and response; inclusion of values for seven radionuclides (Ba-135m, Ge-69, Ir-193m, Ni-57, Sr-83, Tb-149 and Tb-161) in Table 2 of the Code; emphasis on the maintenance of any package that is transported following storage; and requirements for ageing management. Furthermore, an additional requirement related to the endorsement of overseas package design by the Australian competent authority for Type B(U) and Type C package has been added. Other changes are machinery, editorial or clarifying in nature.

It is expected that the changes will have little or no cost to industry.

Australian stakeholders were consulted in 2016 during finalisation of Revision 1 of IAEA SSR-6. All Australian comments were editorial in nature. The final document was approved by the Radiation Health Committee in January 2019 out-of-session for adoption in Australia as RPS C-2, Revision 1. The Radiation Health and Safety Advisory Council advised the CEO to adopt the Code in March 2019.

It is expected that the Code will be further revised and updated from time to time to ensure that it continues to provide the highest standards of safety and protection.

Carl-Magnus Larsson
CEO of ARPANSA

Contents

Foreword..... i

Contents..... ii

1. Introduction iv

1.1 Citation iv

1.2 Background..... iv

1.3 Purpose iv

1.4 Scope iv

1.5 Structure..... iv

2. Modification and clarifications to SSR-6, Rev.1, as adopted in RPS C-2 (Rev.1) v

3. Additional requirements..... vi

Schedule A..... vii

Schedule B – Competent authorities 166

Table B1: List of Australian Competent Authorities for the purpose of this Code..... 166

Table B2: Australian Competent Authority for the transport of radioactive material by air or sea ... 168

(This page intentionally left blank)

1. Introduction

1.1 Citation

This Code may be cited as the *Transport Code (2019)*.

1.2 Background

This Code replaces the *Code for the Safe Transport of Radioactive Material (2014)* and adopts the International Atomic Energy Agency Specific Safety Requirements No. SSR 6, Rev. 1 Regulations for the Safe Transport of Radioactive Material 2018 Edition (SSR-6, Rev. 1).

The transport of radioactive material by any person, organisation or government must comply with the radiation safety legislation of the State, Territory or Commonwealth jurisdiction through which the radioactive material is transported.

1.3 Purpose

This Code is intended to establish national uniformity for the requirements for the transport of radioactive material in Australia.

1.4 Scope

This Code applies to the transport of radioactive material by:

- a) road
- b) rail
- c) waterways under the jurisdiction of States and Territories in Australia.

Details of the relevant Australian competent authorities regulating transport of radioactive materials by air or sea can be found in Table B2 of Schedule B.

1.5 Structure

Section 2 includes modifications and clarifications for Australian circumstances to SSR-6, Rev. 1.

Section 3 includes additional requirements in the Transport Code (2019).

Schedule A of this Code incorporates the SSR-6, Rev. 1, written in regulatory format.

Schedule B contains a list of Australian competent authorities for the Transport of Radioactive Material.

2. Modification and clarifications to SSR-6, Rev.1, as adopted in RPS C-2 (Rev.1)

- 2.1 A person must not transport radioactive material by road, rail or waterways (other than those subject to the *Navigation Act 2012*) unless that person does so in accordance with the SSR-6, Rev. 1 as modified and clarified by Clauses 2.2-2.10 of this Code.
- 2.2 *Competent authorities* for the purpose of:
- a) this Code, are those listed in Table B1 of Schedule B, as amended from time to time;
 - b) transport by air or sea, are those listed in Table B2 of Schedule B, as amended from time to time.
- 2.3 The ‘relevant transport regulations for dangerous goods’ referred to in paragraph 110 of the SSR-6, Rev. 1 are the regulations of Australian States, Territories and the Commonwealth for the transport of dangerous goods by road and rail which are based upon the *Australian Code for the Transport of Dangerous Goods by Road & Rail 2018* (ADG7.6) or the current version of the Australian Dangerous Goods Code (ADG).
- 2.4 Where there is a conflict between the requirements of this Code and ADG7.6 in relation to the transport of radioactive material by road and rail, the provisions of this Code prevail.
- 2.5 Paragraph 308 of the SSR-6, Rev. 1 is replaced by:
- The relevant *competent authority* may impose requirements to ensure that radiation protection measures comply with the requirements in RPS C-1¹.
- 2.6 In paragraph 562 of the SSR-6, Rev. 1 the word ‘dose’ is taken to mean ‘effective dose’.
- 2.7 The limits in relation to U (natural) and Th (natural) are to be applied to the parent radionuclide i.e. U-238 and Th-232 respectively.
- 2.8 The paragraphs of SSR-6, Rev. 1 to be complied with by consignors are:
- 109-110, 301-306, 309-315, 401-434, 501-511, 514, 515(a)-(b), 516-562, 566 568, 570-573, 575-576, 601-686, 701-737, 801-803, 805, 807(a)-(c), 808-809, 811 812, 814-815, 817, 819-825, 827-827A, 829-830.
- 2.9 The paragraphs of SSR-6, Rev. 1 to be complied with by carriers are:
- 109-110, 301-306, 309-315, 504-514, 520, 522-525, 529(c), 537-540, 543 544, 562-579, 583-588, 627-630.
- 2.10 The default values given in paragraphs 523(a) and (b) of SSR-6, Rev. 1, where used instead of actual measurements, may require transport under exclusive use in accordance with paragraph 526 of the SSR-6, Rev. 1².

¹ *Code for Radiation Protection in Planned Exposure Situations* (RPS C-1) (ARPANSA 2016)

² Where the provisions of clause 2.10 of this Code causes difficulty, the relevant *competent authority* should be contacted.

3. Additional requirements

The following new paragraph is included in the Transport Code (2019)

808A. Each *Type B(U)* and *Type C* overseas package design shall require validation from the Australian *competent authority*.

This paragraph shall precede paragraph 809 in the *Transport Code (2019)*.

Schedule A

This is a reproduction of

REGULATIONS FOR THE SAFE TRANSPORT OF RADIOACTIVE MATERIAL

2018 Edition

IAEA Specific Safety Requirements No. SSR-6 (Rev. 1)

© INTERNATIONAL ATOMIC ENERGY AGENCY, VIENNA, 2018

The authentic version of this material is the version distributed by the IAEA or on behalf of the IAEA by duly authorised persons. The IAEA makes no warranty and assumes no responsibility for the accuracy or quality or authenticity or workmanship of this reproduction and its publication and accepts no liability for any loss or damage consequential or otherwise howsoever caused arising directly or indirectly for any use thereof whatsoever and to whomsoever.

COPYRIGHT NOTICE: Permission to reproduce or translate the information contained in this publication may be obtained by writing to the International Atomic Energy Agency, Vienna International Centre, P.O. Box 100, A-1400 Vienna, Austria.

The following pages of this document are a full version of the IAEA's Specific Safety Requirements No. SSR 6, Rev. 1 Regulations for the Safe Transport of Radioactive Material 2018 Edition and described above. This is the version for adoption in Australia for regulatory purposes. The IAEA reviews its Transport Regulations from time to time. The latest version can be found via the following link:

https://www-pub.iaea.org/MTCD/Publications/PDF/PUB1798_web.pdf

NOT FOR RESALE

IAEA SAFETY STANDARDS SERIES No. SSR-6 (Rev. 1)

REGULATIONS FOR THE SAFE TRANSPORT OF RADIOACTIVE MATERIAL

2018 EDITION

SPECIFIC SAFETY REQUIREMENTS

This Safety Requirements publication includes
a CD-ROM containing the IAEA Safety Glossary:
2007 Edition (2007) and the Fundamental Safety Principles (2006),
each in Arabic, Chinese, English, French, Russian and Spanish versions.
The CD-ROM is also available for purchase separately.
See: www.iaea.org/books

INTERNATIONAL ATOMIC ENERGY AGENCY
VIENNA, 2018

COPYRIGHT NOTICE

All IAEA scientific and technical publications are protected by the terms of the Universal Copyright Convention as adopted in 1952 (Berne) and as revised in 1972 (Paris). The copyright has since been extended by the World Intellectual Property Organization (Geneva) to include electronic and virtual intellectual property. Permission to use whole or parts of texts contained in IAEA publications in printed or electronic form must be obtained and is usually subject to royalty agreements. Proposals for non-commercial reproductions and translations are welcomed and considered on a case-by-case basis. Enquiries should be addressed to the IAEA Publishing Section at:

Marketing and Sales Unit, Publishing Section
International Atomic Energy Agency
Vienna International Centre
PO Box 100
1400 Vienna, Austria
fax: +43 1 26007 22529
tel.: +43 1 2600 22417
email: sales.publications@iaea.org
www.iaea.org/books

© IAEA, 2018

Printed by the IAEA in Austria

June 2018

STI/PUB/1798

IAEA Library Cataloguing in Publication Data

Names: International Atomic Energy Agency.

Title: Regulations for the safe transport of radioactive material, 2018 edition / International Atomic Energy Agency.

Description: Vienna : International Atomic Energy Agency, 2018. | Series: IAEA safety standards series, ISSN 1020-525X ; no. SSR-6 (Rev. 1) | Includes bibliographical references.

Identifiers: IAEAL 18-01161 | ISBN 978-92-0-107917-6 (paperback : alk. paper)

Subjects: LCSH: Radioactive substances — Safety regulations. | Radioactive substances — Transportation. | Radioactive substances — Law and legislation.

Classification: UDC 656.073 | STI/PUB/1798

FOREWORD

by Yukiya Amano
Director General

The IAEA's Statute authorizes the Agency to "establish or adopt... standards of safety for protection of health and minimization of danger to life and property" — standards that the IAEA must use in its own operations, and which States can apply by means of their regulatory provisions for nuclear and radiation safety. The IAEA does this in consultation with the competent organs of the United Nations and with the specialized agencies concerned. A comprehensive set of high quality standards under regular review is a key element of a stable and sustainable global safety regime, as is the IAEA's assistance in their application.

The IAEA commenced its safety standards programme in 1958. The emphasis placed on quality, fitness for purpose and continuous improvement has led to the widespread use of the IAEA standards throughout the world. The Safety Standards Series now includes unified Fundamental Safety Principles, which represent an international consensus on what must constitute a high level of protection and safety. With the strong support of the Commission on Safety Standards, the IAEA is working to promote the global acceptance and use of its standards.

Standards are only effective if they are properly applied in practice. The IAEA's safety services encompass design, siting and engineering safety, operational safety, radiation safety, safe transport of radioactive material and safe management of radioactive waste, as well as governmental organization, regulatory matters and safety culture in organizations. These safety services assist Member States in the application of the standards and enable valuable experience and insights to be shared.

Regulating safety is a national responsibility, and many States have decided to adopt the IAEA's standards for use in their national regulations. For parties to the various international safety conventions, IAEA standards provide a consistent, reliable means of ensuring the effective fulfilment of obligations under the conventions. The standards are also applied by regulatory bodies and operators around the world to enhance safety in nuclear power generation and in nuclear applications in medicine, industry, agriculture and research.

Safety is not an end in itself but a prerequisite for the purpose of the protection of people in all States and of the environment — now and in the future. The risks associated with ionizing radiation must be assessed and controlled without unduly limiting the contribution of nuclear energy to equitable and sustainable development. Governments, regulatory bodies and operators everywhere must ensure that nuclear material and radiation sources are used beneficially, safely and ethically. The IAEA safety standards are designed to facilitate this, and I encourage all Member States to make use of them.

PREFACE

This publication is a revision of IAEA Safety Standards Series No. SSR-6, Regulations for the Safe Transport of Radioactive Material, 2012 Edition. The revision was undertaken by amending, adding and/or deleting specific paragraphs. The paragraph numbering system used for the revision is as follows:

- (1) Amended paragraphs retain their original paragraph number. A list of amended paragraphs is given in the table below. As part of the revision process, some minor modifications of an editorial nature may have also been made. Editorial changes are not considered to be amendments to this publication and are not included in the table.
- (2) New paragraphs are indicated by using the number of the preceding paragraph with the addition of an uppercase letter. This numbering system is used only to indicate the location of new paragraphs within the text; it is not intended to imply a link between the paragraphs. A list of all new paragraphs in this publication is given in the table below.
- (3) Where a paragraph has been deleted, the paragraph number is retained together with an explanatory comment. A list of all deleted paragraphs in this publication is given in the table below.

Summary of changed paragraphs in this publication	
Amended paragraphs	101, 102, 104, 244, 304, 305, 309, 409, 411, 413, 414, 423, 424, 427, 503, 509, 510, 513, 514, 515, 516, 517, 520, 522, 523, 524, 527, 528, 529, 540, 543, 546, 566, 571, 572, 573, 575, 579, 605, 617, 622, 624, 626, 627, 628, 629, 630, 648, 659, 671, 680, 701, 716, 809, 817, 819, 820, 823, 825, 832, 833, 838
New paragraphs	220A, 524A, 536A, 613A, 821A, 827A
Deleted paragraphs	233, 601

In addition, the proper shipping name of UN number 2913 has been modified to include the new group of surface contaminated objects SCO-III; this is indicated in Table 1 of this publication. Furthermore, Table 2 of this publication has been extended to include basic radionuclide values for the radionuclides Ba-135m, Ge-69, Ir-193m, Ni-57, Sr-83, Tb-149 and Tb-161.

A table of all the changes made is available upon request to the IAEA (Safety.Standards@iaea.org).

THE IAEA SAFETY STANDARDS

BACKGROUND

Radioactivity is a natural phenomenon and natural sources of radiation are features of the environment. Radiation and radioactive substances have many beneficial applications, ranging from power generation to uses in medicine, industry and agriculture. The radiation risks to workers and the public and to the environment that may arise from these applications have to be assessed and, if necessary, controlled.

Activities such as the medical uses of radiation, the operation of nuclear installations, the production, transport and use of radioactive material, and the management of radioactive waste must therefore be subject to standards of safety.

Regulating safety is a national responsibility. However, radiation risks may transcend national borders, and international cooperation serves to promote and enhance safety globally by exchanging experience and by improving capabilities to control hazards, to prevent accidents, to respond to emergencies and to mitigate any harmful consequences.

States have an obligation of diligence and duty of care, and are expected to fulfil their national and international undertakings and obligations.

International safety standards provide support for States in meeting their obligations under general principles of international law, such as those relating to environmental protection. International safety standards also promote and assure confidence in safety and facilitate international commerce and trade.

A global nuclear safety regime is in place and is being continuously improved. IAEA safety standards, which support the implementation of binding international instruments and national safety infrastructures, are a cornerstone of this global regime. The IAEA safety standards constitute a useful tool for contracting parties to assess their performance under these international conventions.

THE IAEA SAFETY STANDARDS

The status of the IAEA safety standards derives from the IAEA's Statute, which authorizes the IAEA to establish or adopt, in consultation and, where appropriate, in collaboration with the competent organs of the United Nations and with the specialized agencies concerned, standards of safety for protection of health and minimization of danger to life and property, and to provide for their application.

With a view to ensuring the protection of people and the environment from harmful effects of ionizing radiation, the IAEA safety standards establish fundamental safety principles, requirements and measures to control the radiation exposure of people and the release of radioactive material to the environment, to restrict the likelihood of events that might lead to a loss of control over a nuclear reactor core, nuclear chain reaction, radioactive source or any other source of radiation, and to mitigate the consequences of such events if they were to occur. The standards apply to facilities and activities that give rise to radiation risks, including nuclear installations, the use of radiation and radioactive sources, the transport of radioactive material and the management of radioactive waste.

Safety measures and security measures¹ have in common the aim of protecting human life and health and the environment. Safety measures and security measures must be designed and implemented in an integrated manner so that security measures do not compromise safety and safety measures do not compromise security.

The IAEA safety standards reflect an international consensus on what constitutes a high level of safety for protecting people and the environment from harmful effects of ionizing radiation. They are issued in the IAEA Safety Standards Series, which has three categories (see Fig. 1).

Safety Fundamentals

Safety Fundamentals present the fundamental safety objective and principles of protection and safety, and provide the basis for the safety requirements.

Safety Requirements

An integrated and consistent set of Safety Requirements establishes the requirements that must be met to ensure the protection of people and the environment, both now and in the future. The requirements are governed by the objective and principles of the Safety Fundamentals. If the requirements are not met, measures must be taken to reach or restore the required level of safety. The format and style of the requirements facilitate their use for the establishment, in a harmonized manner, of a national regulatory framework. Requirements, including numbered ‘overarching’ requirements, are expressed as ‘shall’ statements. Many requirements are not addressed to a specific party, the implication being that the appropriate parties are responsible for fulfilling them.

¹ See also publications issued in the IAEA Nuclear Security Series.




FIG. 1. The long term structure of the IAEA Safety Standards Series.

Safety Guides

Safety Guides provide recommendations and guidance on how to comply with the safety requirements, indicating an international consensus that it is necessary to take the measures recommended (or equivalent alternative measures). The Safety Guides present international good practices, and increasingly they reflect best practices, to help users striving to achieve high levels of safety. The recommendations provided in Safety Guides are expressed as ‘should’ statements.

APPLICATION OF THE IAEA SAFETY STANDARDS

The principal users of safety standards in IAEA Member States are regulatory bodies and other relevant national authorities. The IAEA safety standards are also used by co-sponsoring organizations and by many organizations that design, construct and operate nuclear facilities, as well as organizations involved in the use of radiation and radioactive sources.

The IAEA safety standards are applicable, as relevant, throughout the entire lifetime of all facilities and activities — existing and new — utilized for peaceful purposes and to protective actions to reduce existing radiation risks. They can be used by States as a reference for their national regulations in respect of facilities and activities.

The IAEA's Statute makes the safety standards binding on the IAEA in relation to its own operations and also on States in relation to IAEA assisted operations.

The IAEA safety standards also form the basis for the IAEA's safety review services, and they are used by the IAEA in support of competence building, including the development of educational curricula and training courses.

International conventions contain requirements similar to those in the IAEA safety standards and make them binding on contracting parties. The IAEA safety standards, supplemented by international conventions, industry standards and detailed national requirements, establish a consistent basis for protecting people and the environment. There will also be some special aspects of safety that need to be assessed at the national level. For example, many of the IAEA safety standards, in particular those addressing aspects of safety in planning or design, are intended to apply primarily to new facilities and activities. The requirements established in the IAEA safety standards might not be fully met at some existing facilities that were built to earlier standards. The way in which IAEA safety standards are to be applied to such facilities is a decision for individual States.

The scientific considerations underlying the IAEA safety standards provide an objective basis for decisions concerning safety; however, decision makers must also make informed judgements and must determine how best to balance the benefits of an action or an activity against the associated radiation risks and any other detrimental impacts to which it gives rise.

DEVELOPMENT PROCESS FOR THE IAEA SAFETY STANDARDS

The preparation and review of the safety standards involves the IAEA Secretariat and five safety standards committees, for emergency preparedness and response (EPReSC) (as of 2016), nuclear safety (NUSSC), radiation safety (RASSC), the safety of radioactive waste (WASSC) and the safe transport of radioactive material (TRANSSC), and a Commission on Safety Standards (CSS) which oversees the IAEA safety standards programme (see Fig. 2).

All IAEA Member States may nominate experts for the safety standards committees and may provide comments on draft standards. The membership of




FIG. 2. The process for developing a new safety standard or revising an existing standard.

the Commission on Safety Standards is appointed by the Director General and includes senior governmental officials having responsibility for establishing national standards.

A management system has been established for the processes of planning, developing, reviewing, revising and establishing the IAEA safety standards. It articulates the mandate of the IAEA, the vision for the future application of the safety standards, policies and strategies, and corresponding functions and responsibilities.

INTERACTION WITH OTHER INTERNATIONAL ORGANIZATIONS

The findings of the United Nations Scientific Committee on the Effects of Atomic Radiation (UNSCEAR) and the recommendations of international

expert bodies, notably the International Commission on Radiological Protection (ICRP), are taken into account in developing the IAEA safety standards. Some safety standards are developed in cooperation with other bodies in the United Nations system or other specialized agencies, including the Food and Agriculture Organization of the United Nations, the United Nations Environment Programme, the International Labour Organization, the OECD Nuclear Energy Agency, the Pan American Health Organization and the World Health Organization.

INTERPRETATION OF THE TEXT

Safety related terms are to be understood as defined in the IAEA Safety Glossary (see <http://www-ns.iaea.org/standards/safety-glossary.htm>). Otherwise, words are used with the spellings and meanings assigned to them in the latest edition of The Concise Oxford Dictionary. For Safety Guides, the English version of the text is the authoritative version.

The background and context of each standard in the IAEA Safety Standards Series and its objective, scope and structure are explained in Section 1, Introduction, of each publication.

Material for which there is no appropriate place in the body text (e.g. material that is subsidiary to or separate from the body text, is included in support of statements in the body text, or describes methods of calculation, procedures or limits and conditions) may be presented in appendices or annexes.

An appendix, if included, is considered to form an integral part of the safety standard. Material in an appendix has the same status as the body text, and the IAEA assumes authorship of it. Annexes and footnotes to the main text, if included, are used to provide practical examples or additional information or explanation. Annexes and footnotes are not integral parts of the main text. Annex material published by the IAEA is not necessarily issued under its authorship; material under other authorship may be presented in annexes to the safety standards. Extraneous material presented in annexes is excerpted and adapted as necessary to be generally useful.

CONTENTS

SECTION I.	INTRODUCTION	1
Background (101–103)		1
Objective (104–105)		2
Scope (106–110)		3
Structure (111)		4
SECTION II.	DEFINITIONS (201–249)	5
SECTION III.	GENERAL PROVISIONS	15
Radiation protection (301–303)		15
Emergency response (304–305)		15
Management system (306)		16
Compliance assurance (307–308)		16
Non-compliance (309)		16
Special arrangement (310)		17
Training (311–315)		17
SECTION IV.	ACTIVITY LIMITS AND CLASSIFICATION	21
General provisions (401)		21
Basic radionuclide values (402)		21
Determination of basic radionuclide values (403–407)		21
Classification of material (408–420)		46
Classification of packages (421–433)		50
Special arrangement (434)		54
SECTION V.	REQUIREMENTS AND CONTROLS FOR TRANSPORT	55
Requirements before the first shipment (501)		55
Requirements before each shipment (502–503)		55
Transport of other goods (504–506)		56
Other dangerous properties of contents (507)		57
Requirements and controls for contamination and for leaking packages (508–514)		57
Requirements and controls for transport of excepted packages (515–516) ..		58

Requirements and controls for transport of LSA material and SCO in industrial packages or unpackaged (517–522)	59
Determination of transport index (523–524A)	60
Determination of criticality safety index for consignments, freight containers and overpacks (525)	63
Limits on transport index, criticality safety index and dose rates for packages and overpacks (526–528)	63
Categories (529)	63
Marking, labelling and placarding (530–544)	64
Consignor's responsibilities (545–561)	72
Transport and storage in transit (562–581)	78
Customs operations (582)	85
Undeliverable consignments (583)	85
Retention and availability of transport documents by carriers (584–588) ..	85

SECTION VI. REQUIREMENTS FOR RADIOACTIVE MATERIAL AND FOR PACKAGINGS AND PACKAGES 87

Requirements for radioactive material (601–605)	87
Requirements for material excepted from fissile classification (606)	88
General requirements for all packagings and packages (607–618)	88
Additional requirements for packages transported by air (619–621)	90
Requirements for excepted packages (622)	90
Requirements for industrial packages (623–630)	90
Requirements for packages containing uranium hexafluoride (631–634) ..	93
Requirements for Type A packages (635–651)	94
Requirements for Type B(U) packages (652–666)	96
Requirements for Type B(M) packages (667–668)	99
Requirements for Type C packages (669–672)	99
Requirements for packages containing fissile material (673–686)	100

SECTION VII. TEST PROCEDURES 107

Demonstration of compliance (701–702)	107
Leaching test for low dispersible radioactive material (703)	107
Tests for special form radioactive material (704–711)	108
Tests for low dispersible radioactive material (712)	110
Tests for packages (713–737)	110

SECTION VIII. APPROVAL AND ADMINISTRATIVE REQUIREMENTS	119
General (801–802)	119
Approval of special form radioactive material and low dispersible radioactive material (803–804)	120
Approval of material excepted from fissile classification (805–806)	120
Approval of package designs (807–816)	121
Approval of alternative activity limits for an exempt consignment of instruments or articles (817–818)	124
Transitional arrangements (819–823)	125
Notification and registration of serial numbers (824)	127
Approval of shipments (825–828)	128
Approval of shipments under special arrangement (829–831)	129
Competent authority certificates of approval (832–833)	130
Contents of certificates of approval (834–839)	132
Validation of certificates (840)	139
REFERENCES	141
ANNEX I: SUMMARY OF APPROVAL AND PRIOR NOTIFICATION REQUIREMENTS	145
ANNEX II: CONVERSION FACTORS AND PREFIXES	151
ANNEX III: SUMMARY OF CONSIGNMENTS REQUIRING EXCLUSIVE USE	153
CONTRIBUTORS TO DRAFTING AND REVIEW (2018)	155
INDEX	159

LIST OF TABLES

Table 1.	Excerpts from the list of UN numbers, proper shipping names and descriptions	22
Table 2.	Basic radionuclide values	25
Table 3.	Basic radionuclide values for unknown radionuclides or mixtures	46
Table 4.	Activity limits for excepted packages	51
Table 5.	Industrial package requirements for LSA material, SCO-I and SCO-II	61
Table 6.	Conveyance activity limits for LSA material and SCO in industrial packages or unpackaged	61
Table 7.	Multiplication factors for tanks, freight containers and unpackaged LSA-I, SCO-I and SCO-III	62
Table 8.	Categories of packages, overpacks and freight containers . .	64
Table 9.	UN marking for packages and overpacks	65
Table 10.	Transport index limits for freight containers and conveyances not under exclusive use	80
Table 11.	CSI limits for freight containers and conveyances containing fissile material	81
Table 12.	Insolation data	97
Table 13.	Values of Z for calculation of CSI in accordance with para. 674	101
Table 14.	Free drop distance for testing packages to normal conditions of transport	113

Section I

INTRODUCTION

BACKGROUND

101. These Regulations establish standards of safety which provide an acceptable level of control of the radiation, criticality and thermal hazards to people, property and the environment that are associated with the transport of *radioactive material*. These Regulations are based on: the Fundamental Safety Principles, IAEA Safety Standards Series No. SF-1 [1], jointly sponsored by the European Atomic Energy Community (EAEC), the Food and Agriculture Organization of the United Nations (FAO), the IAEA, the International Labour Organization (ILO), the International Maritime Organization (IMO), the OECD Nuclear Energy Agency (NEA), the Pan American Health Organization (PAHO), the United Nations Environment Programme (UNEP) and the World Health Organization (WHO); Radiation Protection and Safety of Radiation Sources: International Basic Safety Standards, IAEA Safety Standards Series No. GSR Part 3 [2], jointly sponsored by the European Commission (EC), FAO, IAEA, ILO, OECD/NEA, PAHO, UNEP and WHO; Governmental, Legal and Regulatory Framework for Safety, IAEA Safety Standards Series No. GSR Part 1 (Rev. 1) [3]; and Leadership and Management for Safety, IAEA Safety Standards Series No. GSR Part 2 [4]. Thus, compliance with these Regulations is deemed to satisfy the principles of GSR Part 3 [2] in respect of transport. In accordance with SF-1 [1], the prime responsibility for safety must rest with the person or organization responsible for facilities and activities that give rise to radiation risks.

102. This Safety Standard is supplemented by a hierarchy of Safety Guides, including: Advisory Material for the IAEA Regulations for the Safe Transport of Radioactive Material (2012 Edition), IAEA Safety Standards Series No. SSG-26 [5] (the 2018 edition that will coincide with this edition of the Regulations is under development); Planning and Preparing for Emergency Response to Transport Accidents Involving Radioactive Material, IAEA Safety Standards Series No. TS-G-1.2 (ST-3) [6]; Compliance Assurance for the Safe Transport of Radioactive Material, IAEA Safety Standards Series No. TS-G-1.5 [7]; The Management System for the Safe Transport of Radioactive Material, IAEA Safety Standards Series No. TS-G-1.4 [8]; Radiation Protection Programmes for the Transport of Radioactive Material, IAEA Safety Standards Series No. TS-G-1.3 [9]; and Schedules of Provisions of the IAEA Regulations for the Safe Transport of Radioactive Material (2012 Edition), IAEA Safety

SECTION I

Standards Series No. SSG-33 [10] (the 2018 edition that will coincide with this edition of the Regulations is under development).

103. In certain parts of these Regulations, a particular action is prescribed, but the responsibility for carrying out the action is not specifically assigned to any particular person. Such responsibility may vary according to the laws and customs of different countries and the international conventions into which these countries have entered. For the purpose of these Regulations, it is not necessary to make this assignment, but only to identify the action itself. It remains the prerogative of each government to assign this responsibility.

OBJECTIVE

104. The objective of these Regulations is to establish requirements that must be satisfied to ensure safety and to protect people, property, and the environment from harmful effects of ionizing radiation during the transport of *radioactive material*. This protection is achieved by requiring:

- (a) Containment of the *radioactive contents*;
- (b) Control of external *dose rate*;
- (c) Prevention of criticality;
- (d) Prevention of damage caused by heat.

These requirements are satisfied firstly by applying a graded approach to contents limits for *packages* and *conveyances* and to performance standards applied to *package designs*, depending upon the hazard of the *radioactive contents*. Secondly, they are satisfied by imposing conditions on the *design* and operation of *packages* and on the maintenance of *packagings*, including consideration of the nature of the *radioactive contents*. Thirdly, they are satisfied by requiring administrative controls, including, where appropriate, *approval* by *competent authorities*. Finally, further protection is provided by making arrangements for planning and preparing emergency response to protect people, property and the environment.

105. In the transport of *radioactive material*, the safety of people and the protection of property and the environment are assured when these Regulations are complied with. Confidence in this regard is achieved through *management system* and *compliance assurance* programmes.

INTRODUCTION

SCOPE

106. These Regulations apply to the transport of *radioactive material* by all modes on land, water, or in the air, including transport that is incidental to the use of the *radioactive material*. Transport comprises all operations and conditions associated with, and involved in, the movement of *radioactive material*; these include the *design*, manufacture, maintenance and repair of *packaging*, and the preparation, consigning, loading, carriage including in-transit storage, *shipment* after storage, unloading and receipt at the final destination of loads of *radioactive material* and *packages*. A graded approach is applied in specifying the performance standards in these Regulations, which are characterized in terms of three general severity levels:

- (a) Routine conditions of transport (incident free);
- (b) Normal conditions of transport (minor mishaps);
- (c) Accident conditions of transport.

107. These Regulations do not apply to any of the following:

- (a) *Radioactive material* that is an integral part of the means of transport.
- (b) *Radioactive material* moved within an establishment that is subject to appropriate safety regulations in force in the establishment and where the movement does not involve public roads or railways.
- (c) *Radioactive material* implanted or incorporated into a person or live animal for diagnosis or treatment.
- (d) *Radioactive material* in or on a person who is to be transported for medical treatment because the person has been subject to accidental or deliberate intake of *radioactive material* or to *contamination*.
- (e) *Radioactive material* in consumer products that have received regulatory *approval*, following their sale to the end user.
- (f) Natural material and ores containing naturally occurring radionuclides, which may have been processed, provided the activity concentration of the material does not exceed 10 times the values specified in Table 2, or calculated in accordance with paras 403(a) and 404–407. For natural materials and ores containing naturally occurring radionuclides that are not in secular equilibrium the calculation of the activity concentration shall be performed in accordance with para. 405.
- (g) Non-radioactive solid objects with radioactive substances present on any surface in quantities not in excess of the levels defined in para. 214.

SECTION I

108. These Regulations do not specify controls such as routeing or physical protection that may be instituted for reasons other than radiological safety. Any such controls shall take into account radiological and non-radiological hazards, and shall not detract from the standards of safety that these Regulations are intended to provide.

109. Measures should be taken to ensure that *radioactive material* is kept secure in transport so as to prevent theft or damage and to ensure that control of the material is not relinquished inappropriately (see Annex I).

110. For *radioactive material* having subsidiary hazards, and for transport of *radioactive material* with other dangerous goods, the relevant transport regulations for dangerous goods shall apply in addition to these Regulations.

STRUCTURE

111. This publication is structured so that Section II defines the terms that are required for the purposes of these Regulations; Section III provides general provisions; Section IV provides activity limits and material restrictions used throughout these Regulations; Section V provides requirements and controls for transport; Section VI provides requirements for *radioactive material* and for *packagings* and *packages*; Section VII provides requirements for test procedures; and Section VIII provides requirements for *approvals* and administration.

Section II

DEFINITIONS

The following definitions shall apply for the purposes of these Regulations:

A_1 and A_2

201. A_1 shall mean the activity value of *special form radioactive material* that is listed in Table 2 or derived in Section IV and is used to determine the activity limits for the requirements of these Regulations. A_2 shall mean the activity value of *radioactive material*, other than *special form radioactive material*, that is listed in Table 2 or derived in Section IV and is used to determine the activity limits for the requirements of these Regulations.

Aircraft

202. Cargo *aircraft* shall mean any *aircraft*, other than a passenger *aircraft*, that carries goods or property.

203. Passenger *aircraft* shall mean an *aircraft* that carries any person other than a crew member, a *carrier's* employee in an official capacity, an authorized representative of an appropriate national authority, or a person accompanying a *consignment* or other cargo.

Approval

204. *Multilateral approval* shall mean *approval* by the relevant *competent authority* of the country of origin of the *design* or *shipment*, as applicable, and also, where the *consignment* is to be transported *through or into* any other country, *approval* by the *competent authority* of that country.

205. *Unilateral approval* shall mean an *approval* of a *design* that is required to be given by the *competent authority* of the country of origin of the *design* only.

Carrier

206. *Carrier* shall mean any person, organization or government undertaking the carriage of *radioactive material* by any means of transport. The term includes both *carriers* for hire or reward (known as common or contract *carriers* in some

SECTION II

countries) and *carriers* on own account (known as private *carriers* in some countries).

Competent authority

207. *Competent authority* shall mean any body or authority designated or otherwise recognized as such for any purpose in connection with these Regulations.

Compliance assurance

208. *Compliance assurance* shall mean a systematic programme of measures applied by a *competent authority* that is aimed at ensuring that the provisions of these Regulations are met in practice.

Confinement system

209. *Confinement system* shall mean the assembly of *fissile material* and *packaging* components specified by the designer and agreed to by the *competent authority* as intended to preserve criticality safety.

Consignee

210. *Consignee* shall mean any person, organization or government that is entitled to take delivery of a *consignment*.

Consignment

211. *Consignment* shall mean any *package* or *packages*, or load of *radioactive material*, presented by a *consignor* for transport.

Consignor

212. *Consignor* shall mean any person, organization or government that prepares a *consignment* for transport.

Containment system

213. *Containment system* shall mean the assembly of components of the *packaging* specified by the designer as intended to retain the *radioactive material* during transport.

DEFINITIONS

Contamination

214. *Contamination* shall mean the presence of a radioactive substance on a surface in quantities in excess of 0.4 Bq/cm² for beta and gamma emitters and *low toxicity alpha emitters*, or 0.04 Bq/cm² for all other alpha emitters.

215. *Non-fixed contamination* shall mean *contamination* that can be removed from a surface during routine conditions of transport.

216. *Fixed contamination* shall mean *contamination* other than *non-fixed contamination*.

Conveyance

217. *Conveyance* shall mean:

- (a) For transport by road or rail: any *vehicle*;
- (b) For transport by water: any *vessel*, or any hold, compartment, or *defined deck area* of a *vessel*;
- (c) For transport by air: any *aircraft*.

Criticality safety index

218. *Criticality safety index (CSI)* assigned to a *package*, *overpack* or *freight container* containing *fissile material* shall mean a number that is used to provide control over the accumulation of *packages*, *overpacks* or *freight containers* containing *fissile material*.

Defined deck area

219. *Defined deck area* shall mean the area of the weather deck of a *vessel*, or of a *vehicle* deck of a roll-on/roll-off ship or ferry, that is allocated for the stowage of *radioactive material*.

Design

220. *Design* shall mean the description of *fissile material* excepted under para. 417(f), *special form radioactive material*, *low dispersible radioactive material*, *package* or *packaging* that enables such an item to be fully identified. The description may include specifications, engineering drawings, reports

SECTION II

demonstrating compliance with regulatory requirements, and other relevant documentation.

Dose rate

220A. *Dose rate* shall mean the ambient dose equivalent or the directional dose equivalent, as appropriate, per unit time, measured at the point of interest.

Exclusive use

221. *Exclusive use* shall mean the sole use, by a single *consignor*, of a *conveyance* or of a *large freight container*, in respect of which all initial, intermediate and final loading and unloading and *shipment* are carried out in accordance with the directions of the *consignor* or *consignee*, where so required by these Regulations.

Fissile nuclides and fissile material

222. *Fissile nuclides* shall mean uranium-233, uranium-235, plutonium-239 and plutonium-241. *Fissile material* shall mean a material containing any of the *fissile nuclides*. Excluded from the definition of *fissile material* are the following:

- (a) *Natural uranium* or *depleted uranium* that is unirradiated;
- (b) *Natural uranium* or *depleted uranium* that has been irradiated in thermal reactors only;
- (c) Material with *fissile nuclides* less than a total of 0.25 g;
- (d) Any combination of (a), (b) and/or (c).

These exclusions are only valid if there is no other material with *fissile nuclides* in the *package* or in the *consignment* if shipped unpackaged.

Freight container — small, large

223. *Freight container* shall mean an article of transport equipment that is of a permanent character and is strong enough to be suitable for repeated use; specially designed to facilitate the transport of goods by one or other modes of transport without intermediate reloading, designed to be secured and/or readily handled, and having fittings for these purposes. The term *freight container* does not include the *vehicle*.

DEFINITIONS

A *small freight container* shall mean a *freight container* that has an internal volume of not more than 3 m³. A *large freight container* shall mean a *freight container* that has an internal volume of more than 3 m³.

Intermediate bulk container

224. *Intermediate bulk container (IBC)* shall mean a portable *packaging* that:

- (a) Has a capacity of not more than 3 m³;
- (b) Is designed for mechanical handling;
- (c) Is resistant to the stresses produced during handling and transport, as determined by tests.

Low dispersible radioactive material

225. *Low dispersible radioactive material* shall mean either a solid *radioactive material* or a solid *radioactive material* in a sealed capsule that has limited dispersibility and is not in powder form.

Low specific activity material

226. *Low specific activity (LSA) material* shall mean *radioactive material* that by its nature has a limited *specific activity*, or *radioactive material* for which limits of estimated average *specific activity* apply. External shielding materials surrounding the *LSA material* shall not be considered in determining the estimated average *specific activity*.

Low toxicity alpha emitters

227. *Low toxicity alpha emitters* are: *natural uranium*, *depleted uranium*, natural thorium, uranium-235, uranium-238, thorium-232, thorium-228 and thorium-230 when contained in ores, or in physical and chemical concentrates; or alpha emitters with a half-life of less than 10 days.

Management system

228. *Management system* shall mean a set of interrelated or interacting elements for establishing policies and objectives and enabling the objectives to be achieved in an efficient and effective manner.

SECTION II

Maximum normal operating pressure

229. *Maximum normal operating pressure* shall mean the maximum pressure above atmospheric pressure at mean sea level that would develop in the *containment system* in a period of one year under the conditions of temperature and solar radiation corresponding to the environmental conditions in the absence of venting, external cooling by an ancillary system, or operational controls during transport.

Overpack

230. *Overpack* shall mean an enclosure used by a single *consignor* to contain one or more *packages*, and to form one unit for convenience of handling and stowage during transport.

Package

231. *Package* shall mean the complete product of the packing operation, consisting of the *packaging* and its contents prepared for transport. The types of *package* covered by these Regulations that are subject to the activity limits and material restrictions of Section IV and meet the corresponding requirements are:

- (a) *Excepted package*;
- (b) *Industrial package Type 1 (Type IP-1)*;
- (c) *Industrial package Type 2 (Type IP-2)*;
- (d) *Industrial package Type 3 (Type IP-3)*;
- (e) *Type A package*;
- (f) *Type B(U) package*;
- (g) *Type B(M) package*;
- (h) *Type C package*.

Packages containing *fissile material* or uranium hexafluoride are subject to additional requirements.

Packaging

232. *Packaging* shall mean one or more receptacles and any other components or materials necessary for the receptacles to perform containment and other safety functions.

DEFINITIONS

Radiation level

233. This paragraph was deleted and its content has been transferred to the new para. 220A.

Radiation protection programme

234. *Radiation protection programme* shall mean systematic arrangements that are aimed at providing adequate consideration of radiation protection measures.

Radioactive contents

235. *Radioactive contents* shall mean the *radioactive material* together with any contaminated or activated solids, liquids and gases within the *packaging*.

Radioactive material

236. *Radioactive material* shall mean any material containing radionuclides where both the activity concentration and the total activity in the *consignment* exceed the values specified in paras 402–407.

Shipment

237. *Shipment* shall mean the specific movement of a *consignment* from origin to destination.

Special arrangement

238. *Special arrangement* shall mean those provisions, approved by the *competent authority*, under which *consignments* that do not satisfy all the applicable requirements of these Regulations may be transported.

Special form radioactive material

239. *Special form radioactive material* shall mean either an indispersible solid *radioactive material* or a sealed capsule containing *radioactive material*.

Specific activity

240. *Specific activity* of a radionuclide shall mean the activity per unit mass of that nuclide. The *specific activity* of a material shall mean the activity per

SECTION II

unit mass of the material in which the radionuclides are essentially uniformly distributed.

Surface contaminated object

241. *Surface contaminated object (SCO)* shall mean a solid object that is not itself radioactive but which has *radioactive material* distributed on its surface.

Tank

242. *Tank* shall mean a portable *tank* (including a *tank* container), a road *tank vehicle*, a rail *tank* wagon or a receptacle that contains solids, liquids, or gases, having a capacity of not less than 450 L when used for the transport of gases.

Through or into

243. *Through or into* shall mean *through or into* the countries in which a *consignment* is transported but specifically excludes countries over which a *consignment* is carried by air, provided that there are no scheduled stops in those countries.

Transport index

244. *Transport index (TI)* assigned to a *package*, *overpack* or *freight container*, or to unpackaged *LSA-I*, *SCO-I* or *SCO-III*, shall mean a number that is used to provide control over radiation exposure.

Unirradiated thorium

245. *Unirradiated thorium* shall mean thorium containing not more than 10^{-7} g of uranium-233 per gram of thorium-232.

Unirradiated uranium

246. *Unirradiated uranium* shall mean *uranium* containing not more than 2×10^3 Bq of plutonium per gram of uranium-235, not more than 9×10^6 Bq of fission products per gram of uranium-235 and not more than 5×10^{-3} g of uranium-236 per gram of uranium-235.

DEFINITIONS

Uranium — natural, depleted, enriched

247. *Natural uranium* shall mean *uranium* (which may be chemically separated) containing the naturally occurring distribution of *uranium* isotopes (approximately 99.28% uranium-238 and 0.72% uranium-235, by mass).

Depleted uranium shall mean *uranium* containing a lesser mass percentage of uranium-235 than *natural uranium*.

Enriched uranium shall mean *uranium* containing a greater mass percentage of uranium-235 than 0.72%. In all cases, a very small mass percentage of uranium-234 is present.

Vehicle

248. *Vehicle* shall mean a road *vehicle* (including an articulated *vehicle*, i.e. a tractor and semi-trailer combination), railroad car or railway wagon. Each trailer shall be considered as a separate *vehicle*.

Vessel

249. *Vessel* shall mean any sea-going *vessel* or inland waterway craft used for carrying cargo.

Section III

GENERAL PROVISIONS

RADIATION PROTECTION

301. Doses to persons shall be below the relevant dose limits. Protection and safety shall be optimized in order that the magnitude of individual doses, the number of persons exposed and the likelihood of incurring exposure shall be kept as low as reasonably achievable, economic and social factors being taken into account, within the restriction that the doses to individuals are subject to dose constraints. A structured and systematic approach shall be adopted and shall include consideration of the interfaces between transport and other activities.

302. A *radiation protection programme* shall be established for the transport of *radioactive material*. The nature and extent of the measures to be employed in the programme shall be related to the magnitude and likelihood of radiation exposure. The programme shall incorporate the requirements of paras 301, 303–305, 311 and 562. Programme documents shall be available, on request, for inspection by the relevant *competent authority*.

303. For occupational exposures arising from transport activities, where it is assessed that the effective dose either:

- (a) Is likely to be between 1 and 6 mSv in a year, a dose assessment programme via workplace monitoring or individual monitoring shall be conducted; or
- (b) Is likely to exceed 6 mSv in a year, individual monitoring shall be conducted.

When workplace monitoring or individual monitoring is conducted, appropriate records shall be kept.

EMERGENCY RESPONSE

304. In the event of a nuclear or radiological emergency during the transport of *radioactive material*, provisions as established by relevant national and/or international organizations shall be observed to protect people, property and the environment. *Consignors* and *carriers* shall establish, in advance, arrangements for preparedness and response in accordance with the national and/or international

SECTION III

requirements and in a consistent and coordinated manner with the national and/or international emergency arrangements and emergency management system.

305. The arrangements for preparedness and response shall be based on the graded approach and shall take into consideration the identified hazards and their potential consequences, including the formation of other dangerous substances that may result from the reaction between the contents of a *consignment* and the environment in the event of a nuclear or radiological emergency. Guidance for the establishment of such arrangements is contained in Refs [6, 11–14].

MANAGEMENT SYSTEM

306. A *management system* based on international, national or other standards acceptable to the *competent authority* shall be established and implemented for all activities within the scope of the Regulations, as identified in para. 106, to ensure compliance with the relevant provisions of these Regulations. Certification that the *design* specification has been fully implemented shall be available to the *competent authority*. The manufacturer, *consignor* or user shall be prepared:

- (a) To provide facilities for inspection during manufacture and use;
- (b) To demonstrate compliance with these Regulations to the *competent authority*.

Where *competent authority approval* is required, such *approval* shall take into account, and be contingent upon, the adequacy of the *management system*.

COMPLIANCE ASSURANCE

307. The *competent authority* shall assure compliance with these Regulations.

308. The relevant *competent authority* shall arrange for periodic assessments of the radiation doses to persons due to the transport of *radioactive material*, to ensure that the system of protection and safety complies with GSR Part 3 [2].

NON-COMPLIANCE

309. In the event of non-compliance with any limit in these Regulations applicable to *dose rate* or *contamination*:

GENERAL PROVISIONS

- (a) The *consignor*, *consignee*, *carrier* and any organization involved during transport who may be affected, as appropriate, shall be informed of the non-compliance by:
 - (i) The *carrier* if the non-compliance is identified during transport; or
 - (ii) The *consignee* if the non-compliance is identified at receipt.
- (b) The *consignor*, *carrier* or *consignee*, as appropriate, shall:
 - (i) Take immediate steps to mitigate the consequences of the non-compliance;
 - (ii) Investigate the non-compliance and its causes, circumstances and consequences;
 - (iii) Take appropriate action to remedy the causes and circumstances that led to the non-compliance and to prevent a recurrence of the causes and circumstances similar to those that led to the non-compliance;
 - (iv) Communicate to the relevant *competent authority* the causes of the non-compliance and the corrective or preventive actions taken or to be taken.
- (c) The communication of the non-compliance to the *consignor* and the relevant *competent authority*, respectively, shall be made as soon as practicable and shall be immediate whenever an emergency exposure situation has developed or is developing.

SPECIAL ARRANGEMENT

310. *Consignments* for which conformity with the other provisions of these Regulations is impracticable shall not be transported except under *special arrangement*. Provided the *competent authority* is satisfied that conformity with the other provisions of these Regulations is impracticable and that the requisite standards of safety established by these Regulations have been demonstrated through means alternative to the other provisions of these Regulations, the *competent authority* may approve *special arrangement* transport operations for a single *consignment* or a planned series of multiple *consignments*. The overall level of safety in transport shall be at least equivalent to that which would be provided if all the applicable requirements in these Regulations had been met. For *consignments* of this type, *multilateral approval* shall be required.

TRAINING

311. Workers shall receive appropriate training concerning radiation protection, including the precautions to be observed in order to restrict their occupational

SECTION III

exposure and the exposure of other persons who might be affected by their actions.

312. Persons engaged in the transport of *radioactive material* shall receive training on the contents of these Regulations commensurate with their responsibilities.

313. Persons such as those who classify *radioactive material*; pack *radioactive material*; mark and label *radioactive material*; prepare transport documents for *radioactive material*; offer or accept *radioactive material* for transport; carry or handle *radioactive material* during transport; mark or placard or load or unload *packages* of *radioactive material* into or from transport *vehicles*, bulk *packagings* or *freight containers*; or are otherwise directly involved in the transport of *radioactive material* as determined by the *competent authority*; shall receive the following training:

- (a) General awareness/familiarization training:
 - (i) Each person shall receive training designed to provide familiarity with the general provisions of these Regulations.
 - (ii) The general awareness/familiarization training shall include a description of the categories of *radioactive material*; labelling, marking, placarding and *packaging* and segregation requirements; the purpose and content of the *radioactive material* transport document; and the available emergency response documents.
- (b) Function specific training: Each person shall receive detailed training concerning specific *radioactive material* transport requirements that are applicable to the function that person performs.
- (c) Safety training: Commensurate with the risk of exposure in the event of a release, and with the functions performed, each person shall receive training on:
 - (i) Methods and procedures for avoidance of accident conditions during transport, such as proper use of *package* handling equipment and appropriate methods of stowage of *radioactive material*.
 - (ii) Available emergency response information and how to use it.
 - (iii) General hazards presented by the various categories of *radioactive material* and how to prevent exposure to those hazards, including, if appropriate, the use of personal protective clothing and equipment.
 - (iv) Procedures to be immediately followed in the event of an unintentional release of *radioactive material*, including any emergency response procedures for which the person is responsible and personal protection procedures to be followed.

GENERAL PROVISIONS

314. Records of all safety training undertaken shall be kept by the employer and made available to the employee if requested.

315. The training required in para. 313 shall be provided or verified upon employment in a position involving *radioactive material* transport and shall be periodically supplemented with retraining as deemed appropriate by the *competent authority*.

Section IV

ACTIVITY LIMITS AND CLASSIFICATION

GENERAL PROVISIONS

401. *Radioactive material* shall be assigned one of the United Nations (UN) numbers specified in Table 1 in accordance with paras 408–434.

BASIC RADIONUCLIDE VALUES

402. The following basic values for individual radionuclides are given in Table 2:

- (a) A_1 and A_2 in TBq;
- (b) Activity concentration limits for exempt material in Bq/g;
- (c) Activity limits for exempt *consignments* in Bq.

DETERMINATION OF BASIC RADIONUCLIDE VALUES

403. For individual radionuclides:

- (a) That are not listed in Table 2, the determination of the basic radionuclide values referred to in para. 402 shall require *multilateral approval*. For these radionuclides, activity concentrations for exempt material and activity limits for exempt *consignments* shall be calculated in accordance with the principles established in GSR Part 3 [2]. It is permissible to use an A_2 value calculated using a dose coefficient for the appropriate lung absorption type, as recommended by the International Commission on Radiological Protection, if the chemical forms of each radionuclide under both normal and accident conditions of transport are taken into consideration. Alternatively, the radionuclide values in Table 3 may be used without obtaining *competent authority approval*.
- (b) In instruments or articles in which the *radioactive material* is enclosed in or is included as a component part of the instrument or other manufactured article and which meets para. 423(c), alternative basic radionuclide values to those in Table 2 for the activity limit for an exempt *consignment* are permitted and shall require *multilateral approval*. Such alternative activity

SECTION IV

TABLE 1. EXCERPTS FROM THE LIST OF UN NUMBERS, PROPER SHIPPING NAMES AND DESCRIPTIONS

Assignment of UN numbers	PROPER SHIPPING NAME and description ^a
<i>Excepted package</i>	
UN 2908	RADIOACTIVE MATERIAL, EXCEPTED PACKAGE — EMPTY PACKAGING
UN 2909	RADIOACTIVE MATERIAL, EXCEPTED PACKAGE — ARTICLES MANUFACTURED FROM NATURAL URANIUM or DEPLETED URANIUM or NATURAL THORIUM
UN 2910	RADIOACTIVE MATERIAL, EXCEPTED PACKAGE — LIMITED QUANTITY OF MATERIAL
UN 2911	RADIOACTIVE MATERIAL, EXCEPTED PACKAGE — INSTRUMENTS or ARTICLES
UN 3507	URANIUM HEXAFLUORIDE, RADIOACTIVE MATERIAL, EXCEPTED PACKAGE, less than 0.1 kg per package, non-fissile or fissile-excepted ^b
<i>Low specific activity material</i>	
UN 2912	RADIOACTIVE MATERIAL, LOW SPECIFIC ACTIVITY (LSA-I), non-fissile or fissile-excepted ^b
UN 3321	RADIOACTIVE MATERIAL, LOW SPECIFIC ACTIVITY (LSA-II), non-fissile or fissile-excepted ^b
UN 3322	RADIOACTIVE MATERIAL, LOW SPECIFIC ACTIVITY (LSA-III), non-fissile or fissile-excepted ^b
UN 3324	RADIOACTIVE MATERIAL, LOW SPECIFIC ACTIVITY (LSA-II), FISSILE
UN 3325	RADIOACTIVE MATERIAL, LOW SPECIFIC ACTIVITY (LSA-III), FISSILE
<i>Surface contaminated objects</i>	
UN 2913	RADIOACTIVE MATERIAL, SURFACE CONTAMINATED OBJECTS (SCO-I, SCO-II or SCO-III), non-fissile or fissile-excepted ^b
UN 3326	RADIOACTIVE MATERIAL, SURFACE CONTAMINATED OBJECTS (SCO-I or SCO-II), FISSILE
<i>Type A package</i>	
UN 2915	RADIOACTIVE MATERIAL, TYPE A PACKAGE, non-special form, non-fissile or fissile-excepted ^b
UN 3327	RADIOACTIVE MATERIAL, TYPE A PACKAGE, FISSILE, non-special form

ACTIVITY LIMITS AND CLASSIFICATION

TABLE 1. EXCERPTS FROM THE LIST OF UN NUMBERS, PROPER SHIPPING NAMES AND DESCRIPTIONS (cont.)

Assignment of UN numbers	PROPER SHIPPING NAME and description ^a
UN 3332	RADIOACTIVE MATERIAL, TYPE A PACKAGE, SPECIAL FORM, non-fissile or fissile-excepted ^b
UN 3333	RADIOACTIVE MATERIAL, TYPE A PACKAGE, SPECIAL FORM, FISSILE
<i>Type B(U) package</i>	
UN 2916	RADIOACTIVE MATERIAL, TYPE B(U) PACKAGE, non-fissile or fissile-excepted ^b
UN 3328	RADIOACTIVE MATERIAL, TYPE B(U) PACKAGE, FISSILE
<i>Type B(M) package</i>	
UN 2917	RADIOACTIVE MATERIAL, TYPE B(M) PACKAGE, non-fissile or fissile-excepted ^b
UN 3329	RADIOACTIVE MATERIAL, TYPE B(M) PACKAGE, FISSILE
<i>Type C package</i>	
UN 3323	RADIOACTIVE MATERIAL, TYPE C PACKAGE, non-fissile or fissile-excepted ^b
UN 3330	RADIOACTIVE MATERIAL, TYPE C PACKAGE, FISSILE
<i>Special arrangement</i>	
UN 2919	RADIOACTIVE MATERIAL, TRANSPORTED UNDER SPECIAL ARRANGEMENT, non-fissile or fissile-excepted ^b
UN 3331	RADIOACTIVE MATERIAL, TRANSPORTED UNDER SPECIAL ARRANGEMENT, FISSILE
<i>Uranium hexafluoride</i>	
UN 2977	RADIOACTIVE MATERIAL, URANIUM HEXAFLUORIDE, FISSILE
UN 2978	RADIOACTIVE MATERIAL, URANIUM HEXAFLUORIDE, non-fissile or fissile-excepted ^b

^a The “PROPER SHIPPING NAME” is found in the column “PROPER SHIPPING NAME and description” and is restricted to that part shown in CAPITAL LETTERS. In the cases of UN 2909, UN 2911, UN 2913 and UN 3326, where alternative proper shipping names are separated by the word “or”, only the relevant proper shipping name shall be used.

^b The term ‘fissile-excepted’ refers only to material excepted under para. 417.

SECTION IV

limits for an exempt *consignment* shall be calculated in accordance with the principles set out in GSR Part 3 [2].

404. In the calculations of A_1 and A_2 for a radionuclide not listed in Table 2, a single radioactive decay chain in which the radionuclides are present in their naturally occurring proportions, and in which no progeny nuclide has a half-life either longer than 10 days or longer than that of the parent nuclide, shall be considered as a single radionuclide; and the activity to be taken into account and the A_1 or A_2 value to be applied shall be that corresponding to the parent nuclide of that chain. In the case of radioactive decay chains in which any progeny nuclide has a half-life either longer than 10 days or longer than that of the parent nuclide, the parent and such progeny nuclides shall be considered as mixtures of different nuclides.

405. For mixtures of radionuclides, the basic radionuclide values referred to in para. 402 may be determined as follows:

$$X_m = \frac{1}{\sum_i \frac{f(i)}{X(i)}}$$

where

$f(i)$ is the fraction of activity or activity concentration of radionuclide i in the mixture.

$X(i)$ is the appropriate value of A_1 or A_2 , or the activity concentration limit for exempt material or the activity limit for an exempt *consignment* as appropriate for radionuclide i .

X_m is the derived value of A_1 or A_2 , or the activity concentration limit for exempt material or the activity limit for an exempt *consignment* in the case of a mixture.

Text continued on p.45

ACTIVITY LIMITS AND CLASSIFICATION

TABLE 2. BASIC RADIONUCLIDE VALUES

Radionuclide (atomic number)	A_1 (TBq)	A_2 (TBq)	Activity concentration limit for exempt material (Bq/g)	Activity limit for an exempt <i>consignment</i> (Bq)
Actinium (89)				
Ac-225 (a)	8×10^{-1}	6×10^{-3}	1×10^1	1×10^4
Ac-227 (a)	9×10^{-1}	9×10^{-5}	1×10^{-1}	1×10^3
Ac-228	6×10^{-1}	5×10^{-1}	1×10^1	1×10^6
Silver (47)				
Ag-105	2×10^0	2×10^0	1×10^2	1×10^6
Ag-108m (a)	7×10^{-1}	7×10^{-1}	1×10^1 (b)	1×10^6 (b)
Ag-110m (a)	4×10^{-1}	4×10^{-1}	1×10^1	1×10^6
Ag-111	2×10^0	6×10^{-1}	1×10^3	1×10^6
Aluminium (13)				
Al-26	1×10^{-1}	1×10^{-1}	1×10^1	1×10^5
Americium (95)				
Am-241	1×10^1	1×10^{-3}	1×10^0	1×10^4
Am-242m (a)	1×10^1	1×10^{-3}	1×10^0 (b)	1×10^4 (b)
Am-243 (a)	5×10^0	1×10^{-3}	1×10^0 (b)	1×10^3 (b)
Argon (18)				
Ar-37	4×10^1	4×10^1	1×10^6	1×10^8
Ar-39	4×10^1	2×10^1	1×10^7	1×10^4
Ar-41	3×10^{-1}	3×10^{-1}	1×10^2	1×10^9
Arsenic (33)				
As-72	3×10^{-1}	3×10^{-1}	1×10^1	1×10^5
As-73	4×10^1	4×10^1	1×10^3	1×10^7
As-74	1×10^0	9×10^{-1}	1×10^1	1×10^6
As-76	3×10^{-1}	3×10^{-1}	1×10^2	1×10^5
As-77	2×10^1	7×10^{-1}	1×10^3	1×10^6
Astatine (85)				
At-211 (a)	2×10^1	5×10^{-1}	1×10^3	1×10^7

For footnotes see pp. 42–45

SECTION IV

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1 (TBq)	A_2 (TBq)	Activity concentration limit for exempt material (Bq/g)	Activity limit for an exempt <i>consignment</i> (Bq)
Gold (79)				
Au-193	7×10^0	2×10^0	1×10^2	1×10^7
Au-194	1×10^0	1×10^0	1×10^1	1×10^6
Au-195	1×10^1	6×10^0	1×10^2	1×10^7
Au-198	1×10^0	6×10^{-1}	1×10^2	1×10^6
Au-199	1×10^1	6×10^{-1}	1×10^2	1×10^6
Barium (56)				
Ba-131 (a)	2×10^0	2×10^0	1×10^2	1×10^6
Ba-133	3×10^0	3×10^0	1×10^2	1×10^6
Ba-133m	2×10^1	6×10^{-1}	1×10^2	1×10^6
Ba-135m	2×10^1	6×10^{-1}	1×10^2	1×10^6
Ba-140 (a)	5×10^{-1}	3×10^{-1}	1×10^1 (b)	1×10^5 (b)
Beryllium (4)				
Be-7	2×10^1	2×10^1	1×10^3	1×10^7
Be-10	4×10^1	6×10^{-1}	1×10^4	1×10^6
Bismuth (83)				
Bi-205	7×10^{-1}	7×10^{-1}	1×10^1	1×10^6
Bi-206	3×10^{-1}	3×10^{-1}	1×10^1	1×10^5
Bi-207	7×10^{-1}	7×10^{-1}	1×10^1	1×10^6
Bi-210	1×10^0	6×10^{-1}	1×10^3	1×10^6
Bi-210m (a)	6×10^{-1}	2×10^{-2}	1×10^1	1×10^5
Bi-212 (a)	7×10^{-1}	6×10^{-1}	1×10^1 (b)	1×10^5 (b)
Berkelium (97)				
Bk-247	8×10^0	8×10^{-4}	1×10^0	1×10^4
Bk-249 (a)	4×10^1	3×10^{-1}	1×10^3	1×10^6
Bromine (35)				
Br-76	4×10^{-1}	4×10^{-1}	1×10^1	1×10^5
Br-77	3×10^0	3×10^0	1×10^2	1×10^6

For footnotes see pp. 42–45

ACTIVITY LIMITS AND CLASSIFICATION

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1 (TBq)	A_2 (TBq)	Activity concentration limit for exempt material (Bq/g)	Activity limit for an exempt <i>consignment</i> (Bq)
Br-82	4×10^{-1}	4×10^{-1}	1×10^1	1×10^6
Carbon (6)				
C-11	1×10^0	6×10^{-1}	1×10^1	1×10^6
C-14	4×10^1	3×10^0	1×10^4	1×10^7
Calcium (20)				
Ca-41	Unlimited	Unlimited	1×10^5	1×10^7
Ca-45	4×10^1	1×10^0	1×10^4	1×10^7
Ca-47 (a)	3×10^0	3×10^{-1}	1×10^1	1×10^6
Cadmium (48)				
Cd-109	3×10^1	2×10^0	1×10^4	1×10^6
Cd-113m	4×10^1	5×10^{-1}	1×10^3	1×10^6
Cd-115 (a)	3×10^0	4×10^{-1}	1×10^2	1×10^6
Cd-115m	5×10^{-1}	5×10^{-1}	1×10^3	1×10^6
Cerium (58)				
Ce-139	7×10^0	2×10^0	1×10^2	1×10^6
Ce-141	2×10^1	6×10^{-1}	1×10^2	1×10^7
Ce-143	9×10^{-1}	6×10^{-1}	1×10^2	1×10^6
Ce-144 (a)	2×10^{-1}	2×10^{-1}	1×10^2 (b)	1×10^5 (b)
Californium (98)				
Cf-248	4×10^1	6×10^{-3}	1×10^1	1×10^4
Cf-249	3×10^0	8×10^{-4}	1×10^0	1×10^3
Cf-250	2×10^1	2×10^{-3}	1×10^1	1×10^4
Cf-251	7×10^0	7×10^{-4}	1×10^0	1×10^3
Cf-252	1×10^{-1}	3×10^{-3}	1×10^1	1×10^4
Cf-253 (a)	4×10^1	4×10^{-2}	1×10^2	1×10^5
Cf-254	1×10^{-3}	1×10^{-3}	1×10^0	1×10^3
Chlorine (17)				
Cl-36	1×10^1	6×10^{-1}	1×10^4	1×10^6

For footnotes see pp. 42–45

SECTION IV

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1	A_2	Activity concentration limit for exempt material	Activity limit for an exempt <i>consignment</i>
	(TBq)	(TBq)	(Bq/g)	(Bq)
Cl-38	2×10^{-1}	2×10^{-1}	1×10^1	1×10^5
Curium (96)				
Cm-240	4×10^1	2×10^{-2}	1×10^2	1×10^5
Cm-241	2×10^0	1×10^0	1×10^2	1×10^6
Cm-242	4×10^1	1×10^{-2}	1×10^2	1×10^5
Cm-243	9×10^0	1×10^{-3}	1×10^0	1×10^4
Cm-244	2×10^1	2×10^{-3}	1×10^1	1×10^4
Cm-245	9×10^0	9×10^{-4}	1×10^0	1×10^3
Cm-246	9×10^0	9×10^{-4}	1×10^0	1×10^3
Cm-247 (a)	3×10^0	1×10^{-3}	1×10^0	1×10^4
Cm-248	2×10^{-2}	3×10^{-4}	1×10^0	1×10^3
Cobalt (27)				
Co-55	5×10^{-1}	5×10^{-1}	1×10^1	1×10^6
Co-56	3×10^{-1}	3×10^{-1}	1×10^1	1×10^5
Co-57	1×10^1	1×10^1	1×10^2	1×10^6
Co-58	1×10^0	1×10^0	1×10^1	1×10^6
Co-58m	4×10^1	4×10^1	1×10^4	1×10^7
Co-60	4×10^{-1}	4×10^{-1}	1×10^1	1×10^5
Chromium (24)				
Cr-51	3×10^1	3×10^1	1×10^3	1×10^7
Caesium (55)				
Cs-129	4×10^0	4×10^0	1×10^2	1×10^5
Cs-131	3×10^1	3×10^1	1×10^3	1×10^6
Cs-132	1×10^0	1×10^0	1×10^1	1×10^5
Cs-134	7×10^{-1}	7×10^{-1}	1×10^1	1×10^4
Cs-134m	4×10^1	6×10^{-1}	1×10^3	1×10^5
Cs-135	4×10^1	1×10^0	1×10^4	1×10^7
Cs-136	5×10^{-1}	5×10^{-1}	1×10^1	1×10^5

For footnotes see pp. 42–45

ACTIVITY LIMITS AND CLASSIFICATION

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1 (TBq)	A_2 (TBq)	Activity concentration limit for exempt material (Bq/g)	Activity limit for an exempt <i>consignment</i> (Bq)
Cs-137 (a)	2×10^0	6×10^{-1}	1×10^1 (b)	1×10^4 (b)
Copper (29)				
Cu-64	6×10^0	1×10^0	1×10^2	1×10^6
Cu-67	1×10^1	7×10^{-1}	1×10^2	1×10^6
Dysprosium (66)				
Dy-159	2×10^1	2×10^1	1×10^3	1×10^7
Dy-165	9×10^{-1}	6×10^{-1}	1×10^3	1×10^6
Dy-166 (a)	9×10^{-1}	3×10^{-1}	1×10^3	1×10^6
Erbium (68)				
Er-169	4×10^1	1×10^0	1×10^4	1×10^7
Er-171	8×10^{-1}	5×10^{-1}	1×10^2	1×10^6
Europium (63)				
Eu-147	2×10^0	2×10^0	1×10^2	1×10^6
Eu-148	5×10^{-1}	5×10^{-1}	1×10^1	1×10^6
Eu-149	2×10^1	2×10^1	1×10^2	1×10^7
Eu-150 (short lived)	2×10^0	7×10^{-1}	1×10^3	1×10^6
Eu-150 (long lived)	7×10^{-1}	7×10^{-1}	1×10^1	1×10^6
Eu-152	1×10^0	1×10^0	1×10^1	1×10^6
Eu-152m	8×10^{-1}	8×10^{-1}	1×10^2	1×10^6
Eu-154	9×10^{-1}	6×10^{-1}	1×10^1	1×10^6
Eu-155	2×10^1	3×10^0	1×10^2	1×10^7
Eu-156	7×10^{-1}	7×10^{-1}	1×10^1	1×10^6
Fluorine (9)				
F-18	1×10^0	6×10^{-1}	1×10^1	1×10^6
Iron (26)				
Fe-52 (a)	3×10^{-1}	3×10^{-1}	1×10^1	1×10^6
Fe-55	4×10^1	4×10^1	1×10^4	1×10^6
Fe-59	9×10^{-1}	9×10^{-1}	1×10^1	1×10^6

For footnotes see pp. 42–45

SECTION IV

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1 (TBq)	A_2 (TBq)	Activity concentration limit for exempt material (Bq/g)	Activity limit for an exempt <i>consignment</i> (Bq)
Fe-60 (a)	4×10^1	2×10^{-1}	1×10^2	1×10^5
Gallium (31)				
Ga-67	7×10^0	3×10^0	1×10^2	1×10^6
Ga-68	5×10^{-1}	5×10^{-1}	1×10^1	1×10^5
Ga-72	4×10^{-1}	4×10^{-1}	1×10^1	1×10^5
Gadolinium (64)				
Gd-146 (a)	5×10^{-1}	5×10^{-1}	1×10^1	1×10^6
Gd-148	2×10^1	2×10^{-3}	1×10^1	1×10^4
Gd-153	1×10^1	9×10^0	1×10^2	1×10^7
Gd-159	3×10^0	6×10^{-1}	1×10^3	1×10^6
Germanium (32)				
Ge-68 (a)	5×10^{-1}	5×10^{-1}	1×10^1	1×10^5
Ge-69	1×10^0	1×10^0	1×10^1	1×10^6
Ge-71	4×10^1	4×10^1	1×10^4	1×10^8
Ge-77	3×10^{-1}	3×10^{-1}	1×10^1	1×10^5
Hafnium (72)				
Hf-172 (a)	6×10^{-1}	6×10^{-1}	1×10^1	1×10^6
Hf-175	3×10^0	3×10^0	1×10^2	1×10^6
Hf-181	2×10^0	5×10^{-1}	1×10^1	1×10^6
Hf-182	Unlimited	Unlimited	1×10^2	1×10^6
Mercury (80)				
Hg-194 (a)	1×10^0	1×10^0	1×10^1	1×10^6
Hg-195m (a)	3×10^0	7×10^{-1}	1×10^2	1×10^6
Hg-197	2×10^1	1×10^1	1×10^2	1×10^7
Hg-197m	1×10^1	4×10^{-1}	1×10^2	1×10^6
Hg-203	5×10^0	1×10^0	1×10^2	1×10^5
Holmium (67)				
Ho-166	4×10^{-1}	4×10^{-1}	1×10^3	1×10^5

For footnotes see pp. 42–45

ACTIVITY LIMITS AND CLASSIFICATION

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1	A_2	Activity concentration limit for exempt material	Activity limit for an exempt <i>consignment</i>
	(TBq)	(TBq)	(Bq/g)	(Bq)
Ho-166m	6×10^{-1}	5×10^{-1}	1×10^1	1×10^6
Iodine (53)				
I-123	6×10^0	3×10^0	1×10^2	1×10^7
I-124	1×10^0	1×10^0	1×10^1	1×10^6
I-125	2×10^1	3×10^0	1×10^3	1×10^6
I-126	2×10^0	1×10^0	1×10^2	1×10^6
I-129	Unlimited	Unlimited	1×10^2	1×10^5
I-131	3×10^0	7×10^{-1}	1×10^2	1×10^6
I-132	4×10^{-1}	4×10^{-1}	1×10^1	1×10^5
I-133	7×10^{-1}	6×10^{-1}	1×10^1	1×10^6
I-134	3×10^{-1}	3×10^{-1}	1×10^1	1×10^5
I-135 (a)	6×10^{-1}	6×10^{-1}	1×10^1	1×10^6
Indium (49)				
In-111	3×10^0	3×10^0	1×10^2	1×10^6
In-113m	4×10^0	2×10^0	1×10^2	1×10^6
In-114m (a)	1×10^1	5×10^{-1}	1×10^2	1×10^6
In-115m	7×10^0	1×10^0	1×10^2	1×10^6
Iridium (77)				
Ir-189 (a)	1×10^1	1×10^1	1×10^2	1×10^7
Ir-190	7×10^{-1}	7×10^{-1}	1×10^1	1×10^6
Ir-192	1×10^0 (c)	6×10^{-1}	1×10^1	1×10^4
Ir-193m	4×10^1	4×10^0	1×10^4	1×10^7
Ir-194	3×10^{-1}	3×10^{-1}	1×10^2	1×10^5
Potassium (19)				
K-40	9×10^{-1}	9×10^{-1}	1×10^2	1×10^6
K-42	2×10^{-1}	2×10^{-1}	1×10^2	1×10^6
K-43	7×10^{-1}	6×10^{-1}	1×10^1	1×10^6

For footnotes see pp. 42–45

SECTION IV

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1 (TBq)	A_2 (TBq)	Activity concentration limit for exempt material (Bq/g)	Activity limit for an exempt <i>consignment</i> (Bq)
Krypton (36)				
Kr-79	4×10^0	2×10^0	1×10^3	1×10^5
Kr-81	4×10^1	4×10^1	1×10^4	1×10^7
Kr-85	1×10^1	1×10^1	1×10^5	1×10^4
Kr-85m	8×10^0	3×10^0	1×10^3	1×10^{10}
Kr-87	2×10^{-1}	2×10^{-1}	1×10^2	1×10^9
Lanthanum (57)				
La-137	3×10^1	6×10^0	1×10^3	1×10^7
La-140	4×10^{-1}	4×10^{-1}	1×10^1	1×10^5
Lutetium (71)				
Lu-172	6×10^{-1}	6×10^{-1}	1×10^1	1×10^6
Lu-173	8×10^0	8×10^0	1×10^2	1×10^7
Lu-174	9×10^0	9×10^0	1×10^2	1×10^7
Lu-174m	2×10^1	1×10^1	1×10^2	1×10^7
Lu-177	3×10^1	7×10^{-1}	1×10^3	1×10^7
Magnesium (12)				
Mg-28 (a)	3×10^{-1}	3×10^{-1}	1×10^1	1×10^5
Manganese (25)				
Mn-52	3×10^{-1}	3×10^{-1}	1×10^1	1×10^5
Mn-53	Unlimited	Unlimited	1×10^4	1×10^9
Mn-54	1×10^0	1×10^0	1×10^1	1×10^6
Mn-56	3×10^{-1}	3×10^{-1}	1×10^1	1×10^5
Molybdenum (42)				
Mo-93	4×10^1	2×10^1	1×10^3	1×10^8
Mo-99 (a)	1×10^0	6×10^{-1}	1×10^2	1×10^6
Nitrogen (7)				
N-13	9×10^{-1}	6×10^{-1}	1×10^2	1×10^9

For footnotes see pp. 42–45

ACTIVITY LIMITS AND CLASSIFICATION

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1 (TBq)	A_2 (TBq)	Activity concentration limit for exempt material (Bq/g)	Activity limit for an exempt <i>consignment</i> (Bq)
Sodium (11)				
Na-22	5×10^{-1}	5×10^{-1}	1×10^1	1×10^6
Na-24	2×10^{-1}	2×10^{-1}	1×10^1	1×10^5
Niobium (41)				
Nb-93m	4×10^1	3×10^1	1×10^4	1×10^7
Nb-94	7×10^{-1}	7×10^{-1}	1×10^1	1×10^6
Nb-95	1×10^0	1×10^0	1×10^1	1×10^6
Nb-97	9×10^{-1}	6×10^{-1}	1×10^1	1×10^6
Neodymium (60)				
Nd-147	6×10^0	6×10^{-1}	1×10^2	1×10^6
Nd-149	6×10^{-1}	5×10^{-1}	1×10^2	1×10^6
Nickel (28)				
Ni-57	6×10^{-1}	6×10^{-1}	1×10^1	1×10^6
Ni-59	Unlimited	Unlimited	1×10^4	1×10^8
Ni-63	4×10^1	3×10^1	1×10^5	1×10^8
Ni-65	4×10^{-1}	4×10^{-1}	1×10^1	1×10^6
Neptunium (93)				
Np-235	4×10^1	4×10^1	1×10^3	1×10^7
Np-236 (short lived)	2×10^1	2×10^0	1×10^3	1×10^7
Np-236 (long lived)	9×10^0	2×10^{-2}	1×10^2	1×10^5
Np-237	2×10^1	2×10^{-3}	1×10^0 (b)	1×10^3 (b)
Np-239	7×10^0	4×10^{-1}	1×10^2	1×10^7
Osmium (76)				
Os-185	1×10^0	1×10^0	1×10^1	1×10^6
Os-191	1×10^1	2×10^0	1×10^2	1×10^7
Os-191m	4×10^1	3×10^1	1×10^3	1×10^7
Os-193	2×10^0	6×10^{-1}	1×10^2	1×10^6
Os-194 (a)	3×10^{-1}	3×10^{-1}	1×10^2	1×10^5

For footnotes see pp. 42–45

SECTION IV

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1 (TBq)	A_2 (TBq)	Activity concentration limit for exempt material (Bq/g)	Activity limit for an exempt <i>consignment</i> (Bq)
Phosphorus (15)				
P-32	5×10^{-1}	5×10^{-1}	1×10^3	1×10^5
P-33	4×10^1	1×10^0	1×10^5	1×10^8
Protactinium (91)				
Pa-230 (a)	2×10^0	7×10^{-2}	1×10^1	1×10^6
Pa-231	4×10^0	4×10^{-4}	1×10^0	1×10^3
Pa-233	5×10^0	7×10^{-1}	1×10^2	1×10^7
Lead (82)				
Pb-201	1×10^0	1×10^0	1×10^1	1×10^6
Pb-202	4×10^1	2×10^1	1×10^3	1×10^6
Pb-203	4×10^0	3×10^0	1×10^2	1×10^6
Pb-205	Unlimited	Unlimited	1×10^4	1×10^7
Pb-210 (a)	1×10^0	5×10^{-2}	1×10^1 (b)	1×10^4 (b)
Pb-212 (a)	7×10^{-1}	2×10^{-1}	1×10^1 (b)	1×10^5 (b)
Palladium (46)				
Pd-103 (a)	4×10^1	4×10^1	1×10^3	1×10^8
Pd-107	Unlimited	Unlimited	1×10^5	1×10^8
Pd-109	2×10^0	5×10^{-1}	1×10^3	1×10^6
Promethium (61)				
Pm-143	3×10^0	3×10^0	1×10^2	1×10^6
Pm-144	7×10^{-1}	7×10^{-1}	1×10^1	1×10^6
Pm-145	3×10^1	1×10^1	1×10^3	1×10^7
Pm-147	4×10^1	2×10^0	1×10^4	1×10^7
Pm-148m (a)	8×10^{-1}	7×10^{-1}	1×10^1	1×10^6
Pm-149	2×10^0	6×10^{-1}	1×10^3	1×10^6
Pm-151	2×10^0	6×10^{-1}	1×10^2	1×10^6
Polonium (84)				
Po-210	4×10^1	2×10^{-2}	1×10^1	1×10^4

For footnotes see pp. 42–45

ACTIVITY LIMITS AND CLASSIFICATION

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1 (TBq)	A_2 (TBq)	Activity concentration limit for exempt material (Bq/g)	Activity limit for an exempt <i>consignment</i> (Bq)
Praseodymium (59)				
Pr-142	4×10^{-1}	4×10^{-1}	1×10^2	1×10^5
Pr-143	3×10^0	6×10^{-1}	1×10^4	1×10^6
Platinum (78)				
Pt-188 (a)	1×10^0	8×10^{-1}	1×10^1	1×10^6
Pt-191	4×10^0	3×10^0	1×10^2	1×10^6
Pt-193	4×10^1	4×10^1	1×10^4	1×10^7
Pt-193m	4×10^1	5×10^{-1}	1×10^3	1×10^7
Pt-195m	1×10^1	5×10^{-1}	1×10^2	1×10^6
Pt-197	2×10^1	6×10^{-1}	1×10^3	1×10^6
Pt-197m	1×10^1	6×10^{-1}	1×10^2	1×10^6
Plutonium (94)				
Pu-236	3×10^1	3×10^{-3}	1×10^1	1×10^4
Pu-237	2×10^1	2×10^1	1×10^3	1×10^7
Pu-238	1×10^1	1×10^{-3}	1×10^0	1×10^4
Pu-239	1×10^1	1×10^{-3}	1×10^0	1×10^4
Pu-240	1×10^1	1×10^{-3}	1×10^0	1×10^3
Pu-241 (a)	4×10^1	6×10^{-2}	1×10^2	1×10^5
Pu-242	1×10^1	1×10^{-3}	1×10^0	1×10^4
Pu-244 (a)	4×10^{-1}	1×10^{-3}	1×10^0	1×10^4
Radium (88)				
Ra-223 (a)	4×10^{-1}	7×10^{-3}	1×10^2 (b)	1×10^5 (b)
Ra-224 (a)	4×10^{-1}	2×10^{-2}	1×10^1 (b)	1×10^5 (b)
Ra-225 (a)	2×10^{-1}	4×10^{-3}	1×10^2	1×10^5
Ra-226 (a)	2×10^{-1}	3×10^{-3}	1×10^1 (b)	1×10^4 (b)
Ra-228 (a)	6×10^{-1}	2×10^{-2}	1×10^1 (b)	1×10^5 (b)
Rubidium (37)				
Rb-81	2×10^0	8×10^{-1}	1×10^1	1×10^6

For footnotes see pp. 42–45

SECTION IV

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1	A_2	Activity concentration limit for exempt material	Activity limit for an exempt <i>consignment</i>
	(TBq)	(TBq)	(Bq/g)	(Bq)
Rb-83 (a)	2×10^0	2×10^0	1×10^2	1×10^6
Rb-84	1×10^0	1×10^0	1×10^1	1×10^6
Rb-86	5×10^{-1}	5×10^{-1}	1×10^2	1×10^5
Rb-87	Unlimited	Unlimited	1×10^4	1×10^7
Rb (natural)	Unlimited	Unlimited	1×10^4	1×10^7
Rhenium (75)				
Re-184	1×10^0	1×10^0	1×10^1	1×10^6
Re-184m	3×10^0	1×10^0	1×10^2	1×10^6
Re-186	2×10^0	6×10^{-1}	1×10^3	1×10^6
Re-187	Unlimited	Unlimited	1×10^6	1×10^9
Re-188	4×10^{-1}	4×10^{-1}	1×10^2	1×10^5
Re-189 (a)	3×10^0	6×10^{-1}	1×10^2	1×10^6
Re (natural)	Unlimited	Unlimited	1×10^6	1×10^9
Rhodium (45)				
Rh-99	2×10^0	2×10^0	1×10^1	1×10^6
Rh-101	4×10^0	3×10^0	1×10^2	1×10^7
Rh-102	5×10^{-1}	5×10^{-1}	1×10^1	1×10^6
Rh-102m	2×10^0	2×10^0	1×10^2	1×10^6
Rh-103m	4×10^1	4×10^1	1×10^4	1×10^8
Rh-105	1×10^1	8×10^{-1}	1×10^2	1×10^7
Radon (86)				
Rn-222 (a)	3×10^{-1}	4×10^{-3}	1×10^1 (b)	1×10^8 (b)
Ruthenium (44)				
Ru-97	5×10^0	5×10^0	1×10^2	1×10^7
Ru-103 (a)	2×10^0	2×10^0	1×10^2	1×10^6
Ru-105	1×10^0	6×10^{-1}	1×10^1	1×10^6
Ru-106 (a)	2×10^{-1}	2×10^{-1}	1×10^2 (b)	1×10^5 (b)

For footnotes see pp. 42–45

ACTIVITY LIMITS AND CLASSIFICATION

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1 (TBq)	A_2 (TBq)	Activity concentration limit for exempt material (Bq/g)	Activity limit for an exempt <i>consignment</i> (Bq)
Sulphur (16)				
S-35	4×10^1	3×10^0	1×10^5	1×10^8
Antimony (51)				
Sb-122	4×10^{-1}	4×10^{-1}	1×10^2	1×10^4
Sb-124	6×10^{-1}	6×10^{-1}	1×10^1	1×10^6
Sb-125	2×10^0	1×10^0	1×10^2	1×10^6
Sb-126	4×10^{-1}	4×10^{-1}	1×10^1	1×10^5
Scandium (21)				
Sc-44	5×10^{-1}	5×10^{-1}	1×10^1	1×10^5
Sc-46	5×10^{-1}	5×10^{-1}	1×10^1	1×10^6
Sc-47	1×10^1	7×10^{-1}	1×10^2	1×10^6
Sc-48	3×10^{-1}	3×10^{-1}	1×10^1	1×10^5
Selenium (34)				
Se-75	3×10^0	3×10^0	1×10^2	1×10^6
Se-79	4×10^1	2×10^0	1×10^4	1×10^7
Silicon (14)				
Si-31	6×10^{-1}	6×10^{-1}	1×10^3	1×10^6
Si-32	4×10^1	5×10^{-1}	1×10^3	1×10^6
Samarium (62)				
Sm-145	1×10^1	1×10^1	1×10^2	1×10^7
Sm-147	Unlimited	Unlimited	1×10^1	1×10^4
Sm-151	4×10^1	1×10^1	1×10^4	1×10^8
Sm-153	9×10^0	6×10^{-1}	1×10^2	1×10^6
Tin (50)				
Sn-113 (a)	4×10^0	2×10^0	1×10^3	1×10^7
Sn-117m	7×10^0	4×10^{-1}	1×10^2	1×10^6
Sn-119m	4×10^1	3×10^1	1×10^3	1×10^7
Sn-121m (a)	4×10^1	9×10^{-1}	1×10^3	1×10^7

For footnotes see pp. 42–45

SECTION IV

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1	A_2	Activity concentration limit for exempt material	Activity limit for an exempt <i>consignment</i>
	(TBq)	(TBq)	(Bq/g)	(Bq)
Sn-123	8×10^{-1}	6×10^{-1}	1×10^3	1×10^6
Sn-125	4×10^{-1}	4×10^{-1}	1×10^2	1×10^5
Sn-126 (a)	6×10^{-1}	4×10^{-1}	1×10^1	1×10^5
Strontium (38)				
Sr-82 (a)	2×10^{-1}	2×10^{-1}	1×10^1	1×10^5
Sr-83	1×10^0	1×10^0	1×10^1	1×10^6
Sr-85	2×10^0	2×10^0	1×10^2	1×10^6
Sr-85m	5×10^0	5×10^0	1×10^2	1×10^7
Sr-87m	3×10^0	3×10^0	1×10^2	1×10^6
Sr-89	6×10^{-1}	6×10^{-1}	1×10^3	1×10^6
Sr-90 (a)	3×10^{-1}	3×10^{-1}	1×10^2 (b)	1×10^4 (b)
Sr-91 (a)	3×10^{-1}	3×10^{-1}	1×10^1	1×10^5
Sr-92 (a)	1×10^0	3×10^{-1}	1×10^1	1×10^6
Tritium (1)				
T(H-3)	4×10^1	4×10^1	1×10^6	1×10^9
Tantalum (73)				
Ta-178 (long lived)	1×10^0	8×10^{-1}	1×10^1	1×10^6
Ta-179	3×10^1	3×10^1	1×10^3	1×10^7
Ta-182	9×10^{-1}	5×10^{-1}	1×10^1	1×10^4
Terbium (65)				
Tb-149	8×10^{-1}	8×10^{-1}	1×10^1	1×10^6
Tb-157	4×10^1	4×10^1	1×10^4	1×10^7
Tb-158	1×10^0	1×10^0	1×10^1	1×10^6
Tb-160	1×10^0	6×10^{-1}	1×10^1	1×10^6
Tb-161	3×10^1	7×10^{-1}	1×10^3	1×10^6
Technetium (43)				
Tc-95m (a)	2×10^0	2×10^0	1×10^1	1×10^6
Tc-96	4×10^{-1}	4×10^{-1}	1×10^1	1×10^6

For footnotes see pp. 42–45

ACTIVITY LIMITS AND CLASSIFICATION

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1	A_2	Activity concentration limit for exempt material	Activity limit for an exempt <i>consignment</i>
	(TBq)	(TBq)	(Bq/g)	(Bq)
Tc-96m (a)	4×10^{-1}	4×10^{-1}	1×10^3	1×10^7
Tc-97	Unlimited	Unlimited	1×10^3	1×10^8
Tc-97m	4×10^1	1×10^0	1×10^3	1×10^7
Tc-98	8×10^{-1}	7×10^{-1}	1×10^1	1×10^6
Tc-99	4×10^1	9×10^{-1}	1×10^4	1×10^7
Tc-99m	1×10^1	4×10^0	1×10^2	1×10^7
Tellurium (52)				
Te-121	2×10^0	2×10^0	1×10^1	1×10^6
Te-121m	5×10^0	3×10^0	1×10^2	1×10^6
Te-123m	8×10^0	1×10^0	1×10^2	1×10^7
Te-125m	2×10^1	9×10^{-1}	1×10^3	1×10^7
Te-127	2×10^1	7×10^{-1}	1×10^3	1×10^6
Te-127m (a)	2×10^1	5×10^{-1}	1×10^3	1×10^7
Te-129	7×10^{-1}	6×10^{-1}	1×10^2	1×10^6
Te-129m (a)	8×10^{-1}	4×10^{-1}	1×10^3	1×10^6
Te-131m (a)	7×10^{-1}	5×10^{-1}	1×10^1	1×10^6
Te-132 (a)	5×10^{-1}	4×10^{-1}	1×10^2	1×10^7
Thorium (90)				
Th-227	1×10^1	5×10^{-3}	1×10^1	1×10^4
Th-228 (a)	5×10^{-1}	1×10^{-3}	1×10^0 (b)	1×10^4 (b)
Th-229	5×10^0	5×10^{-4}	1×10^0 (b)	1×10^3 (b)
Th-230	1×10^1	1×10^{-3}	1×10^0	1×10^4
Th-231	4×10^1	2×10^{-2}	1×10^3	1×10^7
Th-232	Unlimited	Unlimited	1×10^1	1×10^4
Th-234 (a)	3×10^{-1}	3×10^{-1}	1×10^3 (b)	1×10^5 (b)
Th (natural)	Unlimited	Unlimited	1×10^0 (b)	1×10^3 (b)
Titanium (22)				
Ti-44 (a)	5×10^{-1}	4×10^{-1}	1×10^1	1×10^5

For footnotes see pp. 42–45

SECTION IV

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1	A_2	Activity concentration limit for exempt material	Activity limit for an exempt <i>consignment</i>
	(TBq)	(TBq)	(Bq/g)	(Bq)
Thallium (81)				
Tl-200	9×10^{-1}	9×10^{-1}	1×10^1	1×10^6
Tl-201	1×10^1	4×10^0	1×10^2	1×10^6
Tl-202	2×10^0	2×10^0	1×10^2	1×10^6
Tl-204	1×10^1	7×10^{-1}	1×10^4	1×10^4
Thulium (69)				
Tm-167	7×10^0	8×10^{-1}	1×10^2	1×10^6
Tm-170	3×10^0	6×10^{-1}	1×10^3	1×10^6
Tm-171	4×10^1	4×10^1	1×10^4	1×10^8
Uranium (92)				
U-230 (fast lung absorption) (a)(d)	4×10^1	1×10^{-1}	1×10^1 (b)	1×10^5 (b)
U-230 (medium lung absorption) (a)(e)	4×10^1	4×10^{-3}	1×10^1	1×10^4
U-230 (slow lung absorption) (a)(f)	3×10^1	3×10^{-3}	1×10^1	1×10^4
U-232 (fast lung absorption) (d)	4×10^1	1×10^{-2}	1×10^0 (b)	1×10^3 (b)
U-232 (medium lung absorption) (e)	4×10^1	7×10^{-3}	1×10^1	1×10^4
U-232 (slow lung absorption) (f)	1×10^1	1×10^{-3}	1×10^1	1×10^4
U-233 (fast lung absorption) (d)	4×10^1	9×10^{-2}	1×10^1	1×10^4
U-233 (medium lung absorption) (e)	4×10^1	2×10^{-2}	1×10^2	1×10^5
U-233 (slow lung absorption) (f)	4×10^1	6×10^{-3}	1×10^1	1×10^5
U-234 (fast lung absorption) (d)	4×10^1	9×10^{-2}	1×10^1	1×10^4
U-234 (medium lung absorption) (e)	4×10^1	2×10^{-2}	1×10^2	1×10^5

For footnotes see pp. 42–45

ACTIVITY LIMITS AND CLASSIFICATION

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1 (TBq)	A_2 (TBq)	Activity concentration limit for exempt material (Bq/g)	Activity limit for an exempt <i>consignment</i> (Bq)
U-234 (slow lung absorption) (f)	4×10^1	6×10^{-3}	1×10^1	1×10^5
U-235 (all lung absorption types) (a)(d)(e)(f)	Unlimited	Unlimited	1×10^1 (b)	1×10^4 (b)
U-236 (fast lung absorption) (d)	Unlimited	Unlimited	1×10^1	1×10^4
U-236 (medium lung absorption) (e)	4×10^1	2×10^{-2}	1×10^2	1×10^5
U-236 (slow lung absorption) (f)	4×10^1	6×10^{-3}	1×10^1	1×10^4
U-238 (all lung absorption types) (d)(e)(f)	Unlimited	Unlimited	1×10^1 (b)	1×10^4 (b)
U (natural)	Unlimited	Unlimited	1×10^0 (b)	1×10^3 (b)
U (enriched to 20% or less) (g)	Unlimited	Unlimited	1×10^0	1×10^3
U (depleted)	Unlimited	Unlimited	1×10^0	1×10^3
Vanadium (23)				
V-48	4×10^{-1}	4×10^{-1}	1×10^1	1×10^5
V-49	4×10^1	4×10^1	1×10^4	1×10^7
Tungsten (74)				
W-178 (a)	9×10^0	5×10^0	1×10^1	1×10^6
W-181	3×10^1	3×10^1	1×10^3	1×10^7
W-185	4×10^1	8×10^{-1}	1×10^4	1×10^7
W-187	2×10^0	6×10^{-1}	1×10^2	1×10^6
W-188 (a)	4×10^{-1}	3×10^{-1}	1×10^2	1×10^5
Xenon (54)				
Xe-122 (a)	4×10^{-1}	4×10^{-1}	1×10^2	1×10^9
Xe-123	2×10^0	7×10^{-1}	1×10^2	1×10^9
Xe-127	4×10^0	2×10^0	1×10^3	1×10^5

For footnotes see pp. 42–45

SECTION IV

TABLE 2. BASIC RADIONUCLIDE VALUES (cont.)

Radionuclide (atomic number)	A_1 (TBq)	A_2 (TBq)	Activity concentration limit for exempt material (Bq/g)	Activity limit for an exempt <i>consignment</i> (Bq)
Xe-131m	4×10^1	4×10^1	1×10^4	1×10^4
Xe-133	2×10^1	1×10^1	1×10^3	1×10^4
Xe-135	3×10^0	2×10^0	1×10^3	1×10^{10}
Yttrium (39)				
Y-87 (a)	1×10^0	1×10^0	1×10^1	1×10^6
Y-88	4×10^{-1}	4×10^{-1}	1×10^1	1×10^6
Y-90	3×10^{-1}	3×10^{-1}	1×10^3	1×10^5
Y-91	6×10^{-1}	6×10^{-1}	1×10^3	1×10^6
Y-91m	2×10^0	2×10^0	1×10^2	1×10^6
Y-92	2×10^{-1}	2×10^{-1}	1×10^2	1×10^5
Y-93	3×10^{-1}	3×10^{-1}	1×10^2	1×10^5
Ytterbium (70)				
Yb-169	4×10^0	1×10^0	1×10^2	1×10^7
Yb-175	3×10^1	9×10^{-1}	1×10^3	1×10^7
Zinc (30)				
Zn-65	2×10^0	2×10^0	1×10^1	1×10^6
Zn-69	3×10^0	6×10^{-1}	1×10^4	1×10^6
Zn-69m (a)	3×10^0	6×10^{-1}	1×10^2	1×10^6
Zirconium (40)				
Zr-88	3×10^0	3×10^0	1×10^2	1×10^6
Zr-93	Unlimited	Unlimited	1×10^3 (b)	1×10^7 (b)
Zr-95 (a)	2×10^0	8×10^{-1}	1×10^1	1×10^6
Zr-97 (a)	4×10^{-1}	4×10^{-1}	1×10^1 (b)	1×10^5 (b)

(a) A_1 and/or A_2 values for these parent radionuclides include contributions from their progeny with half-lives less than 10 days, as listed in the following:

Mg-28	Al-28
Ca-47	Sc-47
Ti-44	Sc-44

ACTIVITY LIMITS AND CLASSIFICATION

Table 2, footnote (a) (cont.)

Fe-52	Mn-52m
Fe-60	Co-60m
Zn-69m	Zn-69
Ge-68	Ga-68
Rb-83	Kr-83m
Sr-82	Rb-82
Sr-90	Y-90
Sr-91	Y-91m
Sr-92	Y-92
Y-87	Sr-87m
Zr-95	Nb-95m
Zr-97	Nb-97m, Nb-97
Mo-99	Tc-99m
Tc-95m	Tc-95
Tc-96m	Tc-96
Ru-103	Rh-103m
Ru-106	Rh-106
Pd-103	Rh-103m
Ag-108m	Ag-108
Ag-110m	Ag-110
Cd-115	In-115m
In-114m	In-114
Sn-113	In-113m
Sn-121m	Sn-121
Sn-126	Sb-126m
Te-127m	Te-127
Te-129m	Te-129
Te-131m	Te-131
Te-132	I-132
I-135	Xe-135m
Xe-122	I-122
Cs-137	Ba-137m
Ba-131	Cs-131
Ba-140	La-140
Ce-144	Pr-144m, Pr-144
Pm-148m	Pm-148
Gd-146	Eu-146
Dy-166	Ho-166
Hf-172	Lu-172
W-178	Ta-178
W-188	Re-188
Re-189	Os-189m
Os-194	Ir-194
Ir-189	Os-189m
Pt-188	Ir-188

SECTION IV

Table 2, footnote (a) (cont.)

Hg-194	Au-194
Hg-195m	Hg-195
Pb-210	Bi-210
Pb-212	Bi-212, Tl-208, Po-212
Bi-210m	Tl-206
Bi-212	Tl-208, Po-212
At-211	Po-211
Rn-222	Po-218, Pb-214, At-218, Bi-214, Po-214
Ra-223	Rn-219, Po-215, Pb-211, Bi-211, Po-211, Tl-207
Ra-224	Rn-220, Po-216, Pb-212, Bi-212, Tl-208, Po-212
Ra-225	Ac-225, Fr-221, At-217, Bi-213, Tl-209, Po-213, Pb-209
Ra-226	Rn-222, Po-218, Pb-214, At-218, Bi-214, Po-214
Ra-228	Ac-228
Ac-225	Fr-221, At-217, Bi-213, Tl-209, Po-213, Pb-209
Ac-227	Fr-223
Th-228	Ra-224, Rn-220, Po-216, Pb-212, Bi-212, Tl-208, Po-212
Th-234	Pa-234m, Pa-234
Pa-230	Ac-226, Th-226, Fr-222, Ra-222, Rn-218, Po-214
U-230	Th-226, Ra-222, Rn-218, Po-214
U-235	Th-231
Pu-241	U-237
Pu-244	U-240, Np-240m
Am-242m	Am-242, Np-238
Am-243	Np-239
Cm-247	Pu-243
Bk-249	Am-245
Cf-253	Cm-249

- (b) Parent nuclides and their progeny included in secular equilibrium are listed in the following (the activity to be taken into account is that of the parent nuclide only):

Sr-90	Y-90
Zr-93	Nb-93m
Zr-97	Nb-97
Ru-106	Rh-106
Ag-108m	Ag-108
Cs-137	Ba-137m
Ce-144	Pr-144
Ba-140	La-140
Bi-212	Tl-208 (0.36), Po-212 (0.64)
Pb-210	Bi-210, Po-210
Pb-212	Bi-212, Tl-208 (0.36), Po-212 (0.64)
Rn-222	Po-218, Pb-214, Bi-214, Po-214
Ra-223	Rn-219, Po-215, Pb-211, Bi-211, Tl-207
Ra-224	Rn-220, Po-216, Pb-212, Bi-212, Tl-208 (0.36), Po-212 (0.64)

ACTIVITY LIMITS AND CLASSIFICATION

Table 2, footnote (b) (cont.)

Ra-226	Rn-222, Po-218, Pb-214, Bi-214, Po-214, Pb-210, Bi-210, Po-210
Ra-228	Ac-228
Th-228	Ra-224, Rn-220, Po-216, Pb-212, Bi-212, Tl-208 (0.36), Po-212 (0.64)
Th-229	Ra-225, Ac-225, Fr-221, At-217, Bi-213, Po-213, Pb-209
Th-natural*	Ra-228, Ac-228, Th-228, Ra-224, Rn-220, Po-216, Pb-212, Bi-212, Tl-208 (0.36), Po-212 (0.64)
Th-234	Pa-234m
U-230	Th-226, Ra-222, Rn-218, Po-214
U-232	Th-228, Ra-224, Rn-220, Po-216, Pb-212, Bi-212, Tl-208 (0.36), Po-212 (0.64)
U-235	Th-231
U-238	Th-234, Pa-234m
U-natural*	Th-234, Pa-234m, U-234, Th-230, Ra-226, Rn-222, Po-218, Pb-214, Bi-214, Po-214, Pb-210, Bi-210, Po-210
Np-237	Pa-233
Am-242m	Am-242
Am-243	Np-239

* In the case of Th-natural, the parent nuclide is Th-232; in the case of U-natural the parent nuclide is U-238.

- (c) The quantity may be determined from a measurement of the rate of decay or a measurement of the *dose rate* at a prescribed distance from the source.
- (d) These values apply only to compounds of *uranium* that take the chemical form of UF_6 , UO_2F_2 and $\text{UO}_2(\text{NO}_3)_2$ in both normal and accident conditions of transport.
- (e) These values apply only to compounds of *uranium* that take the chemical form of UO_3 , UF_4 , UCl_4 and hexavalent compounds in both normal and accident conditions of transport.
- (f) These values apply to all compounds of *uranium* other than those specified in (d) and (e) above.
- (g) These values apply to *unirradiated uranium* only.

406. When the identity of each radionuclide is known but the individual activities of some of the radionuclides are not known, the radionuclides may be grouped and the lowest radionuclide value, as appropriate for the radionuclides in each group, may be used in applying the formulas in paras 405 and 430. Groups may be based on the total alpha activity and the total beta/gamma activity, when these are known, using the lowest radionuclide values for the alpha emitters or beta/gamma emitters, respectively.

407. For individual radionuclides or for mixtures of radionuclides for which relevant data are not available, the values shown in Table 3 shall be used.

SECTION IV

TABLE 3. BASIC RADIONUCLIDE VALUES FOR UNKNOWN RADIONUCLIDES OR MIXTURES

<i>Radioactive content</i>	A_1	A_2	Activity concentration limit for exempt material	Activity limit for an exempt consignment
	(TBq)	(TBq)	(Bq/g)	(Bq)
Only beta or gamma emitting nuclides are known to be present	0.1	0.02	1×10^1	1×10^4
Alpha emitting nuclides, but no neutron emitters are known to be present	0.2	9×10^{-5}	1×10^{-1}	1×10^3
Neutron emitting nuclides are known to be present or no relevant data are available	0.001	9×10^{-5}	1×10^{-1}	1×10^3

CLASSIFICATION OF MATERIAL

Low specific activity material

408. *Radioactive material* may only be classified as *LSA material* if the conditions of paras 226, 409–411 and 517–522 are met.

409. *LSA material* shall be in one of three groups:

(a) *LSA-I:*

- (i) *Uranium* and thorium ores and concentrates of such ores, and other ores containing naturally occurring radionuclides.
- (ii) *Natural uranium, depleted uranium*, natural thorium or their compounds or mixtures, that are unirradiated and in solid or liquid form.
- (iii) *Radioactive material* for which the A_2 value is unlimited. *Fissile material* may be included only if excepted under para. 417.
- (iv) Other *radioactive material* in which the activity is distributed throughout and the estimated average *specific activity* does not exceed 30 times the values for the activity concentration specified in paras 402–407. *Fissile material* may be included only if excepted under para. 417.

ACTIVITY LIMITS AND CLASSIFICATION

- (b) *LSA-II*:
 - (i) Water with a tritium concentration of up to 0.8 TBq/L;
 - (ii) Other material in which the activity is distributed throughout and the estimated average *specific activity* does not exceed $10^{-4}A_2/\text{g}$ for solids and gases, and $10^{-5}A_2/\text{g}$ for liquids.
- (c) *LSA-III*:

Solids (e.g. consolidated wastes, activated materials), excluding powders, in which:

 - (i) The *radioactive material* is distributed throughout a solid or a collection of solid objects, or is essentially uniformly distributed in a solid compact binding agent (such as concrete, bitumen and ceramic).
 - (ii) The estimated average *specific activity* of the solid, excluding any shielding material, does not exceed $2 \times 10^{-3}A_2/\text{g}$.

410. A single *package* of non-combustible solid *LSA-II* or *LSA-III* material, if carried by air, shall not contain an activity greater than $3000A_2$.

411. The *radioactive contents* in a single *package* of *LSA material* shall be so restricted that the *dose rate* specified in para. 517 shall not be exceeded, and the activity in a single *package* shall also be so restricted that the activity limits for a *conveyance* specified in para. 522 shall not be exceeded.

Surface contaminated object

412. *Radioactive material* may be classified as *SCO* if the conditions in paras 241, 413, 414 and 517–522 are met.

413. *SCO* shall be in one of three groups:

- (a) *SCO-I*: A solid object on which:
 - (i) The *non-fixed contamination* on the accessible surface averaged over 300 cm^2 (or the area of the surface if less than 300 cm^2) does not exceed 4 Bq/cm^2 for beta and gamma emitters and *low toxicity alpha emitters*, or 0.4 Bq/cm^2 for all other alpha emitters;
 - (ii) The *fixed contamination* on the accessible surface averaged over 300 cm^2 (or the area of the surface if less than 300 cm^2) does not exceed $4 \times 10^4 \text{ Bq/cm}^2$ for beta and gamma emitters and *low toxicity alpha emitters*, or 4000 Bq/cm^2 for all other alpha emitters;

SECTION IV

- (iii) The *non-fixed contamination* plus the *fixed contamination* on the inaccessible surface averaged over 300 cm^2 (or the area of the surface if less than 300 cm^2) does not exceed $4 \times 10^4\text{ Bq/cm}^2$ for beta and gamma emitters and *low toxicity alpha emitters*, or 4000 Bq/cm^2 for all other alpha emitters.
- (b) *SCO-II*: A solid object on which either the *fixed* or *non-fixed contamination* on the surface exceeds the applicable limits specified for *SCO-I* in (a) above and on which:
 - (i) The *non-fixed contamination* on the accessible surface averaged over 300 cm^2 (or the area of the surface if less than 300 cm^2) does not exceed 400 Bq/cm^2 for beta and gamma emitters and *low toxicity alpha emitters*, or 40 Bq/cm^2 for all other alpha emitters;
 - (ii) The *fixed contamination* on the accessible surface averaged over 300 cm^2 (or the area of the surface if less than 300 cm^2) does not exceed $8 \times 10^5\text{ Bq/cm}^2$ for beta and gamma emitters and *low toxicity alpha emitters*, or $8 \times 10^4\text{ Bq/cm}^2$ for all other alpha emitters;
 - (iii) The *non-fixed contamination* plus the *fixed contamination* on the inaccessible surface averaged over 300 cm^2 (or the area of the surface if less than 300 cm^2) does not exceed $8 \times 10^5\text{ Bq/cm}^2$ for beta and gamma emitters and *low toxicity alpha emitters*, or $8 \times 10^4\text{ Bq/cm}^2$ for all other alpha emitters.
- (c) *SCO-III*: A large solid object which, because of its size, cannot be transported in a type of *package* described in these Regulations and for which:
 - (i) All openings are sealed to prevent release of *radioactive material* during conditions defined in para. 520(e);
 - (ii) The inside of the object is as dry as practicable;
 - (iii) The *non-fixed contamination* on the external surfaces does not exceed the limits specified in para. 508;
 - (iv) The *non-fixed contamination* plus the *fixed contamination* on the inaccessible surface averaged over 300 cm^2 does not exceed $8 \times 10^5\text{ Bq/cm}^2$ for beta and gamma emitters and *low toxicity alpha emitters*, or $8 \times 10^4\text{ Bq/cm}^2$ for all other alpha emitters.

414. The *radioactive contents* in a single *package* of *SCO* shall be so restricted that the *dose rate* specified in para. 517 shall not be exceeded, and the activity in a single *package* shall also be so restricted that the activity limits for a *conveyance* specified in para. 522 shall not be exceeded.

Special form radioactive material

415. *Radioactive material* may be classified as *special form radioactive material* only if it meets the requirements of paras 602–604 and 802.

Low dispersible radioactive material

416. *Radioactive material* may be classified as *low dispersible radioactive material* only if it meets the requirements of para. 605, taking into account the requirements of paras 665 and 802.

Fissile material

417. *Fissile material* and *packages* containing *fissile material* shall be classified under the relevant entry as “FISSILE” in accordance with Table 1 unless excepted by one of the provisions of subparagraphs (a)–(f) of this paragraph and transported subject to the requirements of para. 570. All provisions apply only to material in *packages* that meet the requirements of para. 636, unless unpackaged material is specifically allowed in the provision:

- (a) *Uranium* enriched in uranium-235 to a maximum of 1% by mass, and with a total plutonium and uranium-233 content not exceeding 1% of the mass of uranium-235, provided that the *fissile nuclides* are distributed essentially homogeneously throughout the material. In addition, if uranium-235 is present in metallic, oxide or carbide forms, it shall not form a lattice arrangement.
- (b) Liquid solutions of uranyl nitrate enriched in uranium-235 to a maximum of 2% by mass, with a total plutonium and uranium-233 content not exceeding 0.002% of the mass of *uranium*, and with a minimum nitrogen to *uranium* atomic ratio (N/U) of 2.
- (c) *Uranium* with a maximum *uranium* enrichment of 5% by mass of uranium-235 provided:
 - (i) There is no more than 3.5 g of uranium-235 per *package*.
 - (ii) The total plutonium and uranium-233 content does not exceed 1% of the mass of uranium-235 per *package*.
 - (iii) Transport of the *package* is subject to the *consignment* limit provided in para. 570(c).
- (d) *Fissile nuclides* with a total mass not greater than 2.0 g per *package*, provided the *package* is transported subject to the *consignment* limit provided in para. 570(d).

SECTION IV

- (e) *Fissile nuclides* with a total mass not greater than 45 g, either packaged or unpackaged, subject to the requirements of para. 570(e).
- (f) A *fissile material* that meets the requirements of paras 570(b), 606 and 802.

418. The contents of *packages* containing *fissile material* shall be as specified for the *package design*, either directly in these Regulations or in the certificate of *approval*.

Uranium hexafluoride

419. Uranium hexafluoride shall be assigned to one of the following UN numbers only:

- (a) UN 2977, RADIOACTIVE MATERIAL, URANIUM HEXAFLUORIDE, FISSILE;
- (b) UN 2978, RADIOACTIVE MATERIAL, URANIUM HEXAFLUORIDE, non-fissile or fissile-excepted;
- (c) UN 3507, URANIUM HEXAFLUORIDE, RADIOACTIVE MATERIAL, EXCEPTED PACKAGE, less than 0.1 kg per *package*, non-fissile or fissile-excepted.

420. The contents of a *package* containing uranium hexafluoride shall comply with the following requirements:

- (a) The mass of uranium hexafluoride shall not be different from that allowed for by the *package design*.
- (b) The mass of uranium hexafluoride shall not be greater than a value that would lead to an ullage of less than 5% at the maximum temperature of the *package*, as specified for in the plant systems where the *package* might be used.
- (c) The uranium hexafluoride shall be in solid form and the internal pressure shall not be above atmospheric pressure when presented for transport.

CLASSIFICATION OF PACKAGES

421. The quantity of *radioactive material* in a *package* shall not exceed the relevant limits for the *package* type as specified below.

Classification as excepted package

422. A *package* may be classified as an *excepted package* if it meets one of the following conditions:

- (a) It is an empty *package* having contained *radioactive material*;
- (b) It contains instruments or articles not exceeding the activity limits specified in Table 4;
- (c) It contains articles manufactured of *natural uranium*, *depleted uranium* or natural thorium;
- (d) It contains *radioactive material* not exceeding the activity limits specified in Table 4;
- (e) It contains less than 0.1 kg of uranium hexafluoride not exceeding the activity limits specified in column 4 of Table 4.

423. *Radioactive material* that is enclosed in or is included as a component part of an instrument or other manufactured article, may be classified under UN 2911, RADIOACTIVE MATERIAL, EXCEPTED PACKAGE — INSTRUMENTS or ARTICLES, provided that:

- (a) The *dose rate* at 10 cm from any point on the external surface of any unpackaged instrument or article is not greater than 0.1 mSv/h.

TABLE 4. ACTIVITY LIMITS FOR EXCEPTED PACKAGES

Physical state of contents	Instrument or article		Materials
	Item limits ^a	Package limits ^a	Package limits ^a
Solids			
<i>Special form</i>	$10^{-2}A_1$	A_1	$10^{-3}A_1$
Other forms	$10^{-2}A_2$	A_2	$10^{-3}A_2$
Liquids	$10^{-3}A_2$	$10^{-1}A_2$	$10^{-4}A_2$
Gases			
Tritium	$2 \times 10^{-2}A_2$	$2 \times 10^{-1}A_2$	$2 \times 10^{-2}A_2$
<i>Special form</i>	$10^{-3}A_1$	$10^{-2}A_1$	$10^{-3}A_1$
Other forms	$10^{-3}A_2$	$10^{-2}A_2$	$10^{-3}A_2$

^a For mixtures of radionuclides, see paras 405–407.

SECTION IV

- (b) Each instrument or article bears the mark “RADIOACTIVE” on its external surface except for the following:
 - (i) Radioluminescent timepieces or devices do not require marks.
 - (ii) Consumer products that have either received regulatory *approval* in accordance with para. 107(e) or do not individually exceed the activity limit for an exempt *consignment* in Table 2 (column 5) do not require marks, provided that such products are transported in a *package* that bears the mark “RADIOACTIVE” on its internal surface in such a manner that a warning of the presence of *radioactive material* is visible on opening the *package*.
 - (iii) Other instruments or articles too small to bear the mark “RADIOACTIVE” do not require marks, provided that they are transported in a *package* that bears the mark “RADIOACTIVE” on its internal surface in such a manner that a warning of the presence of *radioactive material* is visible on opening the *package*.
- (c) The active material is completely enclosed by non-active components (a device performing the sole function of containing *radioactive material* shall not be considered to be an instrument or manufactured article).
- (d) The limits specified in columns 2 and 3 of Table 4 are met for each individual item and each *package*, respectively.
- (e) For transport by post, the total activity in each *excepted package* shall not exceed one tenth of the relevant limits specified in column 3 of Table 4.
- (f) If the *package* contains *fissile material*, one of the provisions of subparagraphs (a)–(f) of para. 417 shall apply.

424. *Radioactive material* in forms other than as specified in para. 423 and with an activity not exceeding the limits specified in column 4 of Table 4 may be classified under UN 2910, RADIOACTIVE MATERIAL, EXCEPTED PACKAGE — LIMITED QUANTITY OF MATERIAL, provided that:

- (a) The *package* retains its *radioactive contents* under routine conditions of transport.
- (b) The *package* bears the mark “RADIOACTIVE” on either:
 - (i) An internal surface in such a manner that a warning of the presence of *radioactive material* is visible on opening the *package*; or
 - (ii) The outside of the *package*, where it is impractical to mark an internal surface.
- (c) For transport by post, the total activity in each *excepted package* shall not exceed one tenth of the relevant limits specified in column 4 of Table 4.
- (d) If the *package* contains *fissile material*, one of the provisions of subparagraphs (a)–(f) of para. 417 shall apply.

425. Uranium hexafluoride not exceeding the limits specified in column 4 of Table 4 may be classified under UN 3507 URANIUM HEXAFLUORIDE, RADIOACTIVE MATERIAL, EXCEPTED PACKAGE, less than 0.1 kg per *package*, non-fissile or fissile-excepted, provided that:

- (a) The mass of uranium hexafluoride in the *package* is less than 0.1 kg.
- (b) The conditions of paras 420, 424(a) and 424(b) are met.

426. Articles manufactured of *natural uranium*, *depleted uranium* or natural thorium and articles in which the sole *radioactive material* is unirradiated *natural uranium*, unirradiated *depleted uranium* or unirradiated natural thorium may be classified under UN 2909, RADIOACTIVE MATERIAL, EXCEPTED PACKAGE — ARTICLES MANUFACTURED FROM NATURAL URANIUM or DEPLETED URANIUM or NATURAL THORIUM, provided that the outer surface of the *uranium* or thorium is enclosed in an inactive sheath made of metal or some other substantial material.

Additional requirements and controls for transport of empty packagings

427. An empty *packaging* that had previously contained *radioactive material* may be classified under UN 2908, RADIOACTIVE MATERIAL, EXCEPTED PACKAGE — EMPTY PACKAGING, provided that:

- (a) It is in a well-maintained condition and securely closed.
- (b) The outer surface of any *uranium* or thorium in its structure is covered with an inactive sheath made of metal or some other substantial material.
- (c) The level of internal *non-fixed contamination* does not exceed 100 times the levels specified in para. 508.
- (d) Any labels that may have been displayed on it in conformity with para. 538 are no longer visible.
- (e) If the *packaging* has contained *fissile material*, one of the provisions of subparagraphs (a)–(f) of para. 417 or one of the provisions for exclusion in para. 222 shall apply.

Classification as Type A package

428. *Packages* containing *radioactive material* may be classified as *Type A packages* provided that the conditions of paras 429 and 430 are met.

429. *Type A packages* shall not contain activities greater than either of the following:

SECTION IV

- (a) For *special form radioactive material* — A_1 ;
- (b) For all other *radioactive material* — A_2 .

430. For mixtures of radionuclides whose identities and respective activities are known, the following condition shall apply to the *radioactive contents* of a *Type A package*:

$$\sum_i \frac{B(i)}{A_1(i)} + \sum_j \frac{C(j)}{A_2(j)} \leq 1$$

where

$B(i)$ is the activity of radionuclide i as *special form radioactive material*;

$A_1(i)$ is the A_1 value for radionuclide i ;

$C(j)$ is the activity of radionuclide j as other than *special form radioactive material*;

$A_2(j)$ is the A_2 value for radionuclide j .

Classification as Type B(U), Type B(M) or Type C package

431. *Type B(U)*, *Type B(M)* and *Type C packages* shall be classified in accordance with the *competent authority* certificate of *approval* for the *package design* issued by the country of origin of *design*.

432. The contents of a *Type B(U)*, *Type B(M)* or *Type C package* shall be as specified in the certificate of *approval*.

433. *Type B(U)* and *Type B(M) packages*, if transported by air, shall meet the requirements of para. 432 and shall not contain activities greater than the following:

- (a) For *low dispersible radioactive material* — as authorized for the *package design* as specified in the certificate of *approval*;
- (b) For *special form radioactive material* — $3000A_1$ or 10^5A_2 , whichever is the lower;
- (c) For all other *radioactive material* — $3000A_2$.

SPECIAL ARRANGEMENT

434. *Radioactive material* shall be classified as transported under *special arrangement* when it is intended to be carried in accordance with para. 310.

Section V

REQUIREMENTS AND CONTROLS FOR TRANSPORT

REQUIREMENTS BEFORE THE FIRST SHIPMENT

501. Before a *packaging* is first used to transport *radioactive material*, it shall be confirmed that it has been manufactured in conformity with the *design* specifications to ensure compliance with the relevant provisions of these Regulations and any applicable certificate of *approval*. The following requirements shall also be fulfilled, if applicable:

- (a) If the *design* pressure of the *containment system* exceeds 35 kPa (gauge), it shall be ensured that the *containment system* of each *packaging* conforms to the approved *design* requirements relating to the capability of that system to maintain its integrity under that pressure.
- (b) For each *packaging* intended for use as a *Type B(U)*, *Type B(M)* or *Type C package* and for each *packaging* intended to contain *fissile material*, it shall be ensured that the effectiveness of its shielding and containment and, where necessary, the heat transfer characteristics and the effectiveness of the *confinement system*, are within the limits applicable to or specified for the approved *design*.
- (c) For each *packaging* intended to contain *fissile material*, it shall be ensured that the effectiveness of the criticality safety features is within the limits applicable to or specified for the *design*, and in particular where, in order to comply with the requirements of para. 673, neutron poisons are specifically included, checks shall be performed to confirm the presence and distribution of those neutron poisons.

REQUIREMENTS BEFORE EACH SHIPMENT

502. Before each *shipment* of any *package*, it shall be ensured that the *package* contains neither:

- (a) Radionuclides different from those specified for the *package design*; nor
- (b) Contents in a form, or physical or chemical state, different from those specified for the *package design*.

SECTION V

503. Before each *shipment* of any *package*, it shall be ensured that all the requirements specified in the relevant provisions of these Regulations and in the applicable certificates of *approval* have been fulfilled. The following requirements shall also be fulfilled, if applicable:

- (a) It shall be ensured that lifting attachments that do not meet the requirements of para. 608 have been removed or otherwise rendered incapable of being used for lifting the *package*, in accordance with para. 609.
- (b) Each *Type B(U)*, *Type B(M)* and *Type C package* shall be held until equilibrium conditions have been approached closely enough to demonstrate compliance with the requirements for temperature and pressure, unless an exemption from these requirements has received *unilateral approval*.
- (c) For each *Type B(U)*, *Type B(M)* and *Type C package*, it shall be ensured by inspection and/or appropriate tests that all closures, valves and other openings of the *containment system* through which the *radioactive contents* might escape are properly closed and, where appropriate, sealed in the manner for which the demonstrations of compliance with the requirements of paras 659 and 671 were made.
- (d) For *packages* containing *fissile material*, the measurement specified in para. 677(b) and the tests to demonstrate closure of each *package* as specified in para. 680 shall be performed.
- (e) For *packages* intended to be used for *shipment* after storage, it shall be ensured that all *packaging* components and *radioactive contents* have been maintained during storage in a manner such that all the requirements specified in the relevant provisions of these Regulations and in the applicable certificates of *approval* have been fulfilled.

TRANSPORT OF OTHER GOODS

504. A *package* shall not contain any items other than those that are necessary for the use of the *radioactive material*. The interaction between these items and the *package*, under the conditions of transport applicable to the *design*, shall not reduce the safety of the *package*.

505. *Freight containers*, *IBCs*, *tanks*, as well as other *packagings* and *overpacks*, used for the transport of *radioactive material* shall not be used for the storage or transport of other goods unless decontaminated below the level of 0.4 Bq/cm² for beta and gamma emitters and *low toxicity alpha emitters* and 0.04 Bq/cm² for all other alpha emitters.

REQUIREMENTS AND CONTROLS FOR TRANSPORT

506. *Consignments* shall be segregated from other dangerous goods during transport in compliance with the relevant transport regulations for dangerous goods of each of the countries *through or into* which the materials will be transported, and, where applicable, with the regulations of the cognizant transport organizations, as well as these Regulations.

OTHER DANGEROUS PROPERTIES OF CONTENTS

507. In addition to the radioactive and fissile properties, any other dangerous properties of the contents of the *package*, such as explosiveness, flammability, pyrophoricity, chemical toxicity and corrosiveness, shall be taken into account in the packing, labelling, marking, placarding, storage and transport in order to be in compliance with the relevant transport regulations for dangerous goods of each of the countries *through or into* which the materials will be transported, and, where applicable, with the regulations of the cognizant transport organizations, as well as these Regulations.

REQUIREMENTS AND CONTROLS FOR CONTAMINATION AND FOR LEAKING PACKAGES

508. The *non-fixed contamination* on the external surfaces of any *package* shall be kept as low as practicable and, under routine conditions of transport, shall not exceed the following limits:

- (a) 4 Bq/cm² for beta and gamma emitters and *low toxicity alpha emitters*;
- (b) 0.4 Bq/cm² for all other alpha emitters.

These limits are applicable when averaged over any area of 300 cm² of any part of the surface.

509. Except as provided in para. 514, the level of *non-fixed contamination* on the external and internal surfaces of *overpacks*, *freight containers* and *conveyances* shall not exceed the limits specified in para. 508. This requirement does not apply to the internal surfaces of *freight containers* being used as *packagings*, either loaded or empty.

510. If it is evident that a *package* is damaged or leaking, or if it is suspected that the *package* may have leaked or been damaged, access to the *package* shall be restricted and a qualified person shall, as soon as possible, assess the extent

SECTION V

of *contamination* and the resultant *dose rate* of the *package*. The scope of the assessment shall include the *package*, the *conveyance*, the adjacent loading and unloading areas and, if necessary, all other material that has been carried in the *conveyance*. When necessary, additional steps for the protection of people, property and the environment, in accordance with provisions established by the relevant *competent authority*, shall be taken to overcome and minimize the consequences of such leakage or damage.

511. *Packages* that are damaged or leaking *radioactive contents* in excess of allowable limits for normal conditions of transport may be removed to an acceptable interim location under supervision, but shall not be forwarded until repaired or reconditioned and decontaminated.

512. A *conveyance* and equipment used regularly for the transport of *radioactive material* shall be periodically checked to determine the level of *contamination*. The frequency of such checks shall be related to the likelihood of *contamination* and the extent to which *radioactive material* is transported.

513. Except as provided in para. 514, any *conveyance*, or equipment or part thereof that has become contaminated above the limits specified in para. 508 in the course of the transport of *radioactive material*, or that shows a *dose rate* in excess of 5 $\mu\text{Sv/h}$ at the surface, shall be decontaminated as soon as possible by a qualified person and shall not be reused unless the following conditions are fulfilled:

- (a) The *non-fixed contamination* shall not exceed the limits specified in para. 508.
- (b) The *dose rate* resulting from the *fixed contamination* shall not exceed 5 $\mu\text{Sv/h}$ at the surface.

514. A *freight container* or *conveyance* dedicated to the transport of unpackaged *radioactive material* under *exclusive use* shall be excepted from the requirements of paras 509 and 513 solely with regard to its internal surfaces and only for as long as it remains under that specific *exclusive use*.

REQUIREMENTS AND CONTROLS FOR TRANSPORT OF EXCEPTED PACKAGES

515. *Excepted packages* shall be subject only to the following provisions in Sections V and VI:

REQUIREMENTS AND CONTROLS FOR TRANSPORT

- (a) The requirements specified in paras 503–505; 507–513; 516; 530–533; 545; 546 introductory sentence; 546(a); 546(j),(i) and (ii); 546(k); 546(m); 550–553; 555; 556; 561; 564; 570; 582 and 583;
- (b) The requirements for *excepted packages* specified in para. 622;
- (c) The requirements specified in paras 580 and 581, if transported by post.

All relevant provisions of the other sections shall apply to *excepted packages*.

516. The *dose rate* at any point on the external surface of an *excepted package* shall not exceed 5 $\mu\text{Sv/h}$.

REQUIREMENTS AND CONTROLS FOR TRANSPORT OF LSA MATERIAL AND SCO IN INDUSTRIAL PACKAGES OR UNPACKAGED

517. The quantity of *LSA material* or *SCO* in a single *Type IP-1*, *Type IP-2*, *Type IP-3 package*, or object or collection of objects, whichever is appropriate, shall be so restricted that the external *dose rate* at 3 m from the unshielded material or object or collection of objects does not exceed 10 mSv/h.

518. For *LSA material* and *SCO* that are or contain *fissile material* that is not excepted under para. 417, the applicable requirements of paras 568 and 569 shall be met.

519. For *LSA material* and *SCO* that are, or contain, *fissile material*, the applicable requirements of para. 673 shall be met.

520. *LSA material* and *SCO* in groups *LSA-I*, *SCO-I* and *SCO-III* may be transported, unpackaged, under the following conditions:

- (a) All unpackaged material other than ores containing only naturally occurring radionuclides shall be transported in such a manner that under routine conditions of transport there will be no escape of the *radioactive contents* from the *conveyance* nor will there be any loss of shielding.
- (b) Each *conveyance* shall be under *exclusive use*, except when only transporting *SCO-I* on which the *contamination* on the accessible and the inaccessible surfaces is not greater than 10 times the applicable level specified in para. 214.
- (c) For *SCO-I* where it is suspected that *non-fixed contamination* exists on inaccessible surfaces in excess of the values specified in para. 413(a)(i),

SECTION V

measures shall be taken to ensure that the *radioactive material* is not released into the *conveyance*.

- (d) Unpackaged *fissile material* shall meet the requirement of para. 417(e).
- (e) For *SCO-III*;
 - (i) Transport shall be under *exclusive use* by road, rail, inland waterway or sea.
 - (ii) Stacking shall not be permitted.
 - (iii) All activities associated with the *shipment*, including radiation protection, emergency response and any special precautions or special administrative or operational controls that are to be employed during transport shall be described in a transport plan. The transport plan shall demonstrate that the overall level of safety in transport is at least equivalent to that which would be provided if the requirements of para. 648 (only for the test specified in para. 724, preceded by the tests specified in paras 720 and 721) had been met.
 - (iv) The requirements of para. 624 for a *Type IP-2 package* shall be satisfied, except that the maximum damage referred to in para. 722 may be determined based on provisions in the transport plan, and the requirements of para. 723 are not applicable.
 - (v) The object and any shielding are secured to the *conveyance* in accordance with para. 607.
 - (vi) The *shipment* shall be subject to *multilateral approval*.

521. *LSA material* and *SCO*, except as otherwise specified in para. 520, shall be packaged in accordance with Table 5.

522. The total activity in a single hold or compartment of an inland waterway craft, or in another *conveyance*, for carriage of *LSA material* or *SCO* in a *Type IP-1*, *Type IP-2*, *Type IP-3 package* or unpackaged, shall not exceed the limits shown in Table 6. For *SCO-III*, the limits in Table 6 may be exceeded provided that the transport plan contains precautions which are to be employed during transport to obtain an overall level of safety at least equivalent to that which would be provided if the limits had been applied.

DETERMINATION OF TRANSPORT INDEX

523. The *TI* for a *package*, *overpack* or *freight container*, or for unpackaged *LSA-I*, *SCO-I* or *SCO-III*, shall be the number derived in accordance with the following procedure:

REQUIREMENTS AND CONTROLS FOR TRANSPORT

TABLE 5. INDUSTRIAL PACKAGE REQUIREMENTS FOR LSA MATERIAL, SCO-I AND SCO-II

<i>Radioactive contents</i>	<i>Industrial package type</i>	
	<i>Exclusive use</i>	<i>Not under exclusive use</i>
<i>LSA-I</i>		
Solid ^a	<i>Type IP-1</i>	<i>Type IP-1</i>
Liquid	<i>Type IP-1</i>	<i>Type IP-2</i>
<i>LSA-II</i>		
Solid	<i>Type IP-2</i>	<i>Type IP-2</i>
Liquid and gas	<i>Type IP-2</i>	<i>Type IP-3</i>
<i>LSA-III</i>	<i>Type IP-2</i>	<i>Type IP-3</i>
<i>SCO-I</i> ^a	<i>Type IP-1</i>	<i>Type IP-1</i>
<i>SCO-II</i>	<i>Type IP-2</i>	<i>Type IP-2</i>

^a Under the conditions specified in para. 520, *LSA-I material* and *SCO-I* may be transported unpackaged.

TABLE 6. CONVEYANCE ACTIVITY LIMITS FOR LSA MATERIAL AND SCO IN INDUSTRIAL PACKAGES OR UNPACKAGED

<i>Nature of material</i>	<i>Activity limit for conveyances other than inland waterway craft</i>	<i>Activity limit for a hold or compartment of an inland waterway craft</i>
<i>LSA-I</i>	No limit	No limit
<i>LSA-II</i> and <i>LSA-III</i> non-combustible solids	No limit	100A ₂
<i>LSA-II</i> and <i>LSA-III</i> combustible solids and all liquids and gases	100A ₂	10A ₂
<i>SCO</i> ^a	100A ₂	10A ₂

^a For *SCO-III* see para. 522.

SECTION V

- (a) Determine the maximum *dose rate* in units of millisieverts per hour (mSv/h) at a distance of 1 m from the external surfaces of the *package*, *overpack*, *freight container* or unpackaged *LSA-I*, *SCO-I* and *SCO-III*. The value determined shall be multiplied by 100. For *uranium* and thorium ores and their concentrates, the maximum *dose rate* at any point 1 m from the external surface of the load may be taken as:
 - (i) 0.4 mSv/h for ores and physical concentrates of *uranium* and thorium;
 - (ii) 0.3 mSv/h for chemical concentrates of thorium;
 - (iii) 0.02 mSv/h for chemical concentrates of *uranium*, other than uranium hexafluoride.
- (b) For *tanks*, *freight containers* and unpackaged *LSA-I*, *SCO-I* and *SCO-III*, the value determined in step (a) shall be multiplied by the appropriate factor from Table 7.
- (c) The value obtained in steps (a) and (b) shall be rounded up to the first decimal place (for example, 1.13 becomes 1.2), except that a value of 0.05 or less may be considered as zero and the resulting number is the *TI* value.

524. The *TI* for each rigid *overpack*, *freight container* or *conveyance* shall be determined as the sum of the *TIs* of all the *packages* contained therein. For a *shipment* from a single *consignor*, the *consignor* may determine the *TI* by direct measurement of *dose rate*.

524A. The *TI* for a non-rigid *overpack* shall be determined only as the sum of the *TIs* of all the *packages* within the *overpack*.

TABLE 7. MULTIPLICATION FACTORS FOR TANKS, FREIGHT CONTAINERS AND UNPACKAGED LSA-I, SCO-I AND SCO-III

Size of load ^a	Multiplication factor
size of load $\leq 1 \text{ m}^2$	1
$1 \text{ m}^2 < \text{size of load} \leq 5 \text{ m}^2$	2
$5 \text{ m}^2 < \text{size of load} \leq 20 \text{ m}^2$	3
$20 \text{ m}^2 < \text{size of load}$	10

^a Largest cross-sectional area of the load being measured.

REQUIREMENTS AND CONTROLS FOR TRANSPORT

DETERMINATION OF CRITICALITY SAFETY INDEX FOR CONSIGNMENTS, FREIGHT CONTAINERS AND OVERPACKS

525. The *CSI* for each *overpack* or *freight container* shall be determined as the sum of the *CSIs* of all the *packages* contained. The same procedure shall be followed for determining the total sum of the *CSIs* in a *consignment* or aboard a *conveyance*.

LIMITS ON TRANSPORT INDEX, CRITICALITY SAFETY INDEX AND DOSE RATES FOR PACKAGES AND OVERPACKS

526. Except for *consignments* under *exclusive use*, the *TI* of any *package* or *overpack* shall not exceed 10, nor shall the *CSI* of any *package* or *overpack* exceed 50.

527. Except for *packages* or *overpacks* transported under *exclusive use* by rail or by road under the conditions specified in para. 573(a), or under *exclusive use* and *special arrangement* by vessel or by air under the conditions specified in para. 575 or para. 579, respectively, the maximum *dose rate* at any point on the external surface of a *package* or *overpack* shall not exceed 2 mSv/h.

528. The maximum *dose rate* at any point on the external surface of a *package* or *overpack* under *exclusive use* shall not exceed 10 mSv/h.

CATEGORIES

529. *Packages*, *overpacks* and *freight containers* shall be assigned to either category I-WHITE, II-YELLOW or III-YELLOW in accordance with the conditions specified in Table 8 and with the following requirements:

- (a) For a *package*, *overpack* or *freight container*, the *TI* and the surface *dose rate* conditions shall be taken into account in determining which category is appropriate. Where the *TI* satisfies the condition for one category but the surface *dose rate* satisfies the condition for a different category, the *package*, *overpack* or *freight container* shall be assigned to the higher category. For this purpose, category I-WHITE shall be regarded as the lowest category.
- (b) The *TI* shall be determined following the procedures specified in paras 523, 524 and 524A.

SECTION V

TABLE 8. CATEGORIES OF PACKAGES, OVERPACKS AND FREIGHT CONTAINERS

Conditions		
<i>TI</i>	Maximum <i>dose rate</i> at any point on external surface	Category
0 ^a	Not more than 0.005 mSv/h	I-WHITE
More than 0 but not more than 1 ^a	More than 0.005 mSv/h but not more than 0.5 mSv/h	II-YELLOW
More than 1 but not more than 10	More than 0.5 mSv/h but not more than 2 mSv/h	III-YELLOW
More than 10	More than 2 mSv/h but not more than 10 mSv/h	III-YELLOW ^b

^a If the measured *TI* is not greater than 0.05, the value quoted may be zero in accordance with para. 523(c).

^b Shall also be transported under *exclusive use* except for *freight containers* (see Table 10).

- (c) If the surface *dose rate* is greater than 2 mSv/h, the *package* or *overpack* shall be transported under *exclusive use* and under the provisions of paras 573(a), 575 or 579, as appropriate.
- (d) A *package* transported under a *special arrangement* shall be assigned to category III-YELLOW except under the provisions of para. 530.
- (e) An *overpack* or *freight container* that contains *packages* transported under *special arrangement* shall be assigned to category III-YELLOW except under the provisions of para. 530.

MARKING, LABELLING AND PLACARDING

530. For each *package* or *overpack*, the UN number and proper shipping name shall be determined (see Table 1). In all cases of international transport of *packages* requiring *competent authority approval* of *design* or *shipment*, for which different *approval* types apply in the different countries concerned by the *shipment*, the UN number, proper shipping name, categorization, labelling and marking shall be in accordance with the certificate of the country of origin of *design*.

Marking

531. Each *package* shall be legibly and durably marked on the outside of the *packaging* with an identification of either the *consignor* or *consignee*, or both. Each *overpack* shall be legibly and durably marked on the outside of the *overpack* with an identification of either the *consignor* or *consignee*, or both, unless these marks of all the *packages* within the *overpack* are clearly visible.

532. Each *package* shall be legibly and durably marked on the outside with the UN marks as specified in Table 9. Additionally, each *overpack* shall be legibly and durably marked with the word “OVERPACK” and the UN marks as specified in Table 9, unless all the marks of the *packages* within the *overpack* are clearly visible.

533. Each *package* of gross mass exceeding 50 kg shall have its permissible gross mass legibly and durably marked on the outside of the *packaging*.

TABLE 9. UN MARKING FOR PACKAGES AND OVERPACKS

Item	UN marks ^a
<i>Package</i> (other than an <i>excepted package</i>)	UN number, preceded by the letters “UN”, and the proper shipping name
<i>Excepted package</i> (other than those in <i>consignments</i> accepted for international movement by post)	UN number, preceded by the letters “UN”
<i>Overpack</i> (other than an <i>overpack</i> containing only <i>excepted packages</i>)	UN number, preceded by the letters “UN” for each applicable UN number in the <i>overpack</i> , followed by the proper shipping name in the case of a <i>non-excepted package</i>
<i>Overpack</i> containing only <i>excepted packages</i> (other than <i>consignments</i> accepted for international movement by post)	UN number, preceded by the letters “UN” for each applicable UN number in the <i>overpack</i>
<i>Consignment</i> accepted for international movement by post	The requirement of para. 581

^a See Table 1 for listing of UN numbers and proper shipping names.

SECTION V

534. Each *package* that conforms to:

- (a) An *IP-1*, *IP-2* or *IP-3 design* shall be legibly and durably marked on the outside of the *packaging* with “TYPE IP-1”, “TYPE IP-2” or “TYPE IP-3”, as appropriate.
- (b) A *Type A package design* shall be legibly and durably marked on the outside of the *packaging* with “TYPE A”.
- (c) An *IP-2*, *IP-3* or a *Type A package design* shall be legibly and durably marked on the outside of the *packaging* with the international *vehicle* registration code (VRI code) of the country of origin of *design* and either the name of the manufacturer or other identification of the *packaging* specified by the *competent authority* of the country of origin of *design*.

535. Each *package* that conforms to a *design* approved under one or more of paras 807–816 and 820 shall be legibly and durably marked on the outside of the *packaging* with the following information:

- (a) The identification mark allocated to that *design* by the *competent authority*;
- (b) A serial number to uniquely identify each *packaging* that conforms to that *design*;
- (c) “TYPE B(U)”, “TYPE B(M)” or “TYPE C”, in the case of a *Type B(U)*, *Type B(M)* or *Type C package design*.

536. Each *package* that conforms to a *Type B(U)*, *Type B(M)* or *Type C package design* shall have the outside of the outermost receptacle, that is resistant to the effects of fire and water, plainly marked by embossing, stamping or other means resistant to the effects of fire and water with the trefoil symbol shown in Fig. 1.

536A. Any mark on the *package* made in accordance with the requirements of paras 534(a) and (b) and 535(c) relating to the *package* type that does not relate to the UN number and proper shipping name assigned to the *consignment* shall be removed or covered.

537. Where *LSA-I* or *SCO-I* material is contained in receptacles or wrapping materials and is transported under *exclusive use*, as permitted by para. 520, the outer surface of these receptacles or wrapping materials may bear the mark “RADIOACTIVE LSA-I” or “RADIOACTIVE SCO-I”, as appropriate.




FIG. 1. Basic trefoil symbol with proportions based on a central circle of radius X . The minimum allowable size of X shall be 4 mm.

Labelling

538. Each *package*, *overpack* and *freight container* shall bear the labels conforming to the applicable models in Figs 2–4, except as allowed under the alternative provisions of para. 543 for *large freight containers* and *tanks*, according to the appropriate category. In addition, each *package*, *overpack* and *freight container* containing *fissile material*, other than *fissile material* excepted under the provisions of para. 417, shall bear labels conforming to the model in Fig. 5. Any labels that do not relate to the contents shall be removed or covered. For *radioactive material* having other dangerous properties, see para. 507.

539. The labels conforming to the applicable models in Figs 2–4 shall be affixed to two opposite sides of the outside of a *package* or *overpack* or on the outside of all four sides of a *freight container* or *tank*. The labels conforming to the model in Fig. 5, where applicable, shall be affixed adjacent to the labels conforming to the applicable models in Figs 2–4. The labels shall not cover the marks specified in paras 531–536.

SECTION V




FIG. 2. Category I-WHITE label. The minimum width of the line inside the edge forming the diamond shall be 2 mm. The background colour of the label shall be white, the colour of the trefoil and the printing shall be black, and the colour of the category bar shall be red.

Labelling for radioactive contents

540. Each label conforming to the applicable models in Figs 2–4 shall be completed with the following information:

- (a) Contents:
 - (i) Except for *LSA-I material*, the name(s) of the radionuclide(s) as taken from Table 2, using the symbols prescribed therein. For mixtures of radionuclides, the most restrictive nuclides must be listed to the extent the space on the line permits. The group of *LSA* or *SCO* shall be




FIG. 3. Category II-YELLOW label. The minimum width of the line inside the edge forming the diamond shall be 2 mm. The background colour of the upper half of the label shall be yellow and the lower half white, the colour of the trefoil and the printing shall be black, and the colour of the category bars shall be red.

shown following the name(s) of the radionuclide(s). The terms *LSA-II*, *LSA-III*, *SCO-I* and *SCO-II* shall be used for this purpose.

- (ii) For *LSA-I material*, the term *LSA-I* is all that is necessary; the name of the radionuclide is not necessary.
- (b) Activity: The maximum activity of the *radioactive contents* during transport expressed in units of becquerels (Bq) with the appropriate SI prefix symbol (see Annex II). For *fissile material*, the total mass of *fissile nuclides* in units of grams (g), or multiples thereof, may be used in place of activity.

SECTION V




FIG. 4. Category III-YELLOW label. The minimum width of the line inside the edge forming the diamond shall be 2 mm. The background colour of the upper half of the label shall be yellow and the lower half white, the colour of the trefoil and the printing shall be black, and the colour of the category bars shall be red.

- (c) For overpacks and freight containers, the “contents” and “activity” entries on the label shall bear the information required in para. 540(a) and 540(b), respectively, totalled together for the entire contents of the overpack or freight container except that on labels for overpacks or freight containers containing mixed loads of packages containing different radionuclides, such entries may read “See Transport Documents”.
- (d) TI: The number determined in accordance with paras 523, 524 and 524A (except for category I-WHITE).




FIG. 5. CSI label. The minimum width of the line inside the edge forming the diamond shall be 2 mm. The background colour of the label shall be white, the colour of the printing shall be black.

Labelling for criticality safety

541. Each label conforming to the model in Fig. 5 shall be completed with the *CSI* as stated in the certificate of *approval* applicable in the countries *through or into* which the *consignment* is transported and issued by the *competent authority* or as specified in para. 674 or para. 675.

SECTION V

542. For *overpacks* and *freight containers*, the label conforming to the model in Fig. 5 shall bear the sum of the *CSIs* of all the *packages* contained therein.

Placarding

543. *Large freight containers* carrying unpackaged *LSA-I material* or *SCO-I* or *packages* other than *excepted packages*, and *tanks* shall bear four placards that conform to the model given in Fig. 6. The placards shall be affixed in a vertical orientation to each side wall and to each end wall of the *large freight container* or *tank*. Any placards that do not relate to the contents shall be removed. Instead of using both labels and placards, it is permitted, as an alternative, to use enlarged labels only, where appropriate, as shown in Figs 2–4, except having the minimum size shown in Fig. 6.

544. Where the *consignment* in the *freight container* or *tank* is unpackaged *LSA-I* or *SCO-I* or where a *consignment* in a *freight container* is required to be shipped under *exclusive use* and is packaged *radioactive material* with a single UN number, the appropriate UN number for the *consignment* (see Table 1) shall also be displayed, in black digits not less than 65 mm high, either:

- (a) In the lower half of the placard shown in Fig. 6 and against the white background; or
- (b) On the placard shown in Fig. 7.

When the alternative given in (b) is used, the subsidiary placard shall be affixed immediately adjacent to the main placard shown in Fig. 6, on all four sides of the *freight container* or *tank*.

CONSIGNOR'S RESPONSIBILITIES

545. Except as otherwise provided in these Regulations, no person may offer *radioactive material* for transport unless it is properly marked, labelled, placarded, described and certified on a transport document, and otherwise in a condition for transport as required by these Regulations.

Particulars of consignment

546. The *consignor* shall include in the transport documents with each *consignment* the identification of the *consignor* and *consignee*, including their




FIG. 6. Placard. Except as permitted by para. 571, minimum dimensions shall be as shown; when different dimensions are used, the relative proportions must be maintained. The number "7" shall not be less than 25 mm high. The background colour of the upper half of the placard shall be yellow and of the lower half white, the colour of the trefoil and the printing shall be black. The use of the word "RADIOACTIVE" in the bottom half is optional, to allow the alternative use of this placard to display the appropriate UN number for the consignment.

names and addresses, and the following information, as applicable, in the order given:

- (a) The UN number assigned to the material as specified in accordance with the provisions of paras 401 and 530, preceded by the letters "UN".
- (b) The proper shipping name, as specified in accordance with the provisions of paras 401 and 530.

SECTION V




FIG. 7. Placard for separate display of UN number. The background colour of the placard shall be orange and the border and UN number shall be black. The symbol “****” denotes the space in which the appropriate UN number for radioactive material, as specified in Table 1, shall be displayed.

- (c) The UN dangerous goods class number “7”.
- (d) The subsidiary hazard class or division number(s) corresponding to the subsidiary hazard label(s) required to be applied, when assigned, shall be entered following the primary hazard class or division and shall be enclosed in parentheses.
- (e) The name or symbol of each radionuclide or, for mixtures of radionuclides, an appropriate general description or a list of the most restrictive nuclides.
- (f) A description of the physical and chemical form of the material, or a notation that the material is *special form radioactive material* or *low dispersible radioactive material*. A generic chemical description is acceptable for chemical form.
- (g) The maximum activity of the *radioactive contents* during transport expressed in units of becquerels (Bq) with the appropriate SI prefix symbol (see Annex II). For *fissile material*, the mass of *fissile material* (or mass of each *fissile nuclide* for mixtures, when appropriate) in units of grams (g), or appropriate multiples thereof, may be used in place of activity.
- (h) The category of the *package, overpack* or *freight container*, as assigned per para. 529, i.e. I-WHITE, II-YELLOW, III-YELLOW.
- (i) The *TI* as determined per paras 523, 524 and 524A (except for category I-WHITE).
- (j) For *fissile material*:
 - (i) Shipped under one exception of subparagraphs 417(a)–(f), reference to that paragraph;

- (ii) Shipped under para. 417(c)–(e), the total mass of *fissile nuclides*;
- (iii) Contained in a *package* for which one of para. 674(a)–(c) or 675 is applied, reference to that paragraph;
- (iv) The *CSI*, where applicable.
- (k) The identification mark for each *competent authority* certificate of *approval* (*special form radioactive material, low dispersible radioactive material, fissile material* excepted under para. 417(f), *special arrangement, package design* or *shipment*) applicable to the *consignment*.
- (l) For *consignments* of more than one *package*, the information contained in para. 546(a)–(k) shall be given for each *package*. For *packages* in an *overpack, freight container* or *conveyance*, a detailed statement of the contents of each *package* within the *overpack, freight container* or *conveyance* and, where appropriate, of each *overpack, freight container* or *conveyance* shall be included. If *packages* are to be removed from the *overpack, freight container* or *conveyance* at a point of intermediate unloading, appropriate transport documents shall be made available.
- (m) Where a *consignment* is required to be shipped under *exclusive use*, the statement “EXCLUSIVE USE SHIPMENT”.
- (n) For *LSA-II, LSA-III, SCO-I, SCO-II* and *SCO-III*, the total activity of the *consignment* as a multiple of A_2 . For *radioactive material* for which the A_2 value is unlimited, the multiple of A_2 shall be zero.

Consignor’s certification or declaration

547. The *consignor* shall include in the transport documents a certification or declaration in the following terms:

“I hereby declare that the contents of this consignment are fully and accurately described above by the proper shipping name and are classified, packaged, marked and labelled/placarded, and are in all respects in proper condition for transport according to applicable international and national governmental regulations.”

548. If the intent of the declaration is already a condition of transport within a particular international convention, the *consignor* need not provide a declaration for that part of the transport covered by the convention.

549. The declaration shall be signed and dated by the *consignor*. Facsimile signatures are acceptable where applicable laws and regulations recognize the legal validity of facsimile signatures.

SECTION V

550. If the dangerous goods documentation is presented to the *carrier* by means of electronic data processing or electronic data interchange transmission techniques, the signature(s) may be replaced by the name(s) (in capitals) of the person authorized to sign.

551. When *radioactive material*, other than when carried in *tanks*, is packed or loaded into any *freight container* or *vehicle* that will be transported by sea, those responsible for packing the container or *vehicle* shall provide a container/*vehicle* packing certificate specifying the container/*vehicle* identification number(s) and certifying that the operation has been carried out in accordance with the applicable conditions of the International Maritime Dangerous Goods (IMDG) Code [15].

552. The information required in the transport documents and the container/*vehicle* packing certificate may be incorporated into a single document, if not, the documents shall be attached. If the information is incorporated into a single document, the document shall include a signed declaration such as:

“It is declared that the packing of the goods into the container/*vehicle* has been carried out in accordance with the applicable provisions”.

This declaration shall be dated and the person signing it shall be identified on the document. Facsimile signatures are acceptable where applicable laws and regulations recognize the legal validity of facsimile signatures.

553. The declaration shall be made on the same transport document that contains the particulars of *consignment* listed in para. 546.

Information for carriers

554. The *consignor* shall provide in the transport documents a statement regarding actions, if any, that are required to be taken by the *carrier*. The statement shall be in the languages deemed necessary by the *carrier* or the authorities concerned and shall include at least the following points:

- (a) Supplementary requirements for loading, stowage, carriage, handling and unloading of the *package*, *overpack* or *freight container*, including any special stowage provisions for the safe dissipation of heat (see para. 565), or a statement that no such requirements are necessary;
- (b) Restrictions on the mode of transport or *conveyance* and any necessary routeing instructions;
- (c) Emergency arrangements appropriate to the *consignment*.

555. The *consignor* shall retain a copy of each of the transport documents containing the information specified in paras 546, 547, 551, 552 and 554, as applicable, for a minimum period of three months.

When the documents are kept electronically, the *consignor* shall be able to reproduce them in a printed form.

556. The applicable *competent authority* certificates need not necessarily accompany the *consignment*. The *consignor* shall make the applicable certificates available to the *carrier(s)* before loading and unloading.

Notification of competent authorities

557. Before the first *shipment* of any *package* requiring *competent authority approval*, the *consignor* shall ensure that copies of each applicable *competent authority* certificate applying to that *package design* have been submitted to the *competent authority* of the country of origin of the *shipment* and to the *competent authority* of each country *through or into* which the *consignment* is to be transported. The *consignor* is not required to await an acknowledgement from the *competent authority*, nor is the *competent authority* required to make such acknowledgement of receipt of the certificate.

558. For each *shipment* listed in (a), (b), (c) or (d) below, the *consignor* shall notify the *competent authority* of the country of origin of the *shipment* and the *competent authority* of each country *through or into* which the *consignment* is to be transported. This notification shall be in the possession of each *competent authority* prior to the commencement of the *shipment*, preferably at least 7 days in advance of the *shipment*. The *shipments* that require *consignor* notification include:

- (a) *Type C packages* containing *radioactive material* with an activity greater than $3000A_1$ or $3000A_2$, as appropriate, or 1000 TBq, whichever is the lower;
- (b) *Type B(U) packages* containing *radioactive material* with an activity greater than $3000A_1$ or $3000A_2$, as appropriate, or 1000 TBq, whichever is the lower;
- (c) *Type B(M) packages*;
- (d) *Shipments* under *special arrangement*.

SECTION V

559. The *consignment* notification shall include:

- (a) Sufficient information to enable the identification of the *package* or *packages*, including all applicable certificate numbers and identification marks.
- (b) Information on the date of *shipment*, the expected date of arrival and the proposed routing.
- (c) The name(s) of the *radioactive material(s)* or nuclide(s).
- (d) Descriptions of the physical and chemical forms of the *radioactive material*, or whether it is *special form radioactive material* or *low dispersible radioactive material*.
- (e) The maximum activity of the *radioactive contents* during transport expressed in units of becquerels (Bq) with the appropriate SI prefix symbol (see Annex II). For *fissile material*, the mass of *fissile material* (or the mass of each *fissile nuclide* for a mixture, when appropriate) in units of grams (g), or multiples thereof, may be used in place of activity.

560. The *consignor* is not required to send a separate notification if the required information has been included in the application for *approval* of *shipment* (see para. 827).

Possession of certificates and instructions

561. The *consignor* shall have in his/her possession a copy of each certificate required under Section VIII of these Regulations and a copy of the instructions with regard to the proper closing of the *package* and other preparations for *shipment* before making any *shipment* under the terms of the certificates.

TRANSPORT AND STORAGE IN TRANSIT

Segregation during transport and storage in transit

562. *Packages, overpacks and freight containers* containing *radioactive material* and unpackaged *radioactive material* shall be segregated during transport and during storage in transit:

- (a) From workers in regularly occupied working areas by distances calculated using a dose criterion of 5 mSv in a year and conservative model parameters;

REQUIREMENTS AND CONTROLS FOR TRANSPORT

- (b) From members of the public in areas where the public has regular access by distances calculated using a dose criterion of 1 mSv in a year and conservative model parameters;
- (c) From undeveloped photographic film by distances calculated using a radiation exposure criterion for undeveloped photographic film due to the transport of *radioactive material* of 0.1 mSv per *consignment* of such film;
- (d) From other dangerous goods in accordance with para. 506.

563. Category II-YELLOW or III-YELLOW *packages* or *overpacks* shall not be carried in compartments occupied by passengers, except those exclusively reserved for couriers specially authorized to accompany such *packages* or *overpacks*.

Stowage during transport and storage in transit

564. *Consignments* shall be securely stowed.

565. Provided that its average surface heat flux does not exceed 15 W/m² and that the immediate surrounding cargo is not in sacks or bags, a *package* or *overpack* may be carried or stored among packaged general cargo without any special stowage provisions except as may be specifically required by the *competent authority* in an applicable certificate of *approval*.

566. Loading of *freight containers* and accumulation of *packages*, *overpacks* and *freight containers* shall be controlled as follows:

- (a) Except under the condition of *exclusive use*, and for *consignments* of *LSA-I material*, the total number of *packages*, *overpacks* and *freight containers* aboard a single *conveyance* shall be limited so that the sum of the *TIs* aboard the *conveyance* does not exceed the values shown in Table 10.
- (b) The *dose rate* under routine conditions of transport shall not exceed 2 mSv/h at any point on the external surface of the *vehicle* or *freight container*, and 0.1 mSv/h at 2 m from the external surface of the *vehicle* or *freight container*, except for *consignments* transported under *exclusive use* by road or rail for which the radiation limits around the *vehicle* are set forth in para. 573(b) and 573(c).
- (c) The sum of the *CSIs* in a *freight container* and aboard a *conveyance* shall not exceed the values shown in Table 11.

567. Any *package* or *overpack* having a *TI* greater than 10, or any *consignment* having a *CSI* greater than 50, shall be transported only under *exclusive use*.

SECTION V

TABLE 10. TRANSPORT INDEX LIMITS FOR FREIGHT CONTAINERS AND CONVEYANCES NOT UNDER EXCLUSIVE USE

Type of <i>freight container</i> or <i>conveyance</i>	Limit on sum of <i>TIs</i> in a <i>freight container</i> or aboard a <i>conveyance</i>
<i>Freight container:</i>	
<i>Small freight container</i>	50
<i>Large freight container</i>	50
<i>Vehicle</i>	50
<i>Aircraft:</i>	
Passenger	50
Cargo	200
Inland waterway craft	50
<i>Sea-going vessel^a:</i>	
(i) Hold, compartment or <i>defined deck area</i> :	
<i>Packages, overpacks, small freight containers</i>	50
<i>Large freight containers</i>	200
(ii) Total vessel:	
<i>Packages, overpacks, small freight containers</i>	200
<i>Large freight containers</i>	No limit

^a *Packages* or *overpacks* carried in or on a *vehicle* that are in accordance with the provisions of para. 573 may be transported by *vessels* provided that they are not removed from the *vehicle* at any time while on board the *vessel*.

Additional requirements relating to transport and storage in transit of fissile material

568. Any group of *packages, overpacks* and *freight containers* containing *fissile material* stored in transit in any one storage area shall be so limited that the sum of the *CSIs* in the group does not exceed 50. Each group shall be stored so as to maintain a spacing of at least 6 m from other such groups.

569. Where the sum of the *CSIs* on board a *conveyance* or in a *freight container* exceeds 50, as permitted in Table 11, storage shall be such as to maintain a spacing of at least 6 m from other groups of *packages, overpacks* or *freight containers* containing *fissile material* or other *conveyances* carrying *radioactive material*.

REQUIREMENTS AND CONTROLS FOR TRANSPORT

TABLE 11. CSI LIMITS FOR FREIGHT CONTAINERS AND CONVEYANCES CONTAINING FISSILE MATERIAL

Type of <i>freight container</i> or <i>conveyance</i>	Limit on sum of <i>CSIs</i> in a <i>freight container</i> or aboard a <i>conveyance</i>	
	Not under <i>exclusive use</i>	Under <i>exclusive use</i>
<i>Freight container:</i>		
<i>Small freight container</i>	50	Not applicable
<i>Large freight container</i>	50	100
<i>Vehicle</i>	50	100
<i>Aircraft:</i>		
Passenger	50	Not applicable
Cargo	50	100
Inland waterway craft	50	100
<i>Sea-going vessel ^a:</i>		
(i) Hold, compartment or <i>defined deck area</i> :		
<i>Packages, overpacks, small freight containers</i>	50	100
<i>Large freight containers</i>	50	100
(ii) Total vessel:		
<i>Packages, overpacks, small freight containers</i>	200 ^b	200 ^c
<i>Large freight containers</i>	No limit ^b	No limit ^c

^a *Packages* or *overpacks* carried in or on a *vehicle* that are in accordance with the provisions of para. 573 may be transported by *vessels* provided that they are not removed from the *vehicle* at any time while on board the *vessel*. In this case, the entries under the heading “under *exclusive use*” apply.

^b The *consignment* shall be so handled and stowed that the sum of *CSIs* in any group does not exceed 50 and that each group is handled and stowed so as to maintain a spacing of at least 6 m from other groups.

^c The *consignment* shall be so handled and stowed that the sum of *CSIs* in any group does not exceed 100 and that each group is handled and stowed so as to maintain a spacing of at least 6 m from other groups. The intervening space between groups may be occupied by other cargo in accordance with para. 506.

SECTION V

570. *Fissile material* meeting one of the provisions (a)–(f) of para. 417 shall meet the following requirements:

- (a) Only one of the provisions (a)–(f) of para. 417 is allowed per *consignment*.
- (b) Only one approved *fissile material* in *packages* classified in accordance with para. 417(f) is allowed per *consignment* unless multiple materials are authorized in the certificate of *approval*.
- (c) *Fissile material* in *packages* classified in accordance with para. 417(c) shall be transported in a *consignment* with no more than 45 g of *fissile nuclides*.
- (d) *Fissile material* in *packages* classified in accordance with para. 417(d) shall be transported in a *consignment* with no more than 15 g of *fissile nuclides*.
- (e) Unpackaged or packaged *fissile material* classified in accordance with para. 417(e) shall be transported under *exclusive use* on a *conveyance* with no more than 45 g of *fissile nuclides*.

Additional requirements relating to transport by rail and by road

571. *Vehicles* carrying *packages*, *overpacks* or *freight containers* labelled with any of the labels shown in Figs 2–5, or carrying unpackaged *LSA-I material*, *SCO-I* or *SCO-III*, shall display the placard shown in Fig. 6 on each of:

- (a) The two external lateral walls in the case of a rail *vehicle*;
- (b) The two external lateral walls and the external rear wall in the case of a road *vehicle*.

In the case of a *vehicle* without sides, the placards may be affixed directly on the cargo carrying unit provided that they are readily visible. In the case of large *tanks* or *freight containers*, the placards on the *tanks* or *freight containers* shall suffice. In the case of *vehicles* that have insufficient area to allow the fixing of larger placards, the dimensions of the placard described in Fig. 6 may be reduced to 100 mm. Any placards that do not relate to the contents shall be removed.

572. Where the *consignment* in or on the *vehicle* is unpackaged *LSA-I material*, *SCO-I* or *SCO-III*, or where a *consignment* is required to be shipped under *exclusive use* and is packaged *radioactive material* with a single UN number, the appropriate UN number (see Table 1) shall also be displayed, in black digits not less than 65 mm high, either:

- (a) In the lower half of the placard shown in Fig. 6, against the white background; or
- (b) On the placard shown in Fig. 7.

REQUIREMENTS AND CONTROLS FOR TRANSPORT

When the alternative given in (b) is used, the subsidiary placard shall be affixed immediately adjacent to the main placard, either on the two external lateral walls in the case of a rail *vehicle* or on the two external lateral walls and the external rear wall in the case of a road *vehicle*.

573. For *consignments* under *exclusive use*, the *dose rate* shall not exceed:

- (a) 10 mSv/h at any point on the external surface of any *package* or *overpack*, and may only exceed 2 mSv/h provided that:
 - (i) The *vehicle* is equipped with an enclosure that, during routine conditions of transport, prevents the access of unauthorized persons to the interior of the enclosure.
 - (ii) Provisions are made to secure the *package* or *overpack* so that its position within the *vehicle* enclosure remains fixed during routine conditions of transport.
 - (iii) There is no loading or unloading during the *shipment*.
- (b) 2 mSv/h at any point on the outer surfaces of the *vehicle*, including the upper and lower surfaces, or, in the case of an open *vehicle*, at any point on the vertical planes projected from the outer edges of the *vehicle*, on the upper surface of the load, and on the lower external surface of the *vehicle*.
- (c) 0.1 mSv/h at any point 2 m from the vertical planes represented by the outer lateral surfaces of the *vehicle*, or, if the load is transported in an open *vehicle*, at any point 2 m from the vertical planes projected from the outer edges of the *vehicle*.

574. In the case of road *vehicles*, no persons other than the driver and assistants shall be permitted in *vehicles* carrying *packages*, *overpacks* or *freight containers* bearing category II-YELLOW or III-YELLOW labels.

Additional requirements relating to transport by vessels

575. *Packages* or *overpacks* having a surface *dose rate* greater than 2 mSv/h, unless being carried in or on a *vehicle* under *exclusive use* in accordance with Table 10, footnote (a), shall not be transported by *vessel* except under *special arrangement*.

576. The transport of *consignments* by means of a special use *vessel* that, by virtue of its *design*, or by reason of its being chartered, is dedicated to the purpose

SECTION V

of carrying *radioactive material*, shall be excepted from the requirements specified in para. 566 provided that the following conditions are met:

- (a) A *radiation protection programme* for the *shipment* shall be approved by the *competent authority* of the flag state of the vessel and, when requested, by the *competent authority* at each port of call.
- (b) Stowage arrangements shall be predetermined for the whole voyage, including any *consignments* to be loaded at ports of call en route.
- (c) The loading, carriage and unloading of the *consignments* shall be supervised by persons qualified in the transport of *radioactive material*.

Additional requirements relating to transport by air

577. *Type B(M) packages* and *consignments* under *exclusive use* shall not be transported on passenger aircraft.

578. Vented *Type B(M) packages*, *packages* that require external cooling by an ancillary cooling system, *packages* subject to operational controls during transport and *packages* containing liquid pyrophoric materials shall not be transported by air.

579. *Packages* or *overpacks* having a surface *dose rate* greater than 2 mSv/h shall not be transported by air except by *special arrangement*.

Additional requirements relating to transport by post

580. A *consignment* that conforms to the requirements of para. 515, in which the activity of the *radioactive contents* does not exceed one tenth of the limits prescribed in Table 4, and that does not contain uranium hexafluoride, may be accepted for domestic movement by national postal authorities, subject to such additional requirements as those authorities may prescribe.

581. A *consignment* that conforms to the requirements of para. 515, in which the activity of the *radioactive contents* does not exceed one tenth of the limits prescribed in Table 4, and that does not contain uranium hexafluoride, may be accepted for international movement by post, subject in particular to the following additional requirements as prescribed by the Acts of the Universal Postal Union:

- (a) The *consignment* shall be deposited with the postal service only by *consignors* authorized by the national authority.
- (b) The *consignment* shall be dispatched by the quickest route, normally by air.

REQUIREMENTS AND CONTROLS FOR TRANSPORT

- (c) The *consignment* shall be plainly and durably marked on the outside with the words “RADIOACTIVE MATERIAL — QUANTITIES PERMITTED FOR MOVEMENT BY POST”. These words shall be crossed out if the *packaging* is returned empty.
- (d) The *consignment* shall carry on the outside the name and address of the *consignor* with the request that the *consignment* be returned in the case of non-delivery.
- (e) The name and address of the *consignor* and the contents of the *consignment* shall be indicated on the internal *packaging*.

CUSTOMS OPERATIONS

582. Customs operations involving the inspection of the *radioactive contents* of a *package* shall be carried out only in a place where adequate means of controlling radiation exposure are provided and in the presence of qualified persons. Any *package* opened on customs instructions shall, before being forwarded to the *consignee*, be restored to its original condition.

UNDELIVERABLE CONSIGNMENTS

583. Where a *consignment* is undeliverable, it shall be placed in a safe location and the appropriate *competent authority* shall be informed as soon as possible and a request made for instructions on further action.

RETENTION AND AVAILABILITY OF TRANSPORT DOCUMENTS BY CARRIERS

584. A *carrier* shall not accept a *consignment* for transport unless:

- (a) A copy of the transport document and other documents or information as required by these Regulations are provided; or
- (b) The information applicable to the *consignment* is provided in electronic form.

585. The information applicable to the *consignment* shall accompany the *consignment* to its final destination. This information may be on the transport document or may be on another document. This information shall be given to the *consignee* when the *consignment* is delivered.

SECTION V

586. When the information applicable to the *consignment* is given to the *carrier* in electronic form, the information shall be available to the *carrier* at all times during transport to the *consignment's* final destination. The information shall be able to be produced without delay in a printed form.

587. The *carrier* shall retain a copy of the transport document and additional information and documentation, as specified in these Regulations, for a minimum period of three months.

588. When the documents are kept electronically or in a computer system, the *carrier* shall be capable of reproducing them in a printed form.

Section VI

REQUIREMENTS FOR RADIOACTIVE MATERIAL AND FOR PACKAGINGS AND PACKAGES

REQUIREMENTS FOR RADIOACTIVE MATERIAL

Requirements for LSA-III material

601. This paragraph was deleted.

Requirements for special form radioactive material

602. *Special form radioactive material* shall have at least one dimension of not less than 5 mm.

603. *Special form radioactive material* shall be of such a nature or shall be so designed that if it is subjected to the tests specified in paras 704–711, it shall meet the following requirements:

- (a) It would not break or shatter under the impact, percussion and bending tests in paras 705–707 and 709(a), as applicable.
- (b) It would not melt or disperse in the heat test in para. 708 or para. 709(b), as applicable.
- (c) The activity in the water from the leaching tests specified in paras 710 and 711 would not exceed 2 kBq; or alternatively, for sealed sources, the leakage rate for the volumetric leakage assessment test specified in the International Organization for Standardization document: Radiation Protection — Sealed Radioactive Sources — Leakage Test Methods (ISO 9978) [16], would not exceed the applicable acceptance threshold acceptable to the *competent authority*.

604. When a sealed capsule constitutes part of the *special form radioactive material*, the capsule shall be so manufactured that it can be opened only by destroying it.

Requirements for low dispersible radioactive material

605. *Low dispersible radioactive material* shall be such that the total amount of this *radioactive material* in a *package* shall meet the following requirements:

- (a) The *dose rate* at 3 m from the unshielded *radioactive material* does not exceed 10 mSv/h.
- (b) If subjected to the tests specified in paras 736 and 737, the airborne release in gaseous and particulate forms of up to 100 μm aerodynamic equivalent diameter would not exceed $100A_2$. A separate specimen may be used for each test.
- (c) If subjected to the test specified in para. 703, the activity in the water would not exceed $100A_2$. In the application of this test, the damaging effects of the tests specified in (b) shall be taken into account.

REQUIREMENTS FOR MATERIAL EXCEPTED FROM FISSILE CLASSIFICATION

606. *Fissile material* excepted from classification as “FISSILE” under para. 417(f) shall be subcritical without the need for accumulation control under the following conditions:

- (a) The conditions of para. 673(a);
- (b) The conditions consistent with the assessment provisions stated in paras 684(b) and 685(b) for *packages*;
- (c) The conditions specified in para. 683(a), if transported by air.

GENERAL REQUIREMENTS FOR ALL PACKAGINGS AND PACKAGES

607. The *package* shall be so designed in relation to its mass, volume and shape that it can be easily and safely transported. In addition, the *package* shall be so designed that it can be properly secured in or on the *conveyance* during transport.

608. The *design* shall be such that any lifting attachments on the *package* will not fail when used in the intended manner and that if failure of the attachments should occur, the ability of the *package* to meet other requirements of these Regulations would not be impaired. The *design* shall take account of appropriate safety factors to cover snatch lifting.

REQUIREMENTS FOR PACKAGES

609. Attachments and any other features on the outer surface of the *package* that could be used to lift it shall be designed either to support its mass in accordance with the requirements of para. 608 or shall be removable or otherwise rendered incapable of being used during transport.

610. As far as practicable, the *packaging* shall be so designed that the external surfaces are free from protruding features and can be easily decontaminated.

611. As far as practicable, the outer layer of the *package* shall be so designed as to prevent the collection and the retention of water.

612. Any features added to the *package* at the time of transport that are not part of the *package* shall not reduce its safety.

613. The *package* shall be capable of withstanding the effects of any acceleration, vibration or vibration resonance that may arise under routine conditions of transport without any deterioration in the effectiveness of the closing devices on the various receptacles or in the integrity of the *package* as a whole. In particular, nuts, bolts and other securing devices shall be so designed as to prevent them from becoming loose or being released unintentionally, even after repeated use.

613A. The *design* of the *package* shall take into account ageing mechanisms.

614. The materials of the *packaging* and any components or structures shall be physically and chemically compatible with each other and with the *radioactive contents*. Account shall be taken of their behaviour under irradiation.

615. All valves through which the *radioactive contents* could escape shall be protected against unauthorized operation.

616. The *design* of the *package* shall take into account ambient temperatures and pressures that are likely to be encountered in routine conditions of transport.

617. A *package* shall be so designed that it provides sufficient shielding to ensure that, under routine conditions of transport and with the maximum *radioactive contents* that the *package* is designed to contain, the *dose rate* at any point on the external surface of the *package* would not exceed the values specified in paras 516, 527 and 528, as applicable, with account taken of paras 566(b) and 573.

618. For *radioactive material* having other dangerous properties, the *package design* shall take into account those properties (see paras 110 and 507).

SECTION VI

ADDITIONAL REQUIREMENTS FOR PACKAGES TRANSPORTED BY AIR

619. For *packages* to be transported by air, the temperature of the accessible surfaces shall not exceed 50°C at an ambient temperature of 38°C with no account taken for insolation.

620. *Packages* to be transported by air shall be so designed that if they were exposed to ambient temperatures ranging from -40°C to +55°C, the integrity of containment would not be impaired.

621. *Packages* containing *radioactive material* to be transported by air shall be capable of withstanding, without loss or dispersal of *radioactive contents* from the *containment system*, an internal pressure that produces a pressure differential of not less than *maximum normal operating pressure* plus 95 kPa.

REQUIREMENTS FOR EXCEPTED PACKAGES

622. An *excepted package* shall be designed to meet the requirements specified in paras 607–618 and, in addition, the requirements of para. 636 if it contains *fissile material* allowed by one of the provisions of subparagraphs (a)–(f) of para. 417, and the requirements of paras 619–621 if carried by air.

REQUIREMENTS FOR INDUSTRIAL PACKAGES

Requirements for Type IP-1

623. A *Type IP-1 package* shall be designed to meet the requirements specified in paras 607–618 and 636 and, in addition, the requirements of paras 619–621 if carried by air.

Requirements for Type IP-2

624. A *package* to be qualified as *Type IP-2* shall be designed to meet the requirements for *Type IP-1* as specified in para. 623 and, in addition, if it were subjected to the tests specified in paras 722 and 723, it would prevent:

- (a) Loss or dispersal of the *radioactive contents*;

REQUIREMENTS FOR PACKAGES

- (b) More than a 20% increase in the maximum *dose rate* at any external surface of the *package*.

Requirements for Type IP-3

625. A *package* to be qualified as *Type IP-3* shall be designed to meet the requirements for *Type IP-1* as specified in para. 623 and, in addition, the requirements specified in paras 636–649.

Alternative requirements for Type IP-2 and Type IP-3

626. *Packages* may be used as *Type IP-2*, provided that:

- (a) They satisfy the requirements for *Type IP-1* specified in para. 623.
- (b) They are designed to satisfy the requirements prescribed for UN Packing Group I or II in Chapter 6.1 of the United Nations Recommendations on the Transport of Dangerous Goods, Model Regulations [17].
- (c) When subjected to the tests required for UN Packing Group I or II, they would prevent:
 - (i) Loss or dispersal of the *radioactive contents*;
 - (ii) More than a 20% increase in the maximum *dose rate* at any external surface of the *package*.

627. Portable *tanks* may also be used as *Type IP-2* or *Type IP-3*, provided that:

- (a) They satisfy the requirements for *Type IP-1* specified in para. 623.
- (b) They are designed to satisfy the requirements prescribed in Chapter 6.7 of the United Nations Recommendations on the Transport of Dangerous Goods, Model Regulations [17], or other requirements, at least equivalent, and are capable of withstanding a test pressure of 265 kPa.
- (c) They are designed so that any additional shielding that is provided shall be capable of withstanding the static and dynamic stresses resulting from handling and routine conditions of transport and of preventing more than a 20% increase in the maximum *dose rate* at any external surface of the portable *tanks*.

628. *Tanks*, other than portable *tanks*, may also be used as *Type IP-2* or *Type IP-3* for transporting *LSA-I* and *LSA-II* as prescribed in Table 5, provided that:

- (a) They satisfy the requirements for *Type IP-1* specified in para. 623.

SECTION VI

- (b) They are designed to satisfy the requirements prescribed in regional or national regulations for the transport of dangerous goods and are capable of withstanding a test pressure of 265 kPa.
- (c) They are designed so that any additional shielding that is provided shall be capable of withstanding the static and dynamic stresses resulting from handling and routine conditions of transport and of preventing more than a 20% increase in the maximum *dose rate* at any external surface of the *tanks*.

629. *Freight containers* with the characteristics of a permanent enclosure may also be used as *Type IP-2* or *Type IP-3*, provided that:

- (a) The *radioactive contents* are restricted to solid materials.
- (b) They satisfy the requirements for *Type IP-1* specified in para. 623.
- (c) They are designed to conform to the International Organization for Standardization document: Series 1 Freight containers — Specifications and Testing — Part 1: General Cargo Containers for General Purposes (ISO 1496-1) [18] excluding dimensions and ratings. They shall be so designed that if subjected to the tests prescribed in that document, and to the accelerations occurring during routine conditions of transport, they would prevent:
 - (i) Loss or dispersal of the *radioactive contents*;
 - (ii) More than a 20% increase in the maximum *dose rate* at any external surface of the *freight containers*.

630. Metal *IBCs* may also be used as *Type IP-2* or *Type IP-3*, provided that:

- (a) They satisfy the requirements for *Type IP-1* specified in para. 623.
- (b) They are designed to satisfy the requirements prescribed for UN Packing Group I or II in Chapter 6.5 of the United Nations Recommendations on the Transport of Dangerous Goods, Model Regulations [17], and if they were subjected to the tests prescribed in that document, but with the drop test conducted in the most damaging orientation, they would prevent:
 - (i) Loss or dispersal of the *radioactive contents*;
 - (ii) More than a 20% increase in the maximum *dose rate* at any external surface of the *IBC*.

REQUIREMENTS FOR PACKAGES

REQUIREMENTS FOR PACKAGES CONTAINING URANIUM HEXAFLUORIDE

631. *Packages* designed to contain uranium hexafluoride shall meet the requirements that pertain to the radioactive and fissile properties of the material prescribed elsewhere in these Regulations. Except as allowed in para. 634, uranium hexafluoride in quantities of 0.1 kg or more shall also be packaged and transported in accordance with the provisions of the International Organization for Standardization document: Nuclear Energy — Packaging of Uranium Hexafluoride (UF₆) for Transport (ISO 7195) [19], and the requirements of paras 632 and 633.

632. Each *package* designed to contain 0.1 kg or more of uranium hexafluoride shall be so designed that the *package* will meet the following requirements:

- (a) Withstand, without leakage and without unacceptable stress, as specified in ISO 7195 [19], the structural test as specified in para. 718, except as allowed in para. 634;
- (b) Withstand, without loss or dispersal of the uranium hexafluoride, the free drop test specified in para. 722;
- (c) Withstand, without rupture of the *containment system*, the thermal test specified in para. 728, except as allowed in para. 634.

633. *Packages* designed to contain 0.1 kg or more of uranium hexafluoride shall not be provided with pressure relief devices.

634. Subject to *multilateral approval*, *packages* designed to contain 0.1 kg or more of uranium hexafluoride may be transported if the *packages* are designed:

- (a) To international or national standards other than ISO 7195 [19], provided an equivalent level of safety is maintained; and/or
- (b) To withstand, without leakage and without unacceptable stress, a test pressure of less than 2.76 MPa as specified in para. 718; and/or
- (c) To contain 9000 kg or more of uranium hexafluoride and the *packages* do not meet the requirement of para. 632(c).

In all other respects, the requirements specified in paras 631–633 shall be satisfied.

SECTION VI

REQUIREMENTS FOR TYPE A PACKAGES

635. *Type A packages* shall be designed to meet the requirements specified in paras 607–618 and, in addition, the requirements of paras 619–621 if carried by air, and of paras 636–651.

636. The smallest overall external dimension of the *package* shall not be less than 10 cm.

637. The outside of the *package* shall incorporate a feature such as a seal that is not readily breakable and which, while intact, will be evidence that the *package* has not been opened.

638. Any tie-down attachments on the *package* shall be so designed that, under normal and accident conditions of transport, the forces in those attachments shall not impair the ability of the *package* to meet the requirements of these Regulations.

639. The *design* of the *package* shall take into account temperatures ranging from -40°C to $+70^{\circ}\text{C}$ for the components of the *packaging*. Attention shall be given to freezing temperatures for liquids and to the potential degradation of *packaging* materials within the given temperature range.

640. The *design* and manufacturing techniques shall be in accordance with national or international standards, or other requirements, acceptable to the *competent authority*.

641. The *design* shall include a *containment system* securely closed by a positive fastening device that cannot be opened unintentionally or by a pressure that may arise within the *package*.

642. *Special form radioactive material* may be considered as a component of the *containment system*.

643. If the *containment system* forms a separate unit of the *package*, the *containment system* shall be capable of being securely closed by a positive fastening device that is independent of any other part of the *packaging*.

644. The *design* of any component of the *containment system* shall take into account, where applicable, the radiolytic decomposition of liquids and

REQUIREMENTS FOR PACKAGES

other vulnerable materials and the generation of gas by chemical reaction and radiolysis.

645. The *containment system* shall retain its *radioactive contents* under a reduction of ambient pressure to 60 kPa.

646. All valves, other than pressure relief valves, shall be provided with an enclosure to retain any leakage from the valve.

647. A radiation shield that encloses a component of the *package* specified as a part of the *containment system* shall be so designed as to prevent the unintentional release of that component from the shield. Where the radiation shield and such component within it form a separate unit, the radiation shield shall be capable of being securely closed by a positive fastening device that is independent of any other *packaging* structure.

648. A *package* shall be so designed that if it were subjected to the tests specified in paras 719–724, it would prevent:

- (a) Loss or dispersal of the *radioactive contents*;
- (b) More than a 20% increase in the maximum *dose rate* at any external surface of the *package*.

649. The *design* of a *package* intended for liquid *radioactive material* shall make provision for ullage to accommodate variations in the temperature of the contents, dynamic effects and filling dynamics.

650. A *Type A package* designed to contain liquid *radioactive material* shall, in addition:

- (a) Be adequate to meet the conditions specified in para. 648(a) if the *package* is subjected to the tests specified in para. 725; and
- (b) Either:
 - (i) Be provided with sufficient absorbent material to absorb twice the volume of the liquid contents. Such absorbent material must be suitably positioned so as to contact the liquid in the event of leakage; or
 - (ii) Be provided with a *containment system* composed of primary inner and secondary outer containment components designed to enclose the liquid contents completely and to ensure their retention within the secondary outer containment components, even if the primary inner components leak.

SECTION VI

651. A *Type A package* designed for gases shall prevent loss or dispersal of the *radioactive contents* if the *package* were subjected to the tests specified in para. 725, except for a *Type A package* designed for tritium gas or for noble gases.

REQUIREMENTS FOR TYPE B(U) PACKAGES

652. *Type B(U) packages* shall be designed to meet the requirements specified in paras 607–618, the requirements specified in paras 619–621 if carried by air, and in paras 636–649, except as specified in para. 648(a), and, in addition, the requirements specified in paras 653–666.

653. A *package* shall be so designed that, under the ambient conditions specified in paras 656 and 657, heat generated within the *package* by the *radioactive contents* shall not, under normal conditions of transport, as demonstrated by the tests in paras 719–724, adversely affect the *package* in such a way that it would fail to meet the applicable requirements for containment and shielding if left unattended for a period of one week. Particular attention shall be paid to the effects of heat that may cause one or more of the following:

- (a) Alteration of the arrangement, the geometrical form or the physical state of the *radioactive contents* or, if the *radioactive material* is enclosed in a can or receptacle (for example, clad fuel elements), cause the can, receptacle or *radioactive material* to deform or melt;
- (b) Lessening of the efficiency of the *packaging* through differential thermal expansion, or cracking or melting of the radiation shielding material;
- (c) Acceleration of corrosion when combined with moisture.

654. A *package* shall be so designed that, under the ambient condition specified in para. 656 and in the absence of insolation, the temperature of the accessible surfaces of a *package* shall not exceed 50°C, unless the *package* is transported under *exclusive use*.

655. Except as required in para. 619 for a *package* transported by air, the maximum temperature of any surface readily accessible during transport of a *package* under *exclusive use* shall not exceed 85°C in the absence of insolation under the ambient condition specified in para. 656. Account may be taken of barriers or screens intended to give protection to persons without the need for the barriers or screens being subject to any test.

656. The ambient temperature shall be assumed to be 38°C.

REQUIREMENTS FOR PACKAGES

657. The solar insolation conditions shall be assumed to be as specified in Table 12.

658. A *package* that includes thermal protection for the purpose of satisfying the requirements of the thermal test specified in para. 728 shall be so designed that such protection will remain effective if the *package* is subjected to the tests specified in paras 719–724 and 727(a) and 727(b) or 727(b) and 727(c), as appropriate. Any such protection on the exterior of the *package* shall not be rendered ineffective by ripping, cutting, skidding, abrading or rough handling.

659. A *package* shall be so designed that if it were subjected to:

- (a) The tests specified in paras 719–724, it would restrict the loss of *radioactive contents* to not more than $10^{-6}A_2$ per hour.
- (b) The tests specified in paras 726, 727(b), 728 and 729 and either the test in:
 - Para. 727(c), when the *package* has a mass not greater than 500 kg, an overall density not greater than 1000 kg/m^3 based on the external dimensions, and *radioactive contents* greater than $1000A_2$ not as *special form radioactive material*; or
 - Para. 727(a), for all other *packages*.
 - (i) It would retain sufficient shielding to ensure that the *dose rate* 1 m from the surface of the *package* would not exceed 10 mSv/h with the maximum *radioactive contents* that the *package* is designed to contain.

TABLE 12. INSOLATION DATA

Case	Form and location of surface	Insolation for 12 h per day (W/m^2)
1	Flat surfaces transported horizontally — downward facing	0
2	Flat surfaces transported horizontally — upward facing	800
3	Surfaces transported vertically	200 ^a
4	Other downward facing (not horizontal) surfaces	200 ^a
5	All other surfaces	400 ^a

^a Alternatively, a sine function may be used, with an absorption coefficient adopted and the effects of possible reflection from neighbouring objects neglected.

SECTION VI

- (ii) It would restrict the accumulated loss of *radioactive contents* in a period of one week to not more than $10A_2$ for krypton-85 and not more than A_2 for all other radionuclides.

Where mixtures of different radionuclides are present, the provisions of paras 405–407 shall apply, except that for krypton-85 an effective $A_2(i)$ value equal to $10A_2$ may be used. For case (a), the assessment shall take into account the external *non-fixed contamination* limits of para. 508.

660. A *package* for *radioactive contents* with activity greater than 10^5A_2 shall be so designed that if it were subjected to the enhanced water immersion test specified in para. 730, there would be no rupture of the *containment system*.

661. Compliance with the permitted activity release limits shall depend neither upon filters nor upon a mechanical cooling system.

662. A *package* shall not include a pressure relief system from the *containment system* that would allow the release of *radioactive material* to the environment under the conditions of the tests specified in paras 719–724 and 726–729.

663. A *package* shall be so designed that if it were at the *maximum normal operating pressure* and it were subjected to the tests specified in paras 719–724 and 726–729, the levels of strains in the *containment system* would not attain values that would adversely affect the *package* in such a way that it would fail to meet the applicable requirements.

664. A *package* shall not have a *maximum normal operating pressure* in excess of a gauge pressure of 700 kPa.

665. A *package* containing *low dispersible radioactive material* shall be so designed that any features added to the *low dispersible radioactive material* that are not part of it, or any internal components of the *packaging*, shall not adversely affect the performance of the *low dispersible radioactive material*.

666. A *package* shall be designed for an ambient temperature range of -40°C to $+38^{\circ}\text{C}$.

REQUIREMENTS FOR PACKAGES

REQUIREMENTS FOR TYPE B(M) PACKAGES

667. *Type B(M) packages* shall meet the requirements for *Type B(U) packages* specified in para. 652, except that for *packages* to be transported solely within a specified country or solely between specified countries, conditions other than those given in paras 639, 655–657 and 660–666 may be assumed with the *approval* of the *competent authorities* of these countries. The requirements for *Type B(U) packages* specified in paras 655 and 660–666 shall be met as far as practicable.

668. Intermittent venting of *Type B(M) packages* may be permitted during transport, provided that the operational controls for venting are acceptable to the relevant *competent authorities*.

REQUIREMENTS FOR TYPE C PACKAGES

669. *Type C packages* shall be designed to meet the requirements specified in paras 607–621 and 636–649, except as specified in para. 648(a), and the requirements specified in paras 653–657, 661–666 and 670–672.

670. A *package* shall be capable of meeting the assessment criteria prescribed for tests in paras 659(b) and 663 after burial in an environment defined by a thermal conductivity of 0.33 W/(m·K) and a temperature of 38°C in the steady state. Initial conditions for the assessment shall assume that any thermal insulation of the *package* remains intact, the *package* is at the *maximum normal operating pressure* and the ambient temperature is 38°C.

671. A *package* shall be so designed that if it were at the *maximum normal operating pressure* and subjected to:

- (a) The tests specified in paras 719–724, it would restrict the loss of *radioactive contents* to not more than $10^{-6}A_2$ per hour.
- (b) The test sequences in para. 734:
 - (i) It would retain sufficient shielding to ensure that the *dose rate* 1 m from the surface of the *package* would not exceed 10 mSv/h with the maximum *radioactive contents* that the *package* is designed to contain.
 - (ii) It would restrict the accumulated loss of *radioactive contents* in a period of one week to not more than $10A_2$ for krypton-85 and not more than A_2 for all other radionuclides.

SECTION VI

Where mixtures of different radionuclides are present, the provisions of paras 405–407 shall apply, except that for krypton-85 an effective $A_2(i)$ value equal to $10A_2$ may be used. For case (a), the assessment shall take into account the external *contamination* limits of para. 508.

672. A *package* shall be so designed that there will be no rupture of the *containment system* following performance of the enhanced water immersion test specified in para. 730.

REQUIREMENTS FOR PACKAGES CONTAINING FISSILE MATERIAL

673. *Fissile material* shall be transported so as to:

- (a) Maintain subcriticality during routine, normal and accident conditions of transport; in particular, the following contingencies shall be considered:
 - (i) Leakage of water into or out of *packages*;
 - (ii) Loss of efficiency of built-in neutron absorbers or moderators;
 - (iii) Rearrangement of the contents either within the *package* or as a result of loss from the *package*;
 - (iv) Reduction of spaces within or between *packages*;
 - (v) *Packages* becoming immersed in water or buried in snow;
 - (vi) Temperature changes.
- (b) Meet the requirements:
 - (i) Of para. 636 except for unpackaged material when specifically allowed by para. 417(e);
 - (ii) Prescribed elsewhere in these Regulations that pertain to the radioactive properties of the material;
 - (iii) Of para. 637 unless the material is excepted by para. 417;
 - (iv) Of paras 676–686, unless the material is excepted by para. 417, 674 or 675.

674. *Packages* containing *fissile material* that meets the requirements of para. 674(d) and one of the provisions of para. 674(a)–(c) are excepted from the requirements of paras 676–686.

- (a) *Packages* containing *fissile material* in any form provided that:
 - (i) The smallest external dimension of the *package* is not less than 10 cm.

REQUIREMENTS FOR PACKAGES

- (ii) The *CSI* of the *package* is calculated using the following formula:

$$CSI = 50 \times 5 \times \{[\text{mass of uranium-235 in } package \text{ (g)}]/Z + [\text{mass of other fissile nuclides}^1 \text{ in } package \text{ (g)}]/280\}$$
 where the values of *Z* are taken from Table 13.
- (iii) The *CSI* of any *package* does not exceed 10.
- (b) *Packages* containing *fissile material* in any form provided that:
 - (i) The smallest external dimension of the *package* is not less than 30 cm.
 - (ii) The *package*, after being subjected to the tests specified in paras 719–724:
 - Retains its *fissile material* contents;
 - Preserves the minimum overall outside dimensions of the *package* to at least 30 cm;
 - Prevents the entry of a 10 cm cube.
 - (iii) The *CSI* of the *package* is calculated using the following formula:

$$CSI = 50 \times 2 \times \{[\text{mass of uranium-235 in } package \text{ (g)}]/Z + [\text{mass of other fissile nuclides}^1 \text{ in } package \text{ (g)}]/280\}$$
 where the values of *Z* are taken from Table 13.
 - (iv) The *CSI* of any *package* does not exceed 10.
- (c) *Packages* containing *fissile material* in any form provided that:
 - (i) The smallest external dimension of the *package* is not less than 10 cm.

TABLE 13. VALUES OF *Z* FOR CALCULATION OF *CSI* IN ACCORDANCE WITH PARA. 674

Enrichment ^a	<i>Z</i>
<i>Uranium</i> enriched up to 1.5%	2200
<i>Uranium</i> enriched up to 5%	850
<i>Uranium</i> enriched up to 10%	660
<i>Uranium</i> enriched up to 20%	580
<i>Uranium</i> enriched up to 100%	450

^a If a *package* contains *uranium* with varying enrichments of uranium-235, then the value corresponding to the highest enrichment shall be used for *Z*.

¹ Plutonium may be of any isotopic composition provided that the amount of plutonium-241 is less than that of plutonium-240 in the *package*.

SECTION VI

- (ii) The *package*, after being subjected to the tests specified in paras 719–724:
 - Retains its *fissile material* contents;
 - Preserves the minimum overall outside dimensions of the *package* to at least 10 cm;
 - Prevents the entry of a 10 cm cube.
- (iii) The *CSI* of the *package* is calculated using the following formula:
$$CSI = 50 \times 2 \times \{[\text{mass of uranium-235 in } \textit{package} \text{ (g)}]/450 + [\text{mass of other } \textit{fissile nuclides}^1 \text{ in } \textit{package} \text{ (g)}]/280\}$$
- (iv) The total mass of *fissile nuclides* in any *package* does not exceed 15 g.
- (d) The total mass of beryllium, hydrogenous material enriched in deuterium, graphite and other allotropic forms of carbon in an individual *package* shall not be greater than the mass of *fissile nuclides* in the *package* except where the total concentration of these materials does not exceed 1 g in any 1000 g of material. Beryllium incorporated in copper alloys up to 4% by weight of the alloy does not need to be considered.

675. *Packages* containing not more than 1000 g of plutonium are excepted from the application of paras 676–686 provided that:

- (a) Not more than 20% of the plutonium by mass is *fissile nuclides*.
- (b) The *CSI* of the *package* is calculated using the following formula:
$$CSI = 50 \times 2 \times [\text{mass of plutonium (g)}]/1000]$$
- (c) If *uranium* is present with the plutonium, the mass of *uranium* shall be no more than 1% of the mass of the plutonium.

Contents specification for assessments of package designs containing fissile material

676. Where the chemical or physical form, isotopic composition, mass or concentration, moderation ratio or density, or geometric configuration is not known, the assessments of paras 680–685 shall be performed assuming that each parameter that is not known has the value that gives the maximum neutron multiplication consistent with the known conditions and parameters in these assessments.

677. For irradiated nuclear fuel, the assessments of paras 680–685 shall be based on an isotopic composition demonstrated to provide either:

- (a) The maximum neutron multiplication during the irradiation history; or

REQUIREMENTS FOR PACKAGES

- (b) A conservative estimate of the neutron multiplication for the *package* assessments. After irradiation but prior to *shipment*, a measurement shall be performed to confirm the conservatism of the isotopic composition.

Geometry and temperature requirements

678. The *package*, after being subjected to the tests specified in paras 719–724, shall:

- (a) Preserve the minimum overall outside dimensions of the *package* to at least 10 cm;
- (b) Prevent the entry of a 10 cm cube.

679. The *package* shall be designed for an ambient temperature range of -40°C to $+38^{\circ}\text{C}$ unless the *competent authority* specifies otherwise in the certificate of *approval* for the *package design*.

Assessment of an individual package in isolation

680. For a *package* in isolation, it shall be assumed that water can leak into or out of all void spaces of the *package*, including those within the *containment system*.

However, if the *design* incorporates special features to prevent such leakage of water into or out of certain void spaces, even as a result of error, absence of leakage may be assumed in respect of those void spaces. Special features shall include either of the following:

- (a) Multiple high standard water barriers, not less than two of which would remain watertight if the *package* were subject to the tests prescribed in para. 685(b), a high degree of quality control in the manufacture, maintenance and repair of *packagings*, and tests to demonstrate the closure of each *package* before each *shipment*; or
- (b) For *packages* containing uranium hexafluoride only, with a maximum *uranium* enrichment of 5 mass per cent uranium-235:
 - (i) *Packages* where, following the tests prescribed in para. 685(b), there is no physical contact between the valve or the plug and any other component of the *packaging* other than at its original point of attachment and where, in addition, following the test prescribed in para. 728, the valve and the plug remain leaktight;

SECTION VI

- (ii) A high degree of quality control in the manufacture, maintenance and repair of *packagings*, coupled with tests to demonstrate closure of each *package* before each *shipment*.

681. It shall be assumed that the *confinement system* is closely reflected by at least 20 cm of water or such greater reflection as may additionally be provided by the surrounding material of the *packaging*. However, when it can be demonstrated that the *confinement system* remains within the *packaging* following the tests prescribed in para. 685(b), close reflection of the *package* by at least 20 cm of water may be assumed in para. 682(c).

682. The *package* shall be subcritical under the conditions of paras 680 and 681 and with the *package* conditions that result in the maximum neutron multiplication consistent with:

- (a) Routine conditions of transport (incident free);
- (b) The tests specified in para. 684(b);
- (c) The tests specified in para. 685(b).

683. For *packages* to be transported by air:

- (a) The *package* shall be subcritical under conditions consistent with the *Type C package* tests specified in para. 734, assuming reflection by at least 20 cm of water but no water in-leakage.
- (b) In the assessment of para. 682, use of special features as specified in para. 680 is allowed provided that leakage of water into or out of the void spaces is prevented when the *package* is submitted to the *Type C package* tests specified in para. 734 followed by the water leakage test specified in para. 733.

Assessment of package arrays under normal conditions of transport

684. A number N shall be derived, such that five times N *packages* shall be subcritical for the arrangement and *package* conditions that provide the maximum neutron multiplication consistent with the following:

- (a) There shall not be anything between the *packages*, and the *package* arrangement shall be reflected on all sides by at least 20 cm of water.
- (b) The state of the *packages* shall be their assessed or demonstrated condition if they had been subjected to the tests specified in paras 719–724.

REQUIREMENTS FOR PACKAGES

Assessment of package arrays under accident conditions of transport

685. A number N shall be derived, such that two times N *packages* shall be subcritical for the arrangement and *package* conditions that provide the maximum neutron multiplication consistent with the following:

- (a) Hydrogenous moderation between the *packages* and the *package* arrangement reflected on all sides by at least 20 cm of water.
- (b) The tests specified in paras 719–724 followed by whichever of the following is the more limiting:
 - (i) The tests specified in para. 727(b) and either para. 727(c) for *packages* having a mass not greater than 500 kg and an overall density not greater than 1000 kg/m^3 based on the external dimensions or para. 727(a) for all other *packages*, followed by the test specified in para. 728 and completed by the tests specified in paras 731–733; or
 - (ii) The test specified in para. 729.
- (c) Where any part of the *fissile material* escapes from the *containment system* following the tests specified in para. 685(b), it shall be assumed that *fissile material* escapes from each *package* in the array and that all of the *fissile material* shall be arranged in the configuration and moderation that results in the maximum neutron multiplication with close reflection by at least 20 cm of water.

Determination of criticality safety index for packages

686. The *CSI* for *packages* containing *fissile material* shall be obtained by dividing the number 50 by the smaller of the two values of N derived in paras 684 and 685 (i.e. $CSI = 50/N$). The value of the *CSI* may be zero, provided that an unlimited number of *packages* are subcritical (i.e. N is effectively equal to infinity in both cases).

Section VII

TEST PROCEDURES

DEMONSTRATION OF COMPLIANCE

701. Demonstration of compliance with the performance standards required in Section VI shall be accomplished by any of the following methods listed below or by a combination thereof:

- (a) Performance of tests with specimens representing *special form radioactive material*, or *low dispersible radioactive material*, or with prototypes or samples of the *packaging*, where the contents of the specimen or the *packaging* for the tests shall simulate as closely as practicable the expected range of *radioactive contents* and the specimen or *packaging* to be tested shall be prepared as presented for transport.
- (b) Reference to previous satisfactory demonstrations of a sufficiently similar nature.
- (c) Performance of tests with models of appropriate scale, incorporating those features that are significant with respect to the item under investigation when engineering experience has shown the results of such tests to be suitable for *design* purposes. When a scale model is used, the need for adjusting certain test parameters, such as penetrator diameter or compressive load, shall be taken into account.
- (d) Calculation, or reasoned argument, when the calculation procedures and parameters are generally agreed to be reliable or conservative.

702. After the specimen, prototype or sample has been subjected to the tests, appropriate methods of assessment shall be used to ensure that the requirements of this section have been fulfilled in compliance with the performance and acceptance standards prescribed in Section VI.

LEACHING TEST FOR LOW DISPERSIBLE RADIOACTIVE MATERIAL

703. A solid material sample representing the entire contents of the *package* shall be immersed for 7 days in water at ambient temperature. The volume of water to be used in the test shall be sufficient to ensure that at the end of the 7 day test period, the free volume of the unabsorbed and unreacted water remaining shall be at least 10% of the volume of the solid test sample itself. The water shall

SECTION VII

have an initial pH of 6–8 and a maximum conductivity of 1 mS/m at 20°C. The total activity of the free volume of water shall be measured following the 7 day immersion of the test sample.

TESTS FOR SPECIAL FORM RADIOACTIVE MATERIAL

General

704. Specimens that comprise or simulate *special form radioactive material* shall be subjected to the impact test, the percussion test, the bending test and the heat test specified in paras 705–708. A different specimen may be used for each of the tests. Following each test, a leaching assessment or volumetric leakage test shall be performed on the specimen by a method no less sensitive than the methods given in para. 710 for indispersible solid material or in para. 711 for encapsulated material.

Test methods

705. Impact test: The specimen shall drop onto the target from a height of 9 m. The target shall be as defined in para. 717.

706. Percussion test: The specimen shall be placed on a sheet of lead that is supported by a smooth solid surface and struck by the flat face of a mild steel bar so as to cause an impact equivalent to that resulting from a free drop of 1.4 kg from a height of 1 m. The lower part of the bar shall be 25 mm in diameter with the edges rounded off to a radius of 3.0 ± 0.3 mm. The lead, of hardness number 3.5–4.5 on the Vickers scale and not more than 25 mm thick, shall cover an area greater than that covered by the specimen. A fresh surface of lead shall be used for each impact. The bar shall strike the specimen so as to cause maximum damage.

707. Bending test: The test shall apply only to long, slender sources with both a minimum length of 10 cm and a length to minimum width ratio of not less than 10. The specimen shall be rigidly clamped in a horizontal position so that one half of its length protrudes from the face of the clamp. The orientation of the specimen shall be such that the specimen will suffer maximum damage when its free end is struck by the flat face of a steel bar. The bar shall strike the specimen so as to cause an impact equivalent to that resulting from a free vertical drop of 1.4 kg from a height of 1 m. The lower part of the bar shall be 25 mm in diameter with the edges rounded off to a radius of 3.0 ± 0.3 mm.

TEST PROCEDURES

708. Heat test: The specimen shall be heated in air to a temperature of 800°C and held at that temperature for a period of 10 min and shall then be allowed to cool.

709. Specimens that comprise or simulate *radioactive material* enclosed in a sealed capsule may be excepted from:

- (a) The tests prescribed in paras 705 and 706, provided that the specimens are alternatively subjected to the impact test prescribed in the International Organization for Standardization document: Radiological Protection — Sealed Radioactive Sources — General Requirements and Classification (ISO 2919) [20]:
 - (i) The Class 4 impact test if the mass of the *special form radioactive material* is less than 200 g;
 - (ii) The Class 5 impact test if the mass of the *special form radioactive material* is more than 200 g but less than 500 g.
- (b) The test prescribed in para. 708, provided the specimens are alternatively subjected to the Class 6 temperature test specified in ISO 2919 [20].

Leaching and volumetric leakage assessment methods

710. For specimens that comprise or simulate indispersible solid material, a leaching assessment shall be performed as follows:

- (a) The specimen shall be immersed for 7 days in water at ambient temperature. The volume of water to be used in the test shall be sufficient to ensure that at the end of the 7 day test period the free volume of the unabsorbed and unreacted water remaining shall be at least 10% of the volume of the solid test sample itself. The water shall have an initial pH of 6–8 and a maximum conductivity of 1 mS/m at 20°C.
- (b) The water and the specimen shall then be heated to a temperature of $50 \pm 5^\circ\text{C}$ and maintained at this temperature for 4 h.
- (c) The activity of the water shall then be determined.
- (d) The specimen shall then be kept for at least 7 days in still air at not less than 30°C and with a relative humidity of not less than 90%.
- (e) The specimen shall then be immersed in water of the same specification as that in (a) and the water and the specimen shall be heated to $50 \pm 5^\circ\text{C}$ and maintained at this temperature for 4 h.
- (f) The activity of the water shall then be determined.

SECTION VII

711. For specimens that comprise or simulate *radioactive material* enclosed in a sealed capsule, either a leaching assessment or a volumetric leakage assessment shall be performed as follows:

- (a) The leaching assessment shall consist of the following steps:
 - (i) The specimen shall be immersed in water at ambient temperature. The water shall have an initial pH of 6–8 with a maximum conductivity of 1 mS/m at 20°C.
 - (ii) The water and the specimen shall then be heated to a temperature of $50 \pm 5^\circ\text{C}$ and maintained at this temperature for 4 h.
 - (iii) The activity of the water shall then be determined.
 - (iv) The specimen shall then be kept for at least 7 days in still air at not less than 30°C and with a relative humidity of not less than 90%.
 - (v) The process in (i), (ii) and (iii) shall be repeated.
- (b) The alternative volumetric leakage assessment shall comprise any of the tests prescribed in the International Organization for Standardization document: Radiation Protection — Sealed Radioactive Sources — Leakage Test Methods (ISO 9978) [16] provided that they are acceptable to the *competent authority*.

TESTS FOR LOW DISPERSIBLE RADIOACTIVE MATERIAL

712. A specimen that comprises or simulates *low dispersible radioactive material* shall be subjected to the enhanced thermal test specified in para. 736 and the impact test specified in para. 737. A different specimen may be used for each of the tests. Following each test, the specimen shall be subjected to the leach test specified in para. 703. After each test it shall be determined if the applicable requirements of para. 605 have been met.

TESTS FOR PACKAGES

Preparation of a specimen for testing

713. All specimens shall be inspected before testing in order to identify and record faults or damage, including the following:

- (a) Divergence from the *design*;
- (b) Defects in manufacture;

TEST PROCEDURES

- (c) Corrosion or other deterioration;
- (d) Distortion of features.

714. The *containment system* of the *package* shall be clearly specified

715. The external features of the specimen shall be clearly identified so that reference may be made simply and clearly to any part of such a specimen.

Testing the integrity of the containment system and shielding and assessing criticality safety

716. After each test or group of tests or sequence of the applicable tests, as appropriate, specified in paras 718–737:

- (a) Faults and damage shall be identified and recorded.
- (b) It shall be determined whether the integrity of the *containment system* and shielding has been retained to the extent required in Section VI for the *package* under test.
- (c) For *packages* containing *fissile material*, it shall be determined whether the assumptions and conditions used in the assessments required by paras 673–686 for one or more *packages* are valid.

Target for drop tests

717. The target for the drop test specified in paras 705, 722, 725(a), 727 and 735 shall be a flat, horizontal surface of such a character that any increase in its resistance to displacement or deformation upon impact by the specimen would not significantly increase damage to the specimen.

Test for packagings designed to contain uranium hexafluoride

718. Specimens that comprise or simulate *packagings* designed to contain 0.1 kg or more of uranium hexafluoride shall be tested hydraulically at an internal pressure of at least 1.38 MPa, but when the test pressure is less than 2.76 MPa, the *design* shall require *multilateral approval*. For retesting *packagings*, any other equivalent non-destructive testing may be applied, subject to *multilateral approval*.

Tests for demonstrating ability to withstand normal conditions of transport

719. The tests are the water spray test, the free drop test, the stacking test and the penetration test. Specimens of the *package* shall be subjected to the free drop test, the stacking test and the penetration test, preceded in each case by the water spray test. One specimen may be used for all the tests, provided that the requirements of para. 720 are fulfilled.

720. The time interval between the conclusion of the water spray test and the succeeding test shall be such that the water has soaked in to the maximum extent, without appreciable drying of the exterior of the specimen. In the absence of any evidence to the contrary, this interval shall be taken to be 2 h if the water spray is applied from four directions simultaneously. No time interval shall elapse, however, if the water spray is applied from each of the four directions consecutively.

721. Water spray test: The specimen shall be subjected to a water spray test that simulates exposure to rainfall of approximately 5 cm per hour for at least 1 h.

722. Free drop test: The specimen shall drop onto the target so as to suffer maximum damage in respect of the safety features to be tested:

- (a) The height of the drop, measured from the lowest point of the specimen to the upper surface of the target, shall be not less than the distance specified in Table 14 for the applicable mass. The target shall be as defined in para. 717.
- (b) For rectangular fibreboard or wood *packages* not exceeding a mass of 50 kg, a separate specimen shall be subjected to a free drop onto each corner from a height of 0.3 m.
- (c) For cylindrical fibreboard *packages* not exceeding a mass of 100 kg, a separate specimen shall be subjected to a free drop onto each of the quarters of each rim from a height of 0.3 m.

723. Stacking test: Unless the shape of the *packaging* effectively prevents stacking, the specimen shall be subjected, for a period of 24 h, to a compressive load equal to the greater of the following:

- (a) The equivalent of 5 times the maximum weight of the *package*;
- (b) The equivalent of 13 kPa multiplied by the vertically projected area of the *package*.

TEST PROCEDURES

TABLE 14. FREE DROP DISTANCE FOR TESTING PACKAGES TO NORMAL CONDITIONS OF TRANSPORT

<i>Package mass (kg)</i>	Free drop distance (m)
$package\ mass < 5\ 000$	1.2
$5\ 000 \leq package\ mass < 10\ 000$	0.9
$10\ 000 \leq package\ mass < 15\ 000$	0.6
$15\ 000 \leq package\ mass$	0.3

The load shall be applied uniformly to two opposite sides of the specimen, one of which shall be the base on which the *package* would typically rest.

724. Penetration test: The specimen shall be placed on a rigid, flat, horizontal surface that will not move significantly while the test is being carried out:

- (a) A bar, 3.2 cm in diameter with a hemispherical end and a mass of 6 kg, shall be dropped and directed to fall with its longitudinal axis vertical onto the centre of the weakest part of the specimen so that if it penetrates sufficiently far it will hit the *containment system*. The bar shall not be significantly deformed by the test performance.
- (b) The height of the drop of the bar, measured from its lower end to the intended point of impact on the upper surface of the specimen, shall be 1 m.

Additional tests for Type A packages designed for liquids and gases

725. A specimen, or separate specimens, shall be subjected to each of the following tests unless it can be demonstrated that one test is more severe for the specimen in question than the other, in which case one specimen shall be subjected to the more severe test:

- (a) Free drop test: The specimen shall drop onto the target so as to suffer the maximum damage in respect of containment. The height of the drop, measured from the lowest part of the specimen to the upper surface of the target, shall be 9 m. The target shall be as defined in para. 717.
- (b) Penetration test: The specimen shall be subjected to the test specified in para. 724, except that the height of the drop shall be increased to 1.7 m from the 1 m specified in para. 724(b).

Tests for demonstrating ability to withstand accident conditions of transport

726. The specimen shall be subjected to the cumulative effects of the tests specified in paras 727 and 728, in that order. Following these tests, either this specimen or a separate specimen shall be subjected to the effect(s) of the water immersion test(s), as specified in para. 729 and, if applicable, para. 730.

727. Mechanical test: The mechanical test consists of three different drop tests. Each specimen shall be subjected to the applicable drops, as specified in para. 659 or para. 685. The order in which the specimen is subjected to the drops shall be such that, on completion of the mechanical test, the specimen shall have suffered such damage as will lead to maximum damage in the thermal test that follows:

- (a) For drop I, the specimen shall drop onto the target so as to suffer maximum damage, and the height of the drop, measured from the lowest point of the specimen to the upper surface of the target, shall be 9 m. The target shall be as defined in para. 717.
- (b) For drop II, the specimen shall drop onto a bar rigidly mounted perpendicularly on the target so as to suffer maximum damage. The height of the drop, measured from the intended point of impact of the specimen to the upper surface of the bar, shall be 1 m. The bar shall be of solid mild steel of circular cross-section, 15.0 ± 0.5 cm in diameter and 20 cm long, unless a longer bar would cause greater damage, in which case a bar of sufficient length to cause maximum damage shall be used. The upper end of the bar shall be flat and horizontal with its edge rounded off to a radius of not more than 6 mm. The target on which the bar is mounted shall be as described in para. 717.
- (c) For drop III, the specimen shall be subjected to a dynamic crush test by positioning the specimen on the target so as to suffer maximum damage by the drop of a 500 kg mass from 9 m onto the specimen. The mass shall consist of a solid mild steel plate 1 m \times 1 m and shall fall in a horizontal attitude. The lower face of the steel plate shall have its edges and corners rounded off to a radius of not more than 6 mm. The height of the drop shall be measured from the underside of the plate to the highest point of the specimen. The target on which the specimen rests shall be as defined in para. 717.

728. Thermal test: The specimen shall be in thermal equilibrium under conditions of an ambient temperature of 38°C, subject to the solar insolation conditions specified in Table 12 and subject to the *design* maximum rate of internal heat generation within the *package* from the *radioactive contents*. Alternatively, any

TEST PROCEDURES

of these parameters are allowed to have different values prior to, and during, the test, provided due account is taken of them in the subsequent assessment of *package* response. The thermal test shall then consist of (a) followed by (b).

- (a) Exposure of a specimen for a period of 30 min to a thermal environment that provides a heat flux at least equivalent to that of a hydrocarbon fuel–air fire in sufficiently quiescent ambient conditions to give a minimum average flame emissivity coefficient of 0.9 and an average temperature of at least 800°C, fully engulfing the specimen, with a surface absorptivity coefficient of 0.8 or that value that the *package* may be demonstrated to possess if exposed to the fire specified.
- (b) Exposure of the specimen to an ambient temperature of 38°C, subject to the solar insolation conditions specified in Table 12 and subject to the *design* maximum rate of internal heat generation within the *package* by the *radioactive contents* for a sufficient period to ensure that temperatures in the specimen are decreasing in all parts of the specimen and/or are approaching initial steady state conditions. Alternatively, any of these parameters are allowed to have different values following cessation of heating, provided due account is taken of them in the subsequent assessment of *package* response. During and following the test, the specimen shall not be artificially cooled and any combustion of materials of the specimen shall be permitted to proceed naturally.

729. Water immersion test: The specimen shall be immersed under a head of water of at least 15 m for a period of not less than 8 h in the attitude that will lead to maximum damage. For demonstration purposes, an external gauge pressure of at least 150 kPa shall be considered to meet these conditions.

Enhanced water immersion test for Type B(U) and Type B(M) packages containing more than 10^5A_2 and Type C packages

730. Enhanced water immersion test: The specimen shall be immersed under a head of water of at least 200 m for a period of not less than 1 h. For demonstration purposes, an external gauge pressure of at least 2 MPa shall be considered to meet these conditions.

Water leakage test for packages containing fissile material

731. *Packages* for which water in-leakage or out-leakage to the extent that results in greatest reactivity has been assumed for purposes of assessment under paras 680–685 shall be excepted from the water leakage test.

SECTION VII

732. Before the specimen is subjected to the water leakage test specified below, it shall be subjected to the tests in para. 727(b) and either para. 727(a) or 727(c), as required by para. 685 and the test specified in para. 728.

733. The specimen shall be immersed under a head of water of at least 0.9 m for a period of not less than 8 h and in the attitude for which maximum leakage is expected.

Tests for Type C packages

734. Specimens shall be subjected to the effects of the following test sequences:

- (a) The tests specified in paras 727(a), 727(c), 735 and 736, in this order;
- (b) The test specified in para. 737.

Separate specimens are allowed to be used for the sequence in (a) and for (b).

735. Puncture-tearing test: The specimen shall be subjected to the damaging effects of a vertical solid probe made of mild steel. The orientation of the *package* specimen and the impact point on the *package* surface shall be such as to cause maximum damage at the conclusion of the test sequence specified in para. 734(a):

- (a) The specimen, representing a *package* having a mass of less than 250 kg, shall be placed on a target and subjected to a probe having a mass of 250 kg falling from a height of 3 m above the intended impact point. For this test the probe shall be a 20 cm diameter cylindrical bar with the striking end forming the frustum of a right circular cone with the following dimensions: 30 cm height and 2.5 cm diameter at the top with its edge rounded off to a radius of not more than 6 mm. The target on which the specimen is placed shall be as specified in para. 717.
- (b) For *packages* having a mass of 250 kg or more, the base of the probe shall be placed on a target and the specimen dropped onto the probe. The height of the drop, measured from the point of impact with the specimen to the upper surface of the probe, shall be 3 m. The probe for this test shall have the same properties and dimensions as specified in (a), except that the length and mass of the probe shall be such as to cause maximum damage to the specimen. The target on which the base of the probe is placed shall be as specified in para. 717.

TEST PROCEDURES

736. Enhanced thermal test: The conditions for this test shall be as specified in para. 728, except that the exposure to the thermal environment shall be for a period of 60 min.

737. Impact test: The specimen shall be subject to an impact on a target at a velocity of not less than 90 m/s, at such an orientation as to suffer maximum damage. The target shall be as defined in para. 717, except that the target surface may be at any orientation as long as the surface is normal to the specimen path.

Section VIII

APPROVAL AND ADMINISTRATIVE REQUIREMENTS

GENERAL

801. For *package designs* where it is not required that a *competent authority* issue a certificate of *approval*, the *consignor* shall, on request, make available for inspection by the relevant *competent authority*, documentary evidence of the compliance of the *package design* with all the applicable requirements.

802. *Competent authority approval* shall be required for the following:

- (a) *Designs* for:
 - (i) *Special form radioactive material* (see paras 803, 804 and 823);
 - (ii) *Low dispersible radioactive material* (see paras 803 and 804);
 - (iii) *Fissile material* excepted under para. 417(f) (see paras 805 and 806);
 - (iv) *Packages* containing 0.1 kg or more of uranium hexafluoride (see para. 807);
 - (v) *Packages* containing *fissile material*, unless excepted by para. 417, 674 or 675 (see paras 814–816 and 820);
 - (vi) *Type B(U) packages* and *Type B(M) packages* (see paras 808–813 and 820);
 - (vii) *Type C packages* (see paras 808–810).
- (b) *Special arrangements* (see paras 829–831).
- (c) Certain *shipments* (see paras 825–828).
- (d) *Radiation protection programme* for special use *vessels* (see para. 576(a)).
- (e) Calculation of radionuclide values that are not listed in Table 2 (see para. 403(a)).
- (f) Calculation of alternative activity limits for an exempt *consignment* of instruments or articles (see para. 403(b)).

The certificates of *approval* for the *package design* and the *shipment* may be combined into a single certificate.

SECTION VIII

APPROVAL OF SPECIAL FORM RADIOACTIVE MATERIAL AND LOW DISPERSIBLE RADIOACTIVE MATERIAL

803. The *design* for *special form radioactive material* shall require *unilateral approval*. The *design* for *low dispersible radioactive material* shall require *multilateral approval*. In both cases, an application for *approval* shall include:

- (a) A detailed description of the *radioactive material* or, if a capsule, the contents; particular reference shall be made to both physical and chemical states.
- (b) A detailed statement of the *design* of any capsule to be used.
- (c) A statement of the tests that have been carried out and their results, or evidence based on calculations, to show that the *radioactive material* is capable of meeting the performance standards, or other evidence that the *special form radioactive material* or *low dispersible radioactive material* meets the applicable requirements of these Regulations.
- (d) A specification of the applicable *management system*, as required in para. 306.
- (e) Any proposed pre-shipment actions for use in the *consignment* of *special form radioactive material* or *low dispersible radioactive material*.

804. The *competent authority* shall establish a certificate of *approval* stating that the approved *design* meets the requirements for *special form radioactive material* or *low dispersible radioactive material* and shall attribute to that *design* an identification mark.

APPROVAL OF MATERIAL EXCEPTED FROM FISSILE CLASSIFICATION

805. The *design* for *fissile material* excepted from “FISSILE” classification in accordance with Table 1, under para. 417(f) shall require *multilateral approval*. An application for *approval* shall include:

- (a) A detailed description of the material; particular reference shall be made to both physical and chemical states.
- (b) A statement of the tests that have been carried out and their results, or evidence based on calculations, to show that the material is capable of meeting the requirements specified in para. 606.

APPROVAL AND ADMINISTRATIVE REQUIREMENTS

- (c) A specification of the applicable *management system* as required in para. 306.
- (d) A statement of specific actions to be taken prior to *shipment*.

806. The *competent authority* shall establish a certificate of *approval* stating that the approved material meets the requirements for *fissile material* excepted by the *competent authority* in accordance with para. 606 and shall attribute to that *design* an identification mark.

APPROVAL OF PACKAGE DESIGNS

Approval of package designs to contain uranium hexafluoride

807. The *approval* of *designs* for *packages* containing 0.1 kg or more of uranium hexafluoride requires that:

- (a) Each *design* that meets the requirements of para. 634 shall require *multilateral approval*.
- (b) Each *design* that meets the requirements of paras 631–633 shall require *unilateral approval* by the *competent authority* of the country of origin of the *design*, unless *multilateral approval* is otherwise required by these Regulations.
- (c) The application for *approval* shall include all information necessary to satisfy the *competent authority* that the *design* meets the requirements of para. 631 and a specification of the applicable *management system*, as required in para. 306.
- (d) The *competent authority* shall establish a certificate of *approval* stating that the approved *design* meets the requirements of para. 631 and shall attribute to that *design* an identification mark.

Approval of Type B(U) and Type C package designs

808. Each *Type B(U)* and *Type C package design* shall require *unilateral approval*, except that:

- (a) A *package design* for *fissile material*, which is also subject to paras 814–816, shall require *multilateral approval*.
- (b) A *Type B(U) package design* for *low dispersible radioactive material* shall require *multilateral approval*.

SECTION VIII

809. An application for *approval* shall include:

- (a) A detailed description of the proposed *radioactive contents* with reference to their physical and chemical states and the nature of the radiation emitted.
- (b) A detailed statement of the *design*, including complete engineering drawings and schedules of materials and methods of manufacture.
- (c) A statement of the tests that have been carried out and their results, or evidence based on calculations or other evidence that the *design* is adequate to meet the applicable requirements.
- (d) The proposed operating and maintenance instructions for the use of the *packaging*.
- (e) If the *package* is designed to have a *maximum normal operating pressure* in excess of 100 kPa gauge, a specification of the materials of manufacture of the *containment system*, the samples to be taken and the tests to be made.
- (f) If the *package* is to be used for *shipment* after storage, a justification of considerations to ageing mechanisms in the safety analysis and within the proposed operating and maintenance instructions.
- (g) Where the proposed *radioactive contents* are irradiated nuclear fuel, the applicant shall state and justify any assumption in the safety analysis relating to the characteristics of the fuel and describe any pre-shipment measurement required by para. 677(b).
- (h) Any special stowage provisions necessary to ensure the safe dissipation of heat from the *package* considering the various modes of transport to be used and the type of *conveyance* or *freight container*.
- (i) A reproducible illustration, not larger than 21 cm × 30 cm, showing the make-up of the *package*.
- (j) A specification of the applicable *management system* as required in para. 306.
- (k) For *packages* which are to be used for *shipment* after storage, a gap analysis programme describing a systematic procedure for a periodic evaluation of changes of regulations, changes in technical knowledge and changes of the state of the *package design* during storage.

810. The *competent authority* shall establish a certificate of *approval* stating that the approved *design* meets the requirements for *Type B(U)* or *Type C packages* and shall attribute to that *design* an identification mark.

Approval of Type B(M) package designs

811. Each *Type B(M) package design*, including those for *fissile material* which are also subject to paras 814–816 and those for *low dispersible radioactive material*, shall require *multilateral approval*.

812. An application for *approval* of a *Type B(M) package design* shall include, in addition to the information required in para. 809 for *Type B(U) packages*:

- (a) A list of the requirements specified in paras 639, 655–657 and 660–666 with which the *package* does not conform;
- (b) Any proposed supplementary operational controls to be applied during transport not regularly provided for in these Regulations, but which are necessary to ensure the safety of the *package* or to compensate for the deficiencies listed in (a);
- (c) A statement relative to any restrictions on the mode of transport and to any special loading, carriage, unloading or handling procedures;
- (d) A statement of the range of ambient conditions (temperature, solar insolation) that are expected to be encountered during transport and which have been taken into account in the *design*.

813. The *competent authority* shall establish a certificate of *approval* stating that the approved *design* meets the applicable requirements for *Type B(M) packages* and shall attribute to that *design* an identification mark.

Approval of package designs to contain fissile material

814. Each *package design* for *fissile material* that is not excepted by any of the paras 417(a)–(f), 674 and 675 shall require *multilateral approval*.

815. An application for *approval* shall include all information necessary to satisfy the *competent authority* that the *design* meets the requirements of para. 673 and a specification of the applicable *management system*, as required in para. 306.

816. The *competent authority* shall establish a certificate of *approval* stating that the approved *design* meets the requirements of para. 673 and shall attribute to that *design* an identification mark.

SECTION VIII

APPROVAL OF ALTERNATIVE ACTIVITY LIMITS FOR AN EXEMPT CONSIGNMENT OF INSTRUMENTS OR ARTICLES

817. Alternative activity limits for an exempt *consignment* of instruments or articles in accordance with para. 403(b) shall require *multilateral approval*. An application for *approval* shall include:

- (a) An identification, and a detailed description, of the instrument or article, its intended uses and the radionuclide(s) incorporated;
- (b) The maximum activity of the radionuclide(s) in the instrument or article;
- (c) The maximum external *dose rate* arising from the instrument or article;
- (d) The chemical and physical forms of the radionuclide(s) contained in the instrument or article;
- (e) Details of the construction and *design* of the instrument or article, particularly as related to the *containment* and shielding of the radionuclide in routine, normal and accident conditions of transport;
- (f) The applicable *management system*, including the quality testing and verification procedures to be applied to radioactive sources, components and finished products to ensure that the maximum specified activity of *radioactive material* or the maximum *dose rate* specified for the instrument or article are not exceeded, and that the instruments or articles are constructed according to the *design* specifications;
- (g) The maximum number of instruments or articles expected to be shipped per *consignment* and annually;
- (h) Dose assessments in accordance with the principles and methodologies set out in GSR Part 3 [2], including individual doses to transport workers and members of the public and, if appropriate, collective doses arising from routine, normal and accident conditions of transport, based on representative transport scenarios that the *consignments* are subject to.

818. The *competent authority* shall establish a certificate of *approval* stating that the approved alternative activity limit for an exempt *consignment* of instruments or articles meets the requirements of para. 403(b) and shall attribute to that certificate an identification mark.

TRANSITIONAL ARRANGEMENTS

Packages not requiring competent authority approval of design under the 1985, 1985 (As Amended 1990), 1996 Edition, 1996 Edition (Revised), 1996 (As Amended 2003), 2005, 2009 and 2012 Editions of these Regulations

819. *Packages* not requiring *competent authority approval of design (excepted packages, Type IP-1, Type IP-2, Type IP-3 and Type A packages)* shall meet this edition of these Regulations in full, except that:

- (a) *Packages* that meet the requirements of the 1985 or 1985 (As Amended 1990) Editions of these Regulations:
 - (i) May continue in transport provided that they were prepared for transport prior to 31 December 2003 and are subject to the requirements of para. 822, if applicable; or
 - (ii) May continue to be used, provided that all the following conditions are met:
 - (1) They were not designed to contain uranium hexafluoride.
 - (2) The applicable requirements of para. 306 of this edition of these Regulations are applied.
 - (3) The activity limits and classification in Section IV of this edition of these Regulations are applied.
 - (4) The requirements and controls for transport in Section V of this edition of these Regulations are applied.
 - (5) The *packaging* was not manufactured or modified after 31 December 2003.
- (b) *Packages* that meet the requirements of the 1996 Edition, 1996 Edition (Revised), 1996 (As Amended 2003), 2005, 2009 or 2012 Editions of these Regulations:
 - (i) May continue in transport provided that they were prepared for transport prior to 31 December 2025 and are subject to the requirements of para. 822, if applicable; or
 - (ii) May continue to be used, provided that all the following conditions are met:
 - (1) The applicable requirements of para. 306 of this edition of these Regulations are applied;
 - (2) The activity limits and classification in Section IV of this edition of these Regulations are applied;
 - (3) The requirements and controls for transport in Section V of this edition of these Regulations are applied; and

SECTION VIII

- (4) The *packaging* was not manufactured or modified after 31 December 2025.

Package designs approved under the 1985, 1985 (As Amended 1990), 1996 Edition, 1996 Edition (Revised), 1996 (As Amended 2003), 2005, 2009 and 2012 Editions of these Regulations

820. *Packages* requiring *competent authority approval* of the *design* shall meet this edition of these Regulations in full except that:

- (a) *Packagings* that were manufactured to a *package design* approved by the *competent authority* under the provisions of 1985 or 1985 (As Amended 1990) Editions of these Regulations may continue to be used provided that all of the following conditions are met:
 - (i) The *package design* is subject to *multilateral approval*.
 - (ii) The applicable requirements of para. 306 of this edition of these Regulations are applied.
 - (iii) The activity limits and classification in Section IV of this edition of these Regulations are applied.
 - (iv) The Requirements and controls for transport in Section V of this edition of these Regulations are applied.
 - (v) For a *package* containing *fissile material* and transported by air, the requirement of para. 683 is met.
- (b) *Packagings* that were manufactured to a *package design* approved by the *competent authority* under the provisions of the 1996 Edition, 1996 Edition (Revised), 1996 (As Amended 2003), 2005, 2009 and 2012 Editions of these Regulations may continue to be used provided that all of the following conditions are met:
 - (i) The *package design* is subject to *multilateral approval* after 31 December 2025.
 - (ii) The applicable requirements of para. 306 of this edition of the Regulations are applied.
 - (iii) The activity limits and material restrictions of Section IV of this edition of these Regulations are applied.
 - (iv) The requirements and controls for transport in Section V of this edition of these Regulations are applied.

821. No new manufacture of *packagings* to a *package design* meeting the provisions of the 1985 and 1985 (As Amended 1990) Editions of these Regulations shall be permitted to commence.

821A. No new manufacture of *packagings* of a *package design* meeting the provisions of the 1996 Edition, 1996 Edition (Revised), 1996 (As Amended 2003), 2005, 2009 and 2012 Editions of these Regulations shall be permitted to commence after 31 December 2028.

Packages excepted from the requirements for fissile material under the 2009 Edition of these Regulations

822. *Packages* containing *fissile material* that is excepted from classification as “FISSILE” according to para. 417(a)(i) or (iii) of the 2009 Edition of these Regulations prepared for transport before 31 December 2014 may continue in transport and may continue to be classified as non-fissile or fissile-excepted except that the *consignment* limits in Table 4 of the 2009 Edition of these Regulations shall apply to the *conveyance*. The *consignment* shall be transported under *exclusive use*.

Special form radioactive material approved under the 1985, 1985 (As Amended 1990), 1996 Edition, 1996 Edition (Revised), 1996 (As Amended 2003), 2005, 2009 and 2012 Editions of these Regulations

823. *Special form radioactive material* manufactured to a *design* that had received *unilateral approval* by the *competent authority* under the 1985, 1985 (As Amended 1990), 1996 Edition, 1996 Edition (Revised), 1996 (As Amended 2003), 2005, 2009 and 2012 Editions of these Regulations may continue to be used when in compliance with the mandatory *management system* in accordance with the applicable requirements of para. 306. There shall be no new manufacture of *special form radioactive material* to a *design* that had received *unilateral approval* by the *competent authority* under the 1985 or 1985 (As Amended 1990) Editions of these Regulations. No new manufacture of *special form radioactive material* to a *design* that had received *unilateral approval* by the *competent authority* under the 1996 Edition, 1996 Edition (Revised), 1996 (As Amended 2003), 2005, 2009 and 2012 Editions of these Regulations shall be permitted to commence after 31 December 2025.

NOTIFICATION AND REGISTRATION OF SERIAL NUMBERS

824. The *competent authority* shall be informed of the serial number of each *packaging* manufactured to a *design* approved under paras 808, 811, 814 and 820.

SECTION VIII

APPROVAL OF SHIPMENTS

825. *Multilateral approval* shall be required for:

- (a) The *shipment* of *Type B(M) packages* not conforming with the requirements of para. 639 or designed to allow controlled intermittent venting.
- (b) The *shipment* of *Type B(M) packages* containing *radioactive material* with an activity greater than $3000A_1$ or $3000A_2$, as appropriate, or 1000 TBq, whichever is the lower.
- (c) The *shipment* of *packages* containing *fissile material* if the sum of the *CSIs* of the *packages* in a single *freight container* or in a single *conveyance* exceeds 50. Excluded from this requirement shall be *shipments* by sea-going *vessels* if the sum of the *CSIs* does not exceed 50 for any hold, compartment or *defined deck area* and the distance of 6 m between groups of *packages* or *overpacks*, as required in Table 11, is met.
- (d) *Radiation protection programmes* for *shipments* by special use *vessels* in accordance with para. 576(a).
- (e) The *shipment* of *SCO-III*.

826. A *competent authority* may authorize transport *through or into* its country without *shipment approval*, by a specific provision in its *design approval*.

827. An application for *approval* of *shipment* shall include:

- (a) The period of time, related to the *shipment*, for which the *approval* is sought;
- (b) The actual *radioactive contents*, the expected modes of transport, the type of *conveyance* and the probable or proposed route;
- (c) The details of how the precautions and administrative or operational controls, referred to in the certificates of *approval* for the *package design*, if applicable, issued under paras 810, 813 and 816, are to be put into effect.

827A. An application for *approval* of *SCO-III shipments* shall include:

- (a) A statement of the respects in which, and of the reasons why, the *consignment* is considered *SCO-III*.
- (b) Justification for choosing *SCO-III* by demonstrating that:
 - (i) No suitable *packaging* currently exists;
 - (ii) Designing and/or constructing a *packaging* or segmenting the object is not practically, technically or economically feasible;
 - (iii) No other viable alternative exists.

APPROVAL AND ADMINISTRATIVE REQUIREMENTS

- (c) A detailed description of the proposed *radioactive contents* with reference to their physical and chemical states and the nature of the radiation emitted.
- (d) A detailed statement of the *design* of the *SCO-III*, including complete engineering drawings and schedules of materials and methods of manufacture.
- (e) All information necessary to satisfy the *competent authority* that the requirements of para. 520(e) and the requirements of para. 522, if applicable, are satisfied.
- (f) A transport plan.
- (g) A specification of the applicable *management system* as required in para. 306.

828. Upon *approval* of the *shipment*, the *competent authority* shall issue a certificate of *approval*.

APPROVAL OF SHIPMENTS UNDER SPECIAL ARRANGEMENT

829. Each *consignment* transported under *special arrangement* shall require *multilateral approval*.

830. An application for *approval* of *shipments* under *special arrangement* shall include all the information necessary to satisfy the *competent authority* that the overall level of safety in transport is at least equivalent to that which would be provided if all the applicable requirements of these Regulations had been met. The application shall also include:

- (a) A statement of the respects in which, and of the reasons why, the *shipment* cannot be made in full accordance with the applicable requirements;
- (b) A statement of any special precautions or special administrative or operational controls that are to be employed during transport to compensate for the failure to meet the applicable requirements.

831. Upon *approval* of *shipments* under *special arrangement*, the *competent authority* shall issue a certificate of *approval*.

SECTION VIII

COMPETENT AUTHORITY CERTIFICATES OF APPROVAL

Competent authority identification marks

832. Each certificate of *approval* issued by a *competent authority* shall be assigned an identification mark. The mark shall be of the following generalized type:

VRI/Number/Type code

- (a) Except as provided in para. 833(b), VRI represents the international *vehicle* registration identification code of the country issuing the certificate.
- (b) The number shall be assigned by the *competent authority* and shall be unique and specific with regard to the particular *design*, *shipment* or alternative activity limit for exempt *consignment*. The identification mark of the *approval* of *shipment* shall be clearly related to the identification mark of the *approval* of *design*.
- (c) The following type codes shall be used in the order listed to indicate the types of certificate of *approval* issued:
 - AF *Type A package design for fissile material*
 - B(U) *Type B(U) package design (B(U)F if for fissile material)*
 - B(M) *Type B(M) package design (B(M)F if for fissile material)*
 - C *Type C package design (CF if for fissile material)*
 - IF *Industrial package design for fissile material*
 - S *Special form radioactive material*
 - LD *Low dispersible radioactive material*
 - FE *Fissile material complying with the requirements of para. 606*
 - T *Shipment*
 - X *Special arrangement*
 - AL *Alternative activity limits for an exempt consignment of instruments or articles*

In the case of *package designs* for non-fissile or fissile-excepted uranium hexafluoride, where none of the above codes apply, the following type codes shall be used:

- H(U) *Unilateral approval*
- H(M) *Multilateral approval.*

APPROVAL AND ADMINISTRATIVE REQUIREMENTS

833. These identification marks shall be applied as follows:

- (a) Each certificate and each *package* shall bear the appropriate identification mark comprising the symbols prescribed in para. 832(a)–(c), except that, for *packages*, only the applicable *design* type codes shall appear following the second stroke, that is, the “T” or “X” shall not appear in the identification mark on the *package*. Where the *approval* of *design* and the *approval* of *shipment* are combined, the applicable type codes do not need to be repeated. For example:

A/132/B(M)F: A *Type B(M) package design* approved for *fissile material*, requiring *multilateral approval*, for which the *competent authority* of Austria has assigned the *design* number 132 (to be marked both on the *package* and on the certificate of *approval* for the *package design*)

A/132/B(M)FT: The *approval* of *shipment* issued for a *package* bearing the identification mark elaborated above (to be marked on the certificate only)

A/137/X: An *approval* of *special arrangement* issued by the *competent authority* of Austria, to which the number 137 has been assigned (to be marked on the certificate only)

A/139/IF: An industrial *package design* for *fissile material* approved by the *competent authority* of Austria, to which *package design* number 139 has been assigned (to be marked both on the *package* and on the certificate of *approval* for the *package design*)

A/145/H(U): A *package design* for fissile-excepted uranium hexafluoride approved by the *competent authority* of Austria, to which *package design* number 145 has been assigned (to be marked both on the *package* and on the certificate of *approval* for the *package design*).

- (b) Where *multilateral approval* is effected by validation in accordance with para. 840, only the identification mark issued by the country of origin of the *design* or *shipment* shall be used. Where *multilateral approval* is effected by issue of certificates by successive countries, each certificate shall bear the appropriate identification mark and the *package* whose *design* was so approved shall bear all appropriate identification marks.

For example:

A/132/B(M)F

CH/28/B(M)F

SECTION VIII

would be the identification mark of a *package* that was originally approved by Austria and was subsequently approved, by separate certificate, by Switzerland. Additional identification marks would be tabulated in a similar manner on the *package*.

- (c) The revision of a certificate shall be indicated by a parenthetical expression following the identification mark on the certificate. For example, A/132/B(M)F (Rev. 2) would indicate revision 2 of the Austrian certificate of *approval* for the *package design*; or A/132/B(M)F (Rev. 0) would indicate the original issuance of the Austrian certificate of *approval* for the *package design*. For original issuances, the parenthetical entry is optional and other words such as “original issuance” may also be used in place of “Rev. 0”. Certificate revision numbers may only be issued by the country issuing the original certificate of *approval*.
- (d) Additional symbols (as may be necessitated by national requirements) may be added in brackets to the end of the identification mark, for example, A/132/B(M)F (SP503).
- (e) It is not necessary to alter the identification mark on the *packaging* each time that a revision to the *design* certificate is made. Such re-marking shall be required only in those cases where the revision to the *package design* certificate involves a change in the letter type codes for the *package design* following the second stroke.

CONTENTS OF CERTIFICATES OF APPROVAL

Certificates of approval for special form radioactive material and low dispersible radioactive material

834. Each certificate of *approval* issued by a *competent authority* for *special form radioactive material* or *low dispersible radioactive material* shall include the following information:

- (a) Type of certificate;
- (b) The *competent authority* identification mark;
- (c) The issue date and an expiry date;
- (d) A list of applicable national and international regulations, including the edition of the IAEA Regulations for the Safe Transport of Radioactive Material under which the *special form radioactive material* or *low dispersible radioactive material* is approved;
- (e) The identification of the *special form radioactive material* or *low dispersible radioactive material*;

APPROVAL AND ADMINISTRATIVE REQUIREMENTS

- (f) A description of the *special form radioactive material* or *low dispersible radioactive material*;
- (g) *Design* specifications for the *special form radioactive material* or *low dispersible radioactive material*, which may include references to drawings;
- (h) A specification of the *radioactive contents* that includes the activities involved and which may include the physical and chemical forms;
- (i) A specification of the applicable *management system*, as required in para. 306;
- (j) Reference to information provided by the applicant relating to specific actions to be taken prior to *shipment*;
- (k) If deemed appropriate by the *competent authority*, reference to the identity of the applicant;
- (l) Signature and identification of the certifying official.

Certificates of approval for material excepted from fissile classification

835. Each certificate of *approval* issued by a *competent authority* for material excepted from classification as “FISSILE” shall include the following information:

- (a) Type of certificate;
- (b) The *competent authority* identification mark;
- (c) The issue date and an expiry date;
- (d) A list of applicable national and international regulations, including the edition of the IAEA Regulations for the Safe Transport of Radioactive Material under which the exception is approved;
- (e) A description of the excepted material;
- (f) Limiting specifications for the excepted material;
- (g) A specification of the applicable *management system*, as required in para. 306;
- (h) Reference to information provided by the applicant relating to specific actions to be taken prior to *shipment*;
- (i) If deemed appropriate by the *competent authority*, reference to the identity of the applicant;
- (j) Signature and identification of the certifying official;
- (k) Reference to documentation that demonstrates compliance with para. 606.

Certificates of approval for special arrangement

836. Each certificate of *approval* issued by a *competent authority* for a *special arrangement* shall include the following information:

- (a) Type of certificate.
- (b) The *competent authority* identification mark.
- (c) The issue date and an expiry date.
- (d) Mode(s) of transport.
- (e) Any restrictions on the modes of transport, type of *conveyance*, *freight container* and any necessary routeing instructions.
- (f) A list of applicable national and international regulations, including the edition of the IAEA Regulations for the Safe Transport of Radioactive Material under which the *special arrangement* is approved.
- (g) The following statement: “This certificate does not relieve the *consignor* from compliance with any requirement of the government of any country *through or into* which the *package* will be transported”.
- (h) References to certificates for alternative *radioactive contents*, other *competent authority* validation, or additional technical data or information, as deemed appropriate by the *competent authority*.
- (i) Description of the *packaging* by reference to the drawings or a specification of the *design*. If deemed appropriate by the *competent authority*, a reproducible illustration not larger than 21 cm × 30 cm, showing the make-up of the *package*, should also be provided, accompanied by a brief description of the *packaging*, including materials of manufacture, gross mass, general external dimensions and appearance.
- (j) A specification of the authorized *radioactive contents*, including any restrictions on the *radioactive contents* that might not be obvious from the nature of the *packaging*. This specification shall include the physical and chemical forms, the activities involved (including those of the various isotopes, if appropriate), mass in grams (for *fissile material* or for each *fissile nuclide*, when appropriate) and whether the *special arrangement* is for *special form radioactive material*, *low dispersible radioactive material* or *fissile material* excepted under para. 417(f), if applicable.
- (k) Additionally, for *packages* containing *fissile material*:
 - (i) A detailed description of the authorized *radioactive contents*;
 - (ii) The value of the *CSI*;
 - (iii) Reference to the documentation that demonstrates the criticality safety of the *package*;
 - (iv) Any special features on the basis of which the absence of water from certain void spaces has been assumed in the criticality assessment;

APPROVAL AND ADMINISTRATIVE REQUIREMENTS

- (v) Any allowance (based on para. 677(b)) for a change in neutron multiplication assumed in the criticality assessment as a result of actual irradiation experience;
- (vi) The ambient temperature range for which the *special arrangement* has been approved.
- (l) A detailed listing of any supplementary operational controls required for preparation, loading, carriage, unloading and handling of the *consignment*, including any special stowage provisions for the safe dissipation of heat.
- (m) If deemed appropriate by the *competent authority*, reasons for the *special arrangement*.
- (n) Description of the compensatory measures to be applied as a result of the *shipment* being under *special arrangement*.
- (o) Reference to information provided by the applicant relating to the use of the *packaging* or specific actions to be taken prior to the *shipment*.
- (p) A statement regarding the ambient conditions assumed for purposes of *design* if these are not in accordance with those specified in paras 656, 657 and 666, as applicable.
- (q) Any emergency arrangements deemed necessary by the *competent authority*.
- (r) A specification of the applicable *management system*, as required in para. 306.
- (s) If deemed appropriate by the *competent authority*, reference to the identity of the applicant and to the identity of the *carrier*.
- (t) Signature and identification of the certifying official.

Certificates of approval for shipments

837. Each certificate of *approval* for a *shipment* issued by a *competent authority* shall include the following information:

- (a) Type of certificate.
- (b) The *competent authority* identification mark(s).
- (c) The issue date and an expiry date.
- (d) A list of applicable national and international regulations, including the edition of the IAEA Regulations for the Safe Transport of Radioactive Material under which the *shipment* is approved.
- (e) Any restrictions on the modes of transport, type of *conveyance*, *freight container* and any necessary routeing instructions.
- (f) The following statement: “This certificate does not relieve the *consignor* from compliance with any requirement of the government of any country *through or into* which the *package* will be transported”.

SECTION VIII

- (g) A detailed listing of any supplementary operational controls required for preparation, loading, carriage, unloading and handling of the *consignment*, including any special stowage provisions for the safe dissipation of heat or maintenance of criticality safety.
- (h) Reference to information provided by the applicant relating to specific actions to be taken prior to *shipment*.
- (i) Reference to the applicable certificate(s) of *approval of design*.
- (j) A specification of the actual *radioactive contents*, including any restrictions on the *radioactive contents* that might not be obvious from the nature of the *packaging*. This specification shall include the physical and chemical forms, the total activities involved (including those of the various isotopes, if appropriate), mass in grams (for *fissile material* or for each *fissile nuclide*, when appropriate) and whether the *shipment* is for *special form radioactive material*, *low dispersible radioactive material* or *fissile material* excepted under para. 417(f), if applicable.
- (k) Any emergency arrangements deemed necessary by the *competent authority*.
- (l) A specification of the applicable *management system*, as required in para. 306.
- (m) If deemed appropriate by the *competent authority*, reference to the identity of the applicant.
- (n) Signature and identification of the certifying official.

Certificates of approval for package design

838. Each certificate of *approval* of the *design* of a *package* issued by a *competent authority* shall include the following information:

- (a) Type of certificate.
- (b) The *competent authority* identification mark.
- (c) The issue date and an expiry date.
- (d) Any restriction on the modes of transport, if appropriate.
- (e) A list of applicable national and international regulations, including the edition of the IAEA Regulations for the Safe Transport of Radioactive Material under which the *design* is approved.
- (f) The following statement: “This certificate does not relieve the *consignor* from compliance with any requirement of the government of any country *through or into* which the *package* will be transported”.
- (g) References to certificates for alternative *radioactive contents*, other *competent authority* validation, or additional technical data or information, as deemed appropriate by the *competent authority*.

APPROVAL AND ADMINISTRATIVE REQUIREMENTS

- (h) A statement authorizing *shipment*, where *approval of shipment* is required under para. 825, if deemed appropriate.
- (i) Identification of the *packaging*.
- (j) Description of the *packaging* by reference to the drawings or specification of the *design*. If deemed appropriate by the *competent authority*, a reproducible illustration not larger than 21 cm × 30 cm, showing the make-up of the *package*, should also be provided, accompanied by a brief description of the *packaging*, including materials of manufacture, gross mass, general external dimensions and appearance.
- (k) Specification of the *design* by reference to the drawings.
- (l) A specification of the authorized *radioactive contents*, including any restrictions on the *radioactive contents* that might not be obvious from the nature of the *packaging*. This specification shall include the physical and chemical forms, the activities involved (including those of the various isotopes, if appropriate), the mass in grams (for *fissile material*, the total mass of *fissile nuclides* or the mass for each *fissile nuclide*, when appropriate) and whether the *package design* is for *special form radioactive material*, *low dispersible radioactive material* or *fissile material* excepted under para. 417(f), if applicable.
- (m) A description of the *containment system*.
- (n) For *package designs* containing *fissile material* that require *multilateral approval* of the *package design* in accordance with para. 814:
 - (i) A detailed description of the authorized *radioactive contents*;
 - (ii) A description of the *confinement system*;
 - (iii) The value of the *CSI*;
 - (iv) Reference to the documentation that demonstrates the criticality safety of the *package*;
 - (v) Any special features on the basis of which the absence of water from certain void spaces has been assumed in the criticality assessment;
 - (vi) Any allowance (based on para. 677(b)) for a change in neutron multiplication assumed in the criticality assessment as a result of actual irradiation experience;
 - (vii) The ambient temperature range for which the *package design* has been approved.
- (o) For *Type B(M) packages*, a statement specifying those prescriptions of paras 639, 655–657 and 660–666 with which the *package* does not conform and any amplifying information that may be useful to other *competent authorities*.
- (p) For *package designs* subject to para. 820, a statement specifying those requirements of the current regulations with which the *package* does not conform.

SECTION VIII

- (q) For *packages* containing more than 0.1 kg of uranium hexafluoride, a statement specifying those prescriptions of para. 634 that apply, if any, and any amplifying information that may be useful to other *competent authorities*.
- (r) A detailed listing of any supplementary operational controls required for preparation, loading, carriage, unloading and handling of the *consignment*, including any special stowage provisions for the safe dissipation of heat.
- (s) Reference to information provided by the applicant relating to the use of the *packaging* or to specific actions to be taken prior to *shipment*.
- (t) A statement regarding the ambient conditions assumed for purposes of *design*, if these are not in accordance with those specified in paras 656, 657 and 666, as applicable.
- (u) A specification of the applicable *management system*, as required in para. 306.
- (v) Any emergency arrangements deemed necessary by the *competent authority*.
- (w) If deemed appropriate by the *competent authority*, reference to the identity of the applicant.
- (x) Signature and identification of the certifying official.

Certificates of approval for alternative activity limits for an exempt consignment of instruments or articles

839. Each certificate issued by a *competent authority* for alternative activity limits for an exempt *consignment* of instruments or articles according to para. 818 shall include the following information:

- (a) Type of certificate;
- (b) The *competent authority* identification mark;
- (c) The issue date and an expiry date;
- (d) List of applicable national and international regulations, including the edition of the IAEA Regulations for the Safe Transport of Radioactive Material under which the exemption is approved;
- (e) The identification of the instrument or article;
- (f) A description of the instrument or article;
- (g) *Design* specifications for the instrument or article;
- (h) A specification of the radionuclide(s) and the approved alternative activity limit(s) for the exempt *consignment(s)* of the instrument(s) or article(s);
- (i) Reference to documentation that demonstrates compliance with para. 403(b);

APPROVAL AND ADMINISTRATIVE REQUIREMENTS

- (j) If deemed appropriate by the *competent authority*, reference to the identity of the applicant;
- (k) Signature and identification of the certifying official.

VALIDATION OF CERTIFICATES

840. *Multilateral approval* may be by validation of the original certificate issued by the *competent authority* of the country of origin of the *design* or *shipment*. Such validation may take the form of an endorsement on the original certificate or the issuance of a separate endorsement, annex, supplement, etc., by the *competent authority* of the country *through or into* which the *shipment* is made.

REFERENCES

References are to editions that are current as of the time of publication of these Regulations. Editions that supersede these may be adopted under national legislation.

- [1] EUROPEAN ATOMIC ENERGY COMMUNITY, FOOD AND AGRICULTURE ORGANIZATION OF THE UNITED NATIONS, INTERNATIONAL ATOMIC ENERGY AGENCY, INTERNATIONAL LABOUR ORGANIZATION, INTERNATIONAL MARITIME ORGANIZATION, OECD NUCLEAR ENERGY AGENCY, PAN AMERICAN HEALTH ORGANIZATION, UNITED NATIONS ENVIRONMENT PROGRAMME, WORLD HEALTH ORGANIZATION, Fundamental Safety Principles, IAEA Safety Standards Series No. SF-1, IAEA, Vienna (2006).
- [2] EUROPEAN COMMISSION, FOOD AND AGRICULTURE ORGANIZATION OF THE UNITED NATIONS, INTERNATIONAL ATOMIC ENERGY AGENCY, INTERNATIONAL LABOUR ORGANIZATION, OECD NUCLEAR ENERGY AGENCY, PAN AMERICAN HEALTH ORGANIZATION, UNITED NATIONS ENVIRONMENT PROGRAMME, WORLD HEALTH ORGANIZATION Radiation Protection and Safety of Radiation Sources: International Basic Safety Standards, IAEA Safety Standards Series No. GSR Part 3, IAEA, Vienna (2014).
- [3] INTERNATIONAL ATOMIC ENERGY AGENCY, Governmental, Legal and Regulatory Framework for Safety, IAEA Safety Standards Series No. GSR Part 1 (Rev. 1), IAEA, Vienna (2016).
- [4] INTERNATIONAL ATOMIC ENERGY AGENCY, Leadership and Management for Safety, IAEA Safety Standards Series No. GSR Part 2, IAEA, Vienna (2016).
- [5] INTERNATIONAL ATOMIC ENERGY AGENCY, Advisory Material for the IAEA Regulations for the Safe Transport of Radioactive Material (2012 Edition), IAEA Safety Standards Series No. SSG-26, IAEA, Vienna (2014). (A revision of this publication is in preparation.)
- [6] INTERNATIONAL ATOMIC ENERGY AGENCY, Planning and Preparing for Emergency Response to Transport Accidents Involving Radioactive Material, IAEA Safety Standards Series No. TS-G-1.2 (ST-3), IAEA, Vienna (2002). (A revision of this publication is in preparation.)
- [7] INTERNATIONAL ATOMIC ENERGY AGENCY, Compliance Assurance for the Safe Transport of Radioactive Material, IAEA Safety Standards Series No. TS-G-1.5, IAEA, Vienna (2009).
- [8] INTERNATIONAL ATOMIC ENERGY AGENCY, The Management System for the Safe Transport of Radioactive Material, IAEA Safety Standards Series No. TS-G-1.4, IAEA, Vienna (2008).

REFERENCES

- [9] INTERNATIONAL ATOMIC ENERGY AGENCY, Radiation Protection Programmes for the Transport of Radioactive Material, IAEA Safety Standards Series No. TS-G-1.3, IAEA, Vienna (2007).
- [10] INTERNATIONAL ATOMIC ENERGY AGENCY, Schedules of Provisions of the IAEA Regulations for the Safe Transport of Radioactive Material (2012 Edition), IAEA Safety Standards Series No. SSG-33, IAEA, Vienna (2015). (A revision of this publication is in preparation.)
- [11] FOOD AND AGRICULTURE ORGANIZATION OF THE UNITED NATIONS, INTERNATIONAL ATOMIC ENERGY AGENCY, INTERNATIONAL CIVIL AVIATION ORGANIZATION, INTERNATIONAL LABOUR ORGANIZATION, INTERNATIONAL MARITIME ORGANIZATION, INTERPOL, OECD NUCLEAR ENERGY AGENCY, PAN AMERICAN HEALTH ORGANIZATION, PREPARATORY COMMISSION FOR THE COMPREHENSIVE NUCLEAR-TEST-BAN TREATY ORGANIZATION, UNITED NATIONS ENVIRONMENT PROGRAMME, UNITED NATIONS OFFICE FOR THE COORDINATION OF HUMANITARIAN AFFAIRS, WORLD HEALTH ORGANIZATION, WORLD METEOROLOGICAL ORGANIZATION, Preparedness and Response for a Nuclear or Radiological Emergency, IAEA Safety Standards Series No. GSR Part 7, IAEA, Vienna (2015).
- [12] FOOD AND AGRICULTURE ORGANIZATION OF THE UNITED NATIONS, INTERNATIONAL ATOMIC ENERGY AGENCY, INTERNATIONAL LABOUR OFFICE, PAN AMERICAN HEALTH ORGANIZATION, WORLD HEALTH ORGANIZATION, Criteria for Use in Preparedness and Response for a Nuclear or Radiological Emergency, IAEA Safety Standards Series No. GSG-2, IAEA, Vienna (2011).
- [13] FOOD AND AGRICULTURE ORGANIZATION OF THE UNITED NATIONS, INTERNATIONAL ATOMIC ENERGY AGENCY, INTERNATIONAL LABOUR OFFICE, PAN AMERICAN HEALTH ORGANIZATION, UNITED NATIONS OFFICE FOR THE COORDINATION OF HUMANITARIAN AFFAIRS, WORLD HEALTH ORGANIZATION, Arrangements for Preparedness for a Nuclear or Radiological Emergency, IAEA Safety Standards Series No. GS-G-2.1, IAEA, Vienna (2007).
- [14] FOOD AND AGRICULTURE ORGANIZATION OF THE UNITED NATIONS, INTERNATIONAL ATOMIC ENERGY AGENCY, INTERNATIONAL CIVIL AVIATION ORGANIZATION, INTERNATIONAL LABOUR OFFICE, INTERNATIONAL MARITIME ORGANIZATION, INTERPOL, UNITED NATIONS OFFICE FOR THE COORDINATION OF HUMANITARIAN AFFAIRS, WORLD HEALTH ORGANIZATION, WORLD METEOROLOGICAL ORGANIZATION, Arrangements for the Termination of a Nuclear or Radiological Emergency, IAEA Safety Standards Series No. GSG-11, IAEA, Vienna (2018).
- [15] INTERNATIONAL MARITIME ORGANIZATION, International Maritime Dangerous Goods (IMDG) Code, IMO, London (2014).
- [16] INTERNATIONAL ORGANIZATION FOR STANDARDIZATION, Radiation Protection — Sealed Radioactive Sources — Leakage Test Methods, ISO 9978:1992, ISO, Geneva (1992).

REFERENCES

- [17] UNITED NATIONS, Recommendations on the Transport of Dangerous Goods, Model Regulations, ST/SG/AC.10/1/Rev.19, 2 vols, UN, New York and Geneva (2015).
- [18] INTERNATIONAL ORGANIZATION FOR STANDARDIZATION, Series 1 Freight Containers — Specifications and Testing — Part 1: General Cargo Containers for General Purposes, ISO 1496-1:1990, ISO, Geneva (1990); and subsequent Amendments 1:1993, 2:1998, 3:2005, 4:2006, 5:2006 and ISO 1496-1:2013.
- [19] INTERNATIONAL ORGANIZATION FOR STANDARDIZATION, Nuclear Energy — Packaging of Uranium Hexafluoride (UF₆) for Transport, ISO 7195:2005, ISO, Geneva (2005).
- [20] INTERNATIONAL ORGANIZATION FOR STANDARDIZATION, Radiological Protection — Sealed Radioactive Sources — General Requirements and Classification, ISO 2919:2012, ISO, Geneva (2012).

Annex I

SUMMARY OF APPROVAL AND PRIOR NOTIFICATION REQUIREMENTS

This summary reflects the contents of the Regulations for the Safe Transport of Radioactive Material (2018 Edition). The user's attention is called to the fact that there may be deviations (exceptions, additions, etc.) relative to:

- (a) National regulations relating to safety;
- (b) *Carrier* restrictions;
- (c) National regulations relating to security, physical protection, liability, insurance, pre-notification and/or routing and import/export/transit licensing.¹

¹ In particular, additional measures are taken to provide appropriate physical protection in the transport of nuclear material and to prevent acts without lawful authority that constitute the receipt, possession, use, transfer, alteration, disposal or dispersal of nuclear material and which cause or are likely to cause, death or serious injury to any person or substantial damage to property (see Refs [I-1] to [I-8]).

ANNEX I

ANNEX I: SUMMARY OF APPROVAL AND PRIOR NOTIFICATION REQUIREMENTS (Part 1)

Key paragraphs in the Regulations	Class of <i>package</i> or material	Competent authority approval required		Consignor required to notify country of origin and countries en route ^a of each <i>shipment</i>
		Country of origin	Countries en route ^a	
	<i>Excepted package</i> ^{b,c}	No	No	No
	<i>LSA material</i> ^{c,d,e} and <i>SCO-I</i> ^{c,e} and <i>SCO-II</i> ^{c,e} — Type <i>IP-1</i> , — Type <i>IP-2</i> or — Type <i>IP-3</i>	No	No	No
	<i>Type A</i> ^{c,d,e}	No	No	No
520, 825, 826	<i>SCO-III</i> — <i>Shipment</i>	Yes	Yes	No

^a Countries *through or into* which (but not over which) the *consignment* is transported (see para. 204 of the Regulations).

^b For international transport by post, the *consignment* shall be deposited with the postal service only by *consignors* authorized by the national authority.

^c If the *radioactive contents* are *fissile material* excepted under para. 417(f) of the Regulations, *multilateral approval* shall be required (see para. 805 of the Regulations).

^d If the *radioactive contents* are uranium hexafluoride in quantities of 0.1 kg or more, the *approval* requirements for *packages* containing it shall additionally apply (see paras 802 and 807 of the Regulations).

^e If the *radioactive contents* are *fissile material* that is not excepted from the requirements for *packages* containing *fissile material*, then the *approval* requirements in paras 814, 825 and 826 of the Regulations shall additionally apply.

SUMMARY OF APPROVAL AND PRIOR NOTIFICATION REQUIREMENTS

ANNEX I: SUMMARY OF APPROVAL AND PRIOR NOTIFICATION REQUIREMENTS (Part 2)

Key paragraphs in the Regulations	Class of <i>package</i> or material	<i>Competent authority approval required</i>		<i>Consignor required to notify country of origin and countries en route ^a of each shipment</i>
		Country of origin	Countries en route ^a	
	<i>Type B(U)</i> ^{b,c,d}			
808	— <i>Package design</i>	Yes	No ^e	
559, 560, 825, 826	— <i>Shipment</i>	No	No	(see Notes 1 and 2)
	<i>Type B(M)</i> ^{b,c,e}			
811	— <i>Package design</i>	Yes	Yes	Yes
559, 560, 825, 826	— <i>Shipment</i>	(see Note 3)	(see Note 3)	(see Note 1)
	<i>Type C</i> ^{b,c,d}			
808	— <i>Package design</i>	Yes	No	
559, 560, 825, 826	— <i>Shipment</i>	No	No	(see Notes 1 and 2)

^a Countries *through or into* which (but not over which) the *consignment* is transported (see para. 204 of the Regulations).

^b If the *radioactive contents* are *fissile material* that is not excepted from the requirements for *packages* containing *fissile material*, then the *approval* requirements in paras 814, 825 and 826 of the Regulations shall additionally apply.

^c If the *radioactive contents* are uranium hexafluoride in quantities of 0.1 kg or more, the *approval* requirements for *packages* containing it shall additionally apply (see paras 802 and 807 of the Regulations).

^d If the *radioactive contents* are *fissile material* excepted under para. 417(f) of the Regulations, *multilateral approval* shall be required (see para. 805 of the Regulations).

^e If the *radioactive contents* are *low dispersible radioactive material* and the *package* is to be shipped by air, *multilateral approval* of the *package design* is required (see para. 808(b) of the Regulations).

Note 1: Before the first *shipment* of any *package* requiring *competent authority approval* of the *design*, the *consignor* shall ensure that a copy of the certificate of *approval* for that *design* has been submitted to the *competent authority* of each country (see para. 557 of the Regulations).

Note 2: Notification is required if the *radioactive contents* exceed 3000A₁ or 3000A₂ or 1000 TBq, whichever is the lower (see para. 558 of the Regulations).

Note 3: *Multilateral approval* of *shipment* required if the *radioactive contents* exceed 3000A₁ or 3000A₂ or 1000 TBq, whichever is the lower, or if controlled intermittent venting is allowed (see paras 825 and 826 of the Regulations).

ANNEX I

ANNEX I: SUMMARY OF APPROVAL AND PRIOR NOTIFICATION REQUIREMENTS (Part 3)

Key paragraphs in the Regulations	Class of <i>package</i> or material	<i>Competent authority approval required</i>		<i>Consignor</i> required to notify country of origin and countries en route ^a of each <i>shipment</i>
		Country of origin	Countries en route ^a	
	<i>Packages for fissile material</i>			
814	— <i>Package design</i>	Yes ^b	Yes ^b	
825, 826	— <i>Shipment</i>			
	Σ <i>CSI</i> ≤ 50	No	No	(see Notes 1 and 2)
	Σ <i>CSI</i> > 50	Yes	Yes	(see Notes 1 and 2)
	<i>Packages containing 0.1 kg or more of uranium hexafluoride^d</i>			
807	— <i>Package design</i>	Yes	Yes for H(M)/ no for H(U)	
825, 826	— <i>Shipment</i>	No ^c	No ^c	(see Notes 1 and 2)

^a Countries *through or into* which (but not over which) the *consignment* is transported (see para. 204 of the Regulations).

^b *Designs of packages containing fissile material* may also require *approval* in respect of one of the other items in Annex I.

^c *Shipments* may, however, require *approval* in respect of one of the other items in Annex I.

^d If the *radioactive contents* are *fissile material* excepted under para. 417(f) of the Regulations, *multilateral approval* shall be required (see para. 805 of the Regulations).

Note 1: The *multilateral approval* requirement for *fissile packages*, and for some uranium hexafluoride *packages*, automatically satisfies the requirement of para. 557 of the Regulations.

Note 2: Notification is required if the *radioactive contents* exceed 3000A₁ or 3000A₂ or 1000 TBq, whichever is the lower (see para. 558 of the Regulations).

SUMMARY OF APPROVAL AND PRIOR NOTIFICATION REQUIREMENTS

ANNEX I: SUMMARY OF APPROVAL AND PRIOR NOTIFICATION REQUIREMENTS (Part 4)

Key paragraphs in the Regulations	Class of <i>package</i> or material	<i>Competent authority approval</i> required		<i>Consignor</i> required to notify country of origin and countries en route ^a of each <i>shipment</i>
		Country of origin	Countries en route ^a	
<i>Special form radioactive material</i>				
803	— <i>Design</i>	Yes	No	No
825, 826	— <i>Shipment</i>	(see Note 1)	(see Note 1)	(see Note 1)
<i>Low dispersible radioactive material</i>				
803	— <i>Design</i>	Yes	Yes	No
825, 826	— <i>Shipment</i>	(see Note 1)	(see Note 1)	(see Note 1)
<i>Special arrangement</i>				
560, 802, 831	— <i>Shipment</i>	Yes	Yes	Yes
<i>Type B (U) packages for which design is approved under</i>				
820	— 1973 Regulations	Yes	Yes	(see Note 2)
820	— 1985 Regulations	Yes	Yes	(see Note 2)
805	<i>Fissile material</i> excepted from “FISSILE” classification, in accordance with para. 606	Yes	Yes	No
817	Exempt <i>consignment</i> of instruments or articles	Yes	Yes	No

^a Countries *through or into* which (but not over which) the *consignment* is transported (see para. 204 of the Regulations).

Note 1: See *approval* and prior notification requirements for the applicable *package*.

Note 2: Before the first *shipment* of any *package* requiring *competent authority approval* of the *design*, the *consignor* shall ensure that a copy of the certificate of *approval* for that *design* has been submitted to the *competent authority* of each country (see para. 557 of the Regulations).

REFERENCES TO ANNEX I

- [I-1] Convention on the Physical Protection of Nuclear Material, INFCIRC/274/Rev.1, IAEA, Vienna (1980).
- [I-2] Amendment to the Convention on the Physical Protection of Nuclear Material, GOV/INF/2005/10-GC(49)/INF/6, IAEA, Vienna (2005).
- [I-3] INTERNATIONAL ATOMIC ENERGY AGENCY, Nuclear Security Recommendations on Physical Protection of Nuclear Material and Nuclear Facilities (INFCIRC/225/Revision 5), IAEA Nuclear Security Series No. 13, IAEA, Vienna (2011).
- [I-4] INTERNATIONAL ATOMIC ENERGY AGENCY, Physical Protection of Nuclear Material and Nuclear Facilities, IAEA Nuclear Security Series No. 27-G, IAEA, Vienna (2018).
- [I-5] INTERNATIONAL ATOMIC ENERGY AGENCY, Security in the Transport of Radioactive Material, IAEA Nuclear Security Series No. 9, IAEA, Vienna (2008).
- [I-6] INTERNATIONAL ATOMIC ENERGY AGENCY, Code of Conduct on the Safety and Security of Radioactive Sources, IAEA, Vienna (2004).
- [I-7] INTERNATIONAL ATOMIC ENERGY AGENCY, Guidance on the Import and Export of Radioactive Sources, IAEA, Vienna (2012).
- [I-8] INTERNATIONAL ATOMIC ENERGY AGENCY, Security of Nuclear Material in Transport, IAEA Nuclear Security Series No. 26-G, IAEA, Vienna (2015).

Annex II

CONVERSION FACTORS AND PREFIXES

This edition of the Regulations for the Safe Transport of Radioactive Material uses the International System of Units (SI). The conversion factors for non-SI units are:

RADIATION UNITS

Activity in becquerel (Bq) or curie (Ci)

$$1 \text{ Ci} = 3.7 \times 10^{10} \text{ Bq}$$

$$1 \text{ Bq} = 2.7 \times 10^{-11} \text{ Ci}$$

Dose equivalent in sievert (Sv) or rem

$$1 \text{ rem} = 1.0 \times 10^{-2} \text{ Sv}$$

$$1 \text{ Sv} = 100 \text{ rem}$$

PRESSURE

Pressure in pascal (Pa) or (kgf/cm²)

$$1 \text{ kgf/cm}^2 = 9.806\,808 \times 10^4 \text{ Pa}$$

$$1 \text{ Pa} = 1.020 \times 10^{-5} \text{ kgf/cm}^2$$

CONDUCTIVITY

Conductivity in siemens per metre (S/m) or (mho/cm)

$$10 \text{ } \mu\text{mho/cm} = 1 \text{ mS/m}$$

or

$$1 \text{ mho/cm} = 100 \text{ S/m}$$

$$1 \text{ S/m} = 10^{-2} \text{ mho/cm}$$

ANNEX II

SI PREFIXES AND SYMBOLS

The decimal multiples and submultiples of a unit may be formed by prefixes or symbols, having the following meanings, placed before the name or symbol of the unit:

Multiplying factor	Prefix	Symbol
1 000 000 000 000 000 000 = 10^{18}	exa	E
1 000 000 000 000 000 = 10^{15}	peta	P
1 000 000 000 000 = 10^{12}	tera	T
1 000 000 000 = 10^9	giga	G
1 000 000 = 10^6	mega	M
1 000 = 10^3	kilo	k
100 = 10^2	hecto	h
10 = 10^1	deca	da
0.1 = 10^{-1}	deci	d
0.01 = 10^{-2}	centi	c
0.001 = 10^{-3}	milli	m
0.000 001 = 10^{-6}	micro	μ
0.000 000 001 = 10^{-9}	nano	n
0.000 000 000 001 = 10^{-12}	pico	p
0.000 000 000 000 001 = 10^{-15}	femto	f
0.000 000 000 000 000 001 = 10^{-18}	atto	a

Annex III

SUMMARY OF CONSIGNMENTS REQUIRING EXCLUSIVE USE

The following *consignments* are required to be shipped under *exclusive use*:

- (a) Unpackaged *LSA-I material*, *SCO-I* and *SCO-III* (see para. 520);
- (b) Liquid *LSA-I material* in a *Type IP-1 package* (see para. 521 and Table 5);
- (c) Gaseous and/or liquid *LSA-II material* in a *Type IP-2 package* (see para. 521 and Table 5);
- (d) *LSA-III material* in a *Type IP-2 package* (see para. 521 and Table 5);
- (e) *Packages* or *overpacks* having an individual *TI* greater than 10 or a *consignment CSI* greater than 50 (see paras 526 and 567);
- (f) *Packages* or *overpacks* having the maximum *dose rate* at any point on the external surfaces that exceed 2 mSv/h (see para. 527);
- (g) Loaded *conveyance* or *large freight containers* with a total sum of *TI* exceeding the values given in Table 10 (see para. 566(a));
- (h) Loaded *conveyances* or *large freight containers* with a total sum of *CSI* exceeding the values given in Table 11 for “not under *exclusive use*” (see para. 569);
- (i) *Type B(U)*, *Type B(M)* or *Type C package* whose temperature of accessible surfaces exceeds 50°C when subject to an ambient temperature of 38°C in the absence of insolation (see para. 654);
- (j) Up to 45 g of *fissile nuclides* on a *conveyance*, either packaged or unpackaged, in accordance with the provisions of paras 417(e) and 520(d);
- (k) *Packages* containing *fissile material* classified as non-fissile or fissile-excepted under para. 417(a)(i) or (iii) of the 2009 Edition of these Regulations (see para. 822).

CONTRIBUTORS TO DRAFTING AND REVIEW (2018)

Aceña, V.	Nuclear Safety Council, Spain
Alcocer Ávila, M.E.	National Commission for Nuclear Safety and Safeguards, Mexico
Alvano, P.	National Institute for Environmental Protection and Research, Italy
Basic, S.	Serbian Radiation Protection and Nuclear Safety Agency, Serbia
Börst, F.-M.	Federal Office for Radiation Protection, Germany
Boyle, R.	US Department of Transportation, United States of America
Brajic, B.	Serbian Radiation Protection and Nuclear Safety Agency, Serbia
Buchelnikov, A.	State Atomic Energy Corporation “ROSATOM”, Russian Federation
Budu, M.E.	Sosny Research and Development Company, Russian Federation
Bujnova, A.	Ministry of Transport and Construction of the Slovak Republic, Slovakia
Butchins, L.	Office of Nuclear Regulation, United Kingdom
Capadona, N.	International Atomic Energy Agency
Charbonneau, S.	Nordion, Canada
Charrette, M.A.	Cameco Corporation, Canada
Cordier, N.	Nuclear Safety Authority, France
Davidson, I.	Office for Nuclear Regulation, United Kingdom
Desnoyers, B.	World Nuclear Transport Institute
Doner, K.	National Atomic Energy Agency, Poland

CONTRIBUTORS TO DRAFTING AND REVIEW (2018)

Droste, B.	Federal Institute for Materials Research and Testing, Germany
Ducháček, V.	State Office for Nuclear Safety, Czech Republic
Elechosa, C.F.	Nuclear Regulatory Authority, Argentina
Ellappan, S.	Bhabha Atomic Research Centre, India
Ershov, V.N.	State Atomic Energy Corporation “Rosatom”, Russian Federation
Faille, S.	Canadian Nuclear Safety Commission, Canada
Fasten, C.	Federal Office for Radiation Protection, Germany
Ferran, G.	Nuclear Safety Authority, France
Fulford, G.	Nordion, Canada
Georgievska-Dimitrievski, B.	Radiation Safety Directorate, the former Yugoslav Republic of Macedonia
Haidl, E.	Federal Ministry for Transport, Innovation and Technology, Austria
Hellsten, S.	Radiation and Nuclear Safety Authority, Finland
Hinrichsen, P.J.	National Nuclear Regulator, South Africa
Hirose, M.	Nuclear Regulation Authority, Japan
Hornkjøl, S.	Norwegian Radiation Protection Authority, Norway
Ilijas, B.	State Office for Radiological and Nuclear Safety, Croatia
Ito, D.	World Nuclear Transport Institute
Karasinski, C.	TRANSNUBEL, Belgium
Kervella, O.	United Nations Economic Commission for Europe
Kirchnawy, F.	Federal Ministry for Transport, Innovation and Technology, Austria
Kirkin, A.	Scientific and Engineering Centre for Nuclear and Radiation Safety, Russian Federation

CONTRIBUTORS TO DRAFTING AND REVIEW (2018)

Koch, F.	Swiss Federal Nuclear Safety Inspectorate, Switzerland
Komann, S.-M.	Federal Institute for Materials Research and Testing, Germany
Konnai, A.	National Maritime Research Institute, Japan
Krochmaluk, J.	Institute for Radiological Protection and Nuclear Safety, France
Lizot, M.-T.	Institute for Radiological Protection and Nuclear Safety, France
Lourtie, G.	Federal Agency for Nuclear Control, Belgium
Malesys, P.	International Organization for Standardization
Moutarde, M.	Institute for Radiological Protection and Nuclear Safety, France
Muneer, M.	Pakistan Nuclear Regulatory Authority, Pakistan
Patko, A.	Nuclear Assurance Corp. International, United States of America
Petrová, I.	State Office for Nuclear Safety, Czech Republic
Phimister, I.	Nuclear Decommissioning Authority, United Kingdom
Presta, A.	World Nuclear Transport Institute
Quevedo Garcia, J.R.	National Nuclear Safety Centre, Cuba
Rakouth, M.	Maritime and Fluvial Port Agency of Madagascar, Madagascar
Reiche, I.	Federal Office for Radiation Protection, Germany
Riahi, A.	National Centre for Nuclear Science and Technology, Tunisia
Rooney, K.	International Civil Aviation Organization
Sáfár, J.	Hungarian Atomic Energy Authority, Hungary
Sahyun, A.	Brazilian Association of Nondestructive Tests and Inspection, Brazil

CONTRIBUTORS TO DRAFTING AND REVIEW (2018)

Saini, M.	Atomic Energy Regulatory Board, India
Sallit, G.	Office for Nuclear Regulation, United Kingdom
Sampson, M.	Nuclear Regulatory Commission, United States of America
Sert, G.	Institute for Radiological Protection and Nuclear Safety, France
Smith, A.	Office of Nuclear Regulation, United Kingdom
Spielmann, F.	World Nuclear Transport Institute
Takahashi, K.	Nuclear Regulation Authority, Japan
Tremblay, I.	Canadian Nuclear Safety Commission, Canada
Trivelloni, S.	National Institute for Environmental Protection and Research, Italy
Václav, J.	Nuclear Regulatory Authority of the Slovak Republic, Slovakia
van Aarle, J.	Axpo Power AG - Nuclear Energy, Switzerland
Wallin, M.L.	Swedish Radiation Safety Authority, Sweden
Whittingham, S.	International Atomic Energy Agency
Wille, F.	Federal Institute for Materials Research and Testing, Germany
Yagihashi, H.	Nuclear Regulation Authority, Japan
Yatsu, S.	Nuclear Regulation Authority, Japan
Zamora Martin, F.	Nuclear Safety Council, Spain
Zika, H.	Swedish Radiation Safety Authority, Sweden
Zimmermann, U.M.	Paul Scherrer Institute, Switzerland

Numerous other participants in Member States took part in the review and revision of this publication. Their invaluable contribution to the process is recognized.

INDEX

(by paragraph number)

Accident conditions: 106, 313, 403, 638, 673, 685, 726–730, 817

Activity limit: 111, 201, 231, 402, 403, 405, 411, 414, 422, 423, 802, 817–820, 832, 839

A_1 : 201, 402, 404, 405–407, 422, 429, 430, 433, 558, 825

A_2 : 201, 402–407, 409, 410, 422, 429, 430, 433, 522, 546, 558, 605, 659, 660, 671, 730, 825

Alternative activity limit: 403, 802, 817, 818, 832, 839

Air (transport by): 106, 217, 243, 410, 433, 527, 577–579, 581, 606, 619–623, 635, 652, 655, 683, 820

Ambient conditions: 616, 619, 620, 645, 653–657, 666, 670, 679, 703, 710, 711, 728, 812, 836, 838

Approval: 104, 111, 204, 205, 238, 306, 310, 403, 418, 431–433, 501, 503, 520, 530, 535, 541, 546, 557, 559, 560, 565, 570, 576, 634, 667, 679, 718, 801–820, 823–840

Basic Safety Standards (GSR Part 3): 101, 308, 403, 817

Carrier: 203, 206, 304, 309, 550, 554, 556, 584, 586–588, 836

Categories of *package*: 529, 530, 538, 540, 546, 563, 574

Certificate of *approval*: 418, 431–433, 501, 503, 530, 541, 546, 556, 557, 559–561, 565, 570, 679, 718, 801, 802, 804, 806, 807, 810, 813, 816, 818, 827, 828, 831–840

Competent authority: 104, 204, 205, 207–209, 238, 302, 306–310, 313, 315, 403, 431, 510, 530, 534, 535, 541, 546, 556–558, 565, 576, 583, 603, 640, 667, 668, 679, 711, 801, 802, 804, 806, 807, 810, 813, 815, 816, 818–820, 823, 824, 826, 827A, 828, 830–840

INDEX

Compliance assurance: 102, 105, 208, 307

Confinement system: 209, 501, 681, 838

Consignee: 210, 221, 309, 531, 546, 582, 585

Consignment: 203, 204, 210–212, 222, 236–238, 243, 305, 310, 402, 403, 405, 417, 423, 506, 525, 526, 536A, 541, 544, 546, 547, 553, 554, 556–559, 562, 564, 566, 567, 570, 572, 573, 576, 577, 580, 581, 583–586, 802, 803, 817, 818, 822, 827A, 829, 832, 836–839

Consignor: 211, 212, 221, 230, 304, 306, 309, 524, 531, 546–549, 554–558, 560, 561, 581, 801, 836–838

Containment: 104, 232, 501, 620, 650, 653, 725, 817

Containment system: 213, 229, 501, 503, 621, 632, 641–645, 647, 650, 660, 662, 663, 672, 680, 685, 714, 716, 724, 809, 838

Contamination: 107, 214–216, 309, 413, 427, 508–510, 512, 513, 520, 659, 671

Conveyance: 104, 217, 221, 411, 414, 509, 510, 512–514, 520, 522, 524, 525, 546, 554, 566, 569, 570, 607, 809, 822, 825, 827, 836, 837

Cooling system: 229, 578, 661

Criticality: 101, 104, 209, 501, 673, 716, 836–838

Criticality safety index (CSI): 218, 525, 526, 541, 542, 546, 566–569, 674, 675, 686, 825, 836, 838

Customs: 582

Dangerous goods: 110, 506, 507, 546, 550, 551, 562, 626–628, 630

Deck area: 217, 219, 825

Decontamination: 505, 511, 513, 610

Dose limits: 301

INDEX

Dose rate: 104, 220A, 233, 309, 411, 414, 423, 510, 513, 516, 517, 523, 524, 527–529, 566, 573, 575, 579, 605, 617, 624, 626–630, 648, 659, 671, 817

Emergency: 102, 104, 304, 305, 309, 313, 520, 554, 836–838

Empty packaging: 422, 427, 509, 581

Excepted package: 231, 419, 422–427, 515, 516, 543, 622, 819

Exclusive use: 221, 514, 520, 526–529, 537, 544, 546, 566, 567, 570, 572, 573, 575, 577, 654, 655, 822

Fissile material: 209, 218, 220, 222, 231, 409, 417–419, 423, 424, 427, 501, 503, 518–520, 538, 540, 546, 559, 568–570, 606, 622, 631, 673–686, 716, 731–733, 802, 805, 806, 808, 811, 814–816, 820, 822, 825, 832, 833, 835–838

Freight container: 218, 221, 223, 244, 313, 505, 509, 514, 523–525, 529, 538–540, 542–544, 546, 551, 554, 562, 566, 568, 569, 571, 574, 629, 809, 825, 836, 837

Gas: 235, 242, 409, 605, 644, 651, 725

Heat: 104, 501, 554, 565, 603, 653, 704, 708, 728, 809, 836–838

Identification mark: 535, 546, 559, 804, 806, 807, 810, 813, 816, 818, 832–839

Industrial package (IP): 231, 517–524, 534, 623–630, 819, 832, 833

Insolation: 619, 654, 655, 657, 728, 812

Inspection: 302, 306, 503, 582, 801

Intermediate bulk container (IBC): 224, 505, 630

Label: 313, 427, 507, 530, 538–543, 545–547, 571, 574

Leaching: 603, 703, 704, 710–712

Leakage: 510, 603, 632, 634, 646, 650, 673, 680, 683, 704, 710, 711, 731–733

INDEX

Low dispersible radioactive material: 220, 225, 416, 433, 546, 559, 605, 665, 701, 703, 712, 802–804, 808, 811, 832, 834, 836–838

Low specific activity (LSA): 226, 244, 408–411, 517–523, 537, 540, 543, 544, 546, 566, 571, 572, 628

Maintenance: 104, 106, 680, 809, 837

Management system: 102, 105, 228, 306, 803, 805, 807, 809, 815, 817, 823, 827A, 834–838

Manufacture: 106, 306, 403, 422, 423, 426, 501, 534, 604, 640, 680, 713, 809, 819–821A, 823, 824, 827A, 836, 838

Mark: 313, 423, 424, 507, 530–537, 539, 545, 547, 581, 833

Mass: 240, 247, 417, 420, 425, 533, 540, 546, 559, 607, 609, 659, 674–676, 680, 685, 709, 722–724, 727, 735, 836–838

Maximum normal operating pressure: 229, 621, 663, 664, 670, 671, 809

Multilateral approval: 204, 310, 403, 520, 634, 718, 803, 805, 807, 808, 811, 814, 817, 820, 825, 829, 832, 833, 838, 840

N: 684–686

Normal conditions: 106, 403, 511, 638, 653, 673, 684, 719–725, 817

Notification: 557–560, 824

Operational controls: 229, 520, 578, 668, 812, 827, 830, 836–838

Other dangerous properties: 110, 507, 538, 618

Overpack: 218, 230, 244, 505, 509, 523–532, 538–540, 542, 546, 554, 562, 563, 565–569, 571, 573–575, 579, 825

Package design: 104, 220, 418, 420, 431, 433, 502, 504, 530, 534–536, 546, 557, 607, 672, 676–680, 801, 802, 807–816, 819–821A, 827, 832, 833, 838, 840

INDEX

Packaging: 104, 106, 111, 209, 213, 220, 224, 231, 232, 235, 313, 427, 501, 503, 505, 509, 531, 533–535, 581, 610, 614, 631, 639, 643, 647, 653, 665, 680, 681, 701, 718, 723, 809, 819–821A, 824, 827A, 833, 836–838

Placard: 313, 507, 543–545, 547, 571, 572

Post: 423, 424, 515, 580, 581

Pressure: 229, 420, 501, 503, 616, 621, 627, 628, 633, 634, 641, 645, 646, 662–664, 670, 671, 718, 729, 730, 809

Pressure relief: 633, 646, 662

Radiation exposure: 244, 301–303, 309, 311, 313, 562, 582

Radiation protection: 102, 104, 234, 301–304, 308, 311, 313, 403, 510, 520, 576, 603, 802, 817, 825

Rail (transport by): 106, 107, 217, 242, 248, 520, 527, 566, 571–573

Responsibility: 101, 103

Road (transport by): 106, 107, 217, 242, 248, 520, 527, 566, 571–574

Routine conditions: 106, 215, 424, 508, 520, 566, 573, 613, 616, 617, 627–629, 673, 682, 817

Segregation: 313, 506, 562, 563, 568, 569

Serial number: 535, 824

Shielding: 226, 409, 501, 520, 617, 627, 628, 647, 653, 659, 671, 716, 817

Shipment: 106, 204, 221, 237, 501–503, 520, 524, 530, 546, 557–561, 573, 576, 677, 680, 802, 803, 805, 809, 825–828, 830–838, 840

Shipping name: 530, 536A, 546, 547

Special arrangement: 238, 310, 434, 527, 529, 546, 558, 575, 579, 802, 829–833, 836

INDEX

Special form radioactive material: 201, 220, 239, 415, 429, 430, 433, 546, 559, 602–604, 642, 659, 701, 704, 709, 802–804, 823, 832, 834, 836–838

Specific activity: 226, 240, 409

Storage: 106, 503, 505, 507, 562, 565, 568, 569, 809

Stowage: 219, 230, 313, 554, 564, 565, 566, 576, 809, 836–838

Surface contaminated object (SCO): 241, 244, 412–414, 517–523, 537, 540, 543, 544, 546, 571, 572, 825, 827A

Tank: 242, 505, 523, 538, 539, 543, 544, 551, 571, 627, 628

Tank container: 242

Tank vehicle: 242

Temperature: 229, 420, 503, 616, 619, 620, 639, 649, 654–656, 666, 670, 673, 679, 703, 708–711, 728, 812, 836, 838

Test(s): 111, 224, 503, 520, 603, 605, 624, 626–630, 632, 634, 648, 650, 651, 653, 655, 658–660, 662, 663, 670–672, 674, 678, 680–685, 701–713, 716–737, 803, 805, 809, 817

Tie-down: 638

Transport document(s): 313, 540, 545–547, 552–555, 584–588

Transport index (TI): 244, 523, 524, 524A, 526, 529, 540, 546, 566, 567

Type A package: 231, 428–430, 534, 635–651, 725, 819, 832

Type B(M) package: 231, 431–433, 501, 503, 535, 536, 558, 577, 578, 667, 668, 730, 802, 811–813, 825, 832, 833, 838

Type B(U) package: 231, 431–433, 501, 503, 535, 536, 558, 652–666, 730, 802, 808–810, 812, 832

Type C package: 231, 431, 432, 501, 503, 535, 536, 558, 669–672, 683, 730, 734–737, 802, 808–810, 832

INDEX

Ullage: 420, 649

Unilateral approval: 205, 503, 803, 807, 808, 823, 832

UN number: 401, 419, 530, 536A, 544, 546, 572

Unpackaged: 222, 244, 417, 423, 514, 520, 522, 523, 543, 544, 562, 570–572, 673

Uranium hexafluoride: 231, 419, 420, 422, 425, 523, 580, 581, 631–634, 680, 718, 802, 807, 819, 832, 833, 838

Vehicle: 217, 219, 223, 242, 248, 313, 534, 551, 552, 566, 571–575, 832

Venting: 229, 578, 668, 825

Vessel: 217, 219, 249, 527, 575, 576, 802, 825

Water: 409, 536, 603, 605, 611, 660, 672, 673, 680, 681, 683–685, 703, 710, 711, 719–721, 726, 729–733, 836, 838

Waterway (transport by): 106, 217, 249, 520, 522

Schedule B – Competent authorities

Table B1: List of Australian Competent Authorities for the purpose of this Code

Jurisdiction	Contact	Competent authority
Commonwealth	Chief Executive Officer ARPANSA PO Box 655 Miranda NSW 1490 Email: info@arpansa.gov.au Tel: (02) 9541 8333 Fax: (02) 9541 8314	Australian Radiation Protection and Nuclear Safety Agency (ARPANSA)
Australian Capital Territory	Director, Environment and Radiation Safety Health Protection Service ACT Health Directorate Locked Bag 5005 Weston Creek ACT 2611 Email: hps@act.gov.au Tel: (02) 5124 9700 Fax: (02) 5124 5554	ACT Radiation Council
New South Wales	Manager Hazardous Materials, Chemicals and Radiation Environment Protection Authority PO Box A290 Sydney South NSW 1232 Email: radiation@epa.nsw.gov.au Tel: (02) 9995 5959 Fax: (02) 9995 6603	Environment Protection Authority
Northern Territory (i) for radioactive ores and concentrates	Chief Inspector – Radioactive Ores and Concentrates (Packaging and Transport) NT Worksafe GPO Box 1722 Darwin NT 0801 Email: Ntworksafe@nt.gov.au Tel: 1800 019 115	Work Health Authority
(ii) for all other radioactive substances	Manager Radiation Protection Radiation Protection Section Department of Health GPO Box 40596	Department of Health

Jurisdiction	Contact	Competent authority
	Casuarina NT 0811 Email: envirohealth@nt.gov.au Tel: (08) 8922 7152 Fax: (08) 8922 7334	
Queensland	Director, Radiation Health Queensland Health PO Box 2368 Fortitude Valley BC QLD 4006 Email: Contact Radiation Health Tel: (07) 3328 9200	Queensland Health
South Australia	Manager, Radiation Protection Environment Protection Authority GPO Box 2607 Adelaide SA 5001 Email: radiationprotection@epa.sa.gov.au Tel: (08) 8463 7826 Fax: (08) 8124 4671	Minister for Environment & Conservation
Tasmania	Principal Health Physicist, Radiation Protection Unit Department of Health and Human Services GPO Box 125 Hobart TAS 7001 Email: radiation.protection@dhhs.tas.gov.au Tel: (03) 6222 7256 Fax: (03) 6222 7257	Director of Public Health
Victoria	Team Leader, Radiation Safety Department of Health GPO Box 4541 Melbourne VIC 3001 Email: radiation.safety@health.vic.gov.au Tel: 1300 767 469 Fax: 1300 769 274	Secretary, Department of Health
Western Australia	Secretary Radiological Council Locked Bag 2006 PO Nedlands WA 6009 Email: radiation.health@health.wa.gov.au Tel: (08) 9222 2000	Radiological Council

Table B2: Australian Competent Authority for the transport of radioactive material by air or sea

Mode of transport	Contact	Competent authority
Air	Director, Aviation Safety Civil Aviation Safety Authority GPO Box 2005 Canberra ACT 2601 Email: dg@casa.gov.au Tel: +61 131 757 or 1300 851 857 Fax: (02) 6217 1300	Civil Aviation Safety Authority
Sea (international and interstate)	Manager, Ship Inspections Maritime Operations Australian Maritime Safety Authority GPO Box 2181 Canberra ACT 2601 Email: MOCBRSHIPMAN@amsa.gov.au Tel: (02) 6279 5048 Fax: (02) 6279 5058	Australian Maritime Safety Authority

Tables B1 and B2 were correct at the time of publication but are subject to change from time to time. For the most up-to-date list, the reader is advised to consult the ARPANSA website (www.arpansa.gov.au).